U.S. Livestock

Protocol | Version 4.0 | January 23, 2013

Errata + Protocol





U.S. Livestock Project Protocol Version 4.0 ERRATA AND CLARIFICATIONS

The Climate Action Reserve (Reserve) published its U.S. Livestock Project Protocol Version 4.0 (LSPP V4.0) in January 2013. While the Reserve intends for the LSPP V4.0 to be a complete, transparent document, it recognizes that correction of errors and clarifications will be necessary as the protocol is implemented and issues are identified. This document is an official record of all errata and clarifications applicable to the LSPP V4.0.¹

Per the Reserve's Program Manual, both errata and clarifications are considered effective on the date they are first posted on the Reserve website. The effective date of each erratum or clarification is clearly designated below. All listed and registered livestock projects must incorporate and adhere to these errata and clarifications when they undergo verification. The Reserve will incorporate both errata and clarifications into future versions of the protocol.

All project developers and verification bodies must refer to this document to ensure that the most current guidance is adhered to in project design and verification. Verification bodies shall refer to this document immediately prior to uploading any Verification Statement to assure all issues are properly addressed and incorporated into verification activities.

If you have any questions about the updates or clarifications in this document, please contact Policy at <u>policy@climateactionreserve.org</u> or (213) 891-1444 x3.

¹ See Section 4.3.4 of the Climate Action Reserve Program Manual for an explanation of the Reserve's policies on protocol errata and clarifications. "Errata" are issued to correct typographical errors. "Clarifications" are issued to ensure consistent interpretation and application of the protocol. For document management and program implementation purposes, both errata and clarifications are contained in this single document.

Errata and Clarifications (arranged by protocol section)

Secti	ion 33
1.	Regulatory Compliance at Centralized Digesters (CLARIFICATION – July 21, 2016) 3
Secti	ion 53
2.	Accounting for Methane Emissions during Temporary Project Shutdown (CLARIFICATION – October 29, 2013)
3.	Service Providers for Site-Specific Destruction Efficiency Testing (CLARIFICATION – January 21, 2014)
Secti	ion 65
4. 5.	Monitoring Operational Status (CLARIFICATION – October 29, 2013)
6. 7.	Meter Field Check Procedures (CLARIFICATION – October 29, 2013)
Арре	endix D7
8. 9.	Data Substitution when Operational Data are Missing (ERRATUM – October 29, 2013) 7 Data Substitution for Continuous Methane Data (CLARIFICATION – October 29, 2013). 8

Section 3

1. Regulatory Compliance at Centralized Digesters (CLARIFICATION – July 21, 2016)

Section: 3.6 (Regulatory Compliance)

Context: This section states that, where a verifier determines that project activities have caused a material violation, no CRTs will be issued during the period(s) when the violation occurred. The guidance in this section does not specify how to address regulatory compliance for projects where manure is received from multiple farms and managed in a centralized BCS.

It is unclear whether a violation with respect to one manure source facility would jeopardize the ability of the project to receive credit from emission reductions related to manure from other source facilities. It may be possible for an offset project at a centralized digester to have CRTs issued to it for manure from compliant manure source facilities during a period of time when one or more manure source facilities are materially noncompliant with a regulation.

Clarification: The following text shall be inserted on page 7, at the end of Section 3.6:

"With respect to projects that accept and manage manure from multiple, discrete source facilities (separate from the project BCS in both physical location and management), it may be possible for a project developer to demonstrate that a regulatory violation at one source facility does not affect the eligibility of the entire project under this section. Project developers should contact the Reserve to discuss potential regulatory non-compliance issues."

Section 5

2. Accounting for Methane Emissions during Temporary Project Shutdown (CLARIFICATION – October 29, 2013)

Section: 5.3 (Calculating Project Methane Emissions)

Context: The last full paragraph on page 24 reads: "Although not common under normal digester operation, it is possible that a venting event may occur due to catastrophic failure of digester cover materials, the digester vessel, or the gas collection system. In the event that a catastrophic system failure results in the venting of biogas, the quantity of methane released to the atmosphere shall be estimated according to Equation 5.7 below."

Equation 5.7 on page 26 provides guidance for calculating the quantity of methane released during a venting event, which is added to the total Project Methane Emissions from the BCS, as calculated in Equation 5.6. Equation 5.7 accounts for two releases of biogas: the initial release of biogas being stored in the digester, and then the daily release of additional gas that is generated in the digester until the gas collection system is functional.

The intent of the current guidance is to account for situations where the project digester continues to receive and treat manure, but the gas collection system is discovered to be compromised. In situations where the project digester has been shut down for longer periods of

time, biogas is typically released from the digester and then project manure directed to an anaerobic system (e.g. either the covers are taken off the digester or manure is diverted to open lagoons) that would meet the definition in Section 3.4. During such longer shutdowns, it has not been clear whether this entire period of time should be considered a venting event and, if so, how quantification of emissions should proceed.

Clarification: The following text shall be inserted between Equation 5.7 and Equation 5.8 on page 26:

"A venting event occurs when the project digester continues to process manure, but biogas is vented directly to the atmosphere (e.g. through a rip in a lagoon cover or a broken pipe). Projects that experience a venting event shall continue to use Equation 5.7 to calculate the resulting project methane emissions.

A project shutdown occurs when the project digester is no longer functional. This occurs when the project reverts to an open, uncontrolled, anaerobic manure treatment system (e.g. the manure is redirected to open, anaerobic lagoons, or the cover is completely removed from a covered lagoon digester and no heating or mixing occurs). A project shutdown is defined as a venting event on the day of the shutdown, and then a cessation of project operations until the BCS is once again operable.

In the case where the project BCS is shut down and the manure is treated in an open, uncontrolled, anaerobic system (meeting the definition in Section 3.4), the project scenario shall be assumed to be equal to the baseline scenario. In this case the project must quantify the release of stored biogas (MS_{BCS} in Equation 5.7) at the time that the system is shut down, but not the subsequent daily release of biogas from the open lagoons. In these situations the project will cease quantification of emission reductions until the BCS is once again operational."

3. Service Providers for Site-Specific Destruction Efficiency Testing (CLARIFICATION – January 21, 2014)

Section: 5.3 (Calculating Project Methane Emissions)

Context: Footnote 19 on page 25 provides guidelines for service provider accreditation. It is not clear what specific options are available and permissible for projects located in a state or locality which does not have an accreditation program for source test service providers. Footnote 26 on page 29 and the first full paragraph on page 69 in Appendix B contain similar language.

Clarification: The intent of this requirement is to ensure that any source testing conducted for the determination of a site-specific value for methane destruction efficiency is of a quality that would be acceptable for compliance by a regulatory body. The following text shall replace the last sentence of footnote 19 on page 25, of footnote 26 on page 29, and of the first full paragraph on page 69 of Appendix B:

"If neither the state nor locality relevant to the project site offer accreditation for source testing service providers, projects may use an accredited service provider from another U.S. state or domestic locality. Alternatively, projects may choose a non-accredited service provider, under the following conditions: 1) the service provider must provide verifiable evidence of prior testing which was accepted for compliance by a domestic regulatory agency, and 2) the prior testing procedures must be substantially similar to

the procedures used for determining methane destruction efficiency for the project destruction device(s)."

Section 6

4. Monitoring Operational Status (CLARIFICATION – October 29, 2013)

Section: 6.2 (Biogas Control System Monitoring Requirements)

Context: The first and second paragraphs of page 35 in Section 6.2 states that "[o]perational activity of the destruction devices shall be monitored and documented at least hourly to ensure actual methane destruction. ... If for any reason the destruction device or the operational monitoring equipment...is inoperable, then all metered biogas going to the particular device shall be assumed to be released to atmosphere...[and] the destruction efficiency of the device must be assumed to be zero."

Certain types of destruction devices, such as internal combustion engines and most large boiler systems, are designed in such a way that gas may not flow through the device if it is not operational. It has not been clear how the requirements of Section 6.2 apply to these devices.

Clarification: The first sentence of the first paragraph on page 35 shall be read to apply to all destruction devices in use during the reporting period. The paragraph on page 34 of Section 6.2 starting, "[a] single flow meter may be used...," shall not be construed to relax the requirement for hourly operational data for all destruction devices. Rather, that paragraph is allowing a specific metering arrangement during periods when one or more devices are known to be not operating. All destruction devices must have their operational status monitored and recorded at least hourly. If these data are missing or never recorded for a particular device, that device will be assumed to be not operating and will be assigned a destruction efficiency of zero for all flow data that are assigned to that device.

5. Instrument QA/QC for a Stationary Flow Meter in Use for 60 Days or More that is Removed and Not Reinstalled During the Same Reporting Period (CLARIFICATION – July 19, 2023)

Section: 6.3 (Biogas Measurement Instrument QA/QC)

Context: Section 6.2 of the protocol states that:

"If a stationary meter that was in use for 60 days or more is removed and not reinstalled during a reporting period, that meter shall either be field-checked for calibration accuracy prior to removal or calibrated (with percent drift documented) by the manufacturer or a certified calibration service prior to quantification of emission reductions for that reporting period." The intent of the requirement above is to ensure accurate flow meter data is being recorded and used for emission reduction calculations. However, the timeline and requirement to perform a field-check for calibration accuracy or calibration by the manufacturer is unclear.

Clarification: The following language has replaced the requirement mentioned above:

"If a stationary meter that was in use for 60 days or more is removed and not reinstalled during a reporting period, that meter shall either be:

- field-checked for calibration accuracy within 2 months of removal; or
- calibrated (with percent drift documented) by the manufacturer or a certified calibration service (with as-found results recorded) no more than 12 months prior to use of the meter to quantify emission reductions and no later than the commencement of verification activities for the relevant reporting period.

6. Meter Field Check Procedures (CLARIFICATION – October 29, 2013)

Section: 6.3 (Biogas Measurement Instrument QA/QC)

Context: The second paragraph below the first bulleted list of page 36 in Section 6.3 states that "[i]f the field check on a piece of equipment reveals accuracy outside of a +/- 5% threshold, calibration by the manufacturer or a certified service provider is required for that piece of equipment..."

Certain types of biogas flow meters and methane analyzers are susceptible to measurement drift due to buildup of moisture or contaminants on the metering sensor, even if the equipment itself is not out of calibration. If the as-found condition of the meter is outside of the accuracy threshold, but the as-left condition (after cleaning) is within the accuracy threshold, it is not clear whether a full calibration is still required for this piece of equipment. In some cases the manufacturer provides specific guidance to this effect.

Clarification: The following text shall be inserted after the second paragraph following the bulleted list on page 36:

"The as-found condition (percent drift) of a field check must always be recorded. If the meter is found to be measuring outside of the +/- 5% threshold for accuracy, the data must be adjusted for the period beginning with the last successful field check or calibration event up until the meter is confirmed to be in calibration. If, at the time of the failed field check, the meter is cleaned and checked again, with the as-left condition found to be within the accuracy threshold, a full calibration is not required for that piece of equipment. This shall be considered a failed field check, followed by a successful field check. However, if the as-left condition remains outside of the +/- 5% accuracy threshold, calibration is required by the manufacturer or a certified service provider for that piece of equipment."

7. Methane Analyzer Factory Calibrations (CLARIFICATION – November 16, 2017)

Section: 6.3 (Biogas Measurement Instrument QA/QC)

Context: The fourth bullet in the list at the beginning of this section (page 36) states that "[all gas flow meters and continuous methane analyzers must be] calibrated by the manufacturer or a certified calibration service per manufacturer's guidance or every 5 years, whichever is more frequent."

The principle underlying this requirement is the need to ensure data integrity. More specifically, the intent of this requirement is that meters meet such requirement every time they are used to gather data that is used in project emission reduction quantification. If a meter was out of conformance with this calibration requirement during a portion of the reporting period when it is not in use, but is brought back into conformance with this requirement before again being used to gather data which is used for project emission reduction calculations, then the underlying intent of this requirement is met.

Clarification: The following text shall be inserted after the fourth bulleted point at the beginning of Section 6.3:

"Conformance with this requirement is only required during periods of time where data gathered by the meter are used for emission reduction quantification. Periods where the meter did not meet this requirement will not cause the project to fail this requirement, provided the meter was not being used for project emission reduction quantification during such periods, and provided the meter was brought back into conformance before being employed to gather data which is used for project emission reduction quantification."

Appendix D

8. Data Substitution when Operational Data are Missing (ERRATUM – October 29, 2013)

Section: Appendix D (Data Substitution)

Context: There are three parameters necessary for the quantification of biogas destruction: biogas flow volume, methane concentration, and operational status of the destruction device. Section D.1 on page 80 provides a methodology for the substitution of missing biogas flow or methane concentration data. Data on the operational status of a destruction device are not eligible for substitution. Substitution of one parameter (i.e. flow or concentration) is only allowed if both other parameters are successfully recorded during the data gap. Thus, to employ the data substitution methodology, it is required that the record of operational status be intact during the gap.

This data substitution methodology was originally developed to resolve incidents of missing methane destruction data in landfill gas projects. Under that project type, excluding the data gap entirely is equivalent to the use of a destruction efficiency (DE) value of zero, whereas the same is not true for a livestock project. In the case of the Livestock Project Protocol, there is additional guidance on page 35 of Section 6.2 that requires the use of a DE value of zero for periods where the destruction device is inoperable, or the operational data are missing. This procedure effectively provides substitution of missing operational data with the assumption that the device was inoperable during the data gap. The effect of this substitution is an increase in project emissions, resulting in a more conservative estimate of emission reductions, regardless of whether the ultimate estimate of emission reductions is based on the modeled baseline or the metered methane destruction.

Because of the nature of the quantification methodology for livestock projects, and the ways that it differs from that of landfill projects, it is appropriate and conservative to carry out flow or methane data substitution, even if the destruction device is inoperable. Under this protocol, the quantification of emission reductions will be more conservative than if the data substitution were not employed.

Correction: The guidance on page 35 of Section 6.2 shall supersede the guidance in Appendix D. The following text shall be inserted after the second paragraph of Section D.1 in Appendix D:

"If the destruction device is inoperable, or its operational data are missing, the destruction efficiency for the device shall be zero during that period of time. Data substitution may be employed for missing biogas flow or methane concentration data during periods of missing operational data, provided the dataset is able to fulfill all other requirements of this data substitution methodology. The data substitution methodology shall be employed in the manner resulting in the greatest level of conservativeness for the quantification of emission reductions."

9. Data Substitution for Continuous Methane Data (CLARIFICATION – October 29, 2013)

Section: Appendix D (Data Substitution)

Context: The data substitution methodology in Appendix D may not be used for data gaps that are greater than seven days. However, the minimum measurement frequency for methane concentration data is once per quarter (three months). For projects that measure methane concentration at a frequency that is greater than quarterly, it is not clear how methane values should be applied during gaps of more than one week but less than an entire quarter.

Clarification: As long as a livestock project has at least one methane concentration reading per quarter, the project may satisfy the monitoring requirements in Section 6.2. A livestock project may have gaps between methane concentration readings that are greater than one week without this being considered "missing data" as it is conceived in Appendix D. Thus, project developers may devise a reasonable approach by which to assign a value to periods of time between recorded methane concentration values. The verifier shall confirm that the value(s) applied by the project is reasonable and conservative. No data substitution may be applied if there are no methane concentration readings during an entire quarter.

U.S. Livestock Protocol | Version 4.0 | January 23, 2013



Climate Action Reserve 601 West 5th Street, Suite 650 Los Angeles, CA 90071 www.climateactionreserve.org

Released January 23, 2013

© 2013 Climate Action Reserve. All rights reserved. This material may not be reproduced, displayed, modified or distributed without the express written permission of the Climate Action Reserve.

Acknowledgements

Staff

Mike McCormick Derek Markolf Syd Partridge Max DuBuisson Sami Osman Derik Broekhoff Rachel Tornek Heather Raven Anna Schmitz

The Reserve would like to thank SAIC and Kathryn Bickel Goldman for their work on the performance standard analysis.

The Reserve also recognizes the workgroup for their generous contribution of time and expertise, as well as other members of the public who actively participated in the protocol development process.

Workgroup

Susan Wood	AgCert
William Salas	Applied Geosolutions
Patrick Gaffney	California Air Resources Board
Kitty Howard	California Air Resources Board
Doug Thompson	California Air Resources Board
Dan Weller	California Air Resources Board
Steve Schaffer	California Department of Food and Agriculture
Cynthia Cory	CA Farm Bureau
John Shears	CEERT
Suzy Friedman	Environmental Defense
Martha Davis	Inland Empire Utility Agency
Scott Leloni	Manitoba Agriculture, Food and Rural Initiatives
Allen Dusault	Sustainable Conservation
Michael Boccadoro	The Dolphin Group
Melissa Weitz	U.S. EPA
Frank Mitleohner	UC Davis
Paul Martin	Western United Dairymen
Paul Sousa	Western United Dairymen

Table of Contents

Ał	obreviat	ations and Acronyms	1			
1	Intro	nduction	2			
2	The	GHG Reduction Project	2 ר			
2	2.1	Project Definition	ວ ເ			
	2.1	The Project Developer	ວ			
2	Z.Z Eliaik	ihility Puloe				
5	2 1		+4			
	3.1 2.2	Droject Stort Date	44			
	ა.∠ ว ว	Project Stall Date				
	3.3 2.4	Lineantrolled Anaparahia Bagalina				
	3.4 2 E					
	3.5		0			
4	3.0 The					
4	The	GHG Assessment Boundary	۵			
Э	Quar	Initivity of the Emission Reductions	13			
	5.1	Required Parameters for Modeling Baseline and Project Emissions	14			
	5.2	Modeling Baseline Methane Emissions.				
	5.3	Calculating Project Methane Emissions				
	5.4	Metered Methane Destruction Comparison				
~	5.5	Calculating Baseline and Project Carbon Dioxide Emissions				
6	Proje					
	6.1	Site-Specific Determination of Maximum Methane Potential (B ₀)				
	6.2	Biogas Control System Monitoring Requirements				
	6.3	Biogas Measurement Instrument QA/QC				
_	6.4	Monitoring Parameters				
1	Repo	orting Parameters				
	7.1	Project Documentation				
	7.2	Record Keeping				
_	7.3	Reporting and Verification Cycle				
8	Verif	fication Guidance	50			
	8.1	Standard of Verification				
	8.2	Monitoring Plan	50			
	8.3	Verifying Project Eligibility	50			
	8.4	Core Verification Activities	51			
	8.5	Verification Period				
	8.6	Livestock Verification Items	53			
_	8.7	Completing Verification				
9	Glos	ssary of Terms				
10) Re	eferences	59			
۸.		v A Accepted Environmental Impacts	64			
A	penalx	x A Associated Environmental Impacts				
A	openaix	X D ETTISSION FACTOR I ADIES				
A	openaix	x C Summary of Performance Standard Development				
Ą	openaix	X D Data Substitution	80			
A	pendix	X E Development of the B ₀ Sampling and Analysis Methodology				
A	ppendix F Sample Livestock Project Diagram85					

List of Tables

Table 4.1. Description of all Sources, Sinks, and Reservoirs	10
Table 6.1. Project Monitoring Parameters	38
Table 7.1. Sample Verification Cycle under Option 2	48
Table 7.2. Sample Verification Cycle under Option 3	49
Table 8.1. Summary of Eligibility Criteria for a Livestock Project	51
Table 8.2. Eligibility Verification Items	53
Table 8.3. Quantification Verification Items	54
Table 8.4. Risk Assessment Verification Items	55

List of Figures

Figure 4.1. General Illustration of the GHG Assessment Boundary	9
Figure 5.1. Organization of Equations in Section 5	17
Figure 6.1. Suggested Arrangement of Biogas Metering Equipment	35
Figure E.1. Monthly Milk Production Trends as a Percent Change Over Annual Average	Monthly
Milk Production (1998-2011)	82

List of Equations

Equation 5.1. GHG Reductions from Installing a Biogas Control System	18
Equation 5.2. Modeled Baseline Methane Emissions	19
Equation 5.3. Modeled Baseline Methane Emissions from Anaerobic Storage/Treatment	
Systems	20
Equation 5.4. Modeled Baseline Methane for Non-Anaerobic Storage/Treatment Systems	23
Equation 5.5. Project Methane Emissions	24
Equation 5.6. Project Methane Emissions from the Biogas Control System	25
Equation 5.7. Methane Emissions from Venting Events	26
Equation 5.8. Modeled Project Methane Emissions from Anaerobic Treatment of BCS Effl	uent26
Equation 5.9. Modeled Project Methane Emissions from Non-Anaerobic Treatment of BCS	3
Effluent	28
Equation 5.10. Project Methane Emissions from Non-BCS Related Sources	28
Equation 5.11. Metered Methane Destruction	29
Equation 5.12. Increased Carbon Dioxide Emissions	31

List of Appendix Tables

Table B.1. Manure Management System Components	.62
Table B.2. Livestock Categories and Typical Animal Mass	.63
Table B.3. Volatile Solids and Maximum Methane Potential by Livestock Category	.63
Table B.4. Biogas Collection Efficiency by Digester Type	.63
Table B.5a. 2010 Volatile Solid Default Values for Dairy Cows, Heifers, Heifers-Grazing and	
Cows-Grazing by State (kg/day/1000 kg mass)	.64
Table B.6. IPCC 2006 Methane Conversion Factors by Manure Management System	
Component/Methane Source 'S'	.67
Table B.7. Biogas Destruction Efficiency Default Values by Destruction Device	.69
Table B.8. CO ₂ Emission Factors for Fossil Fuel Use	.70
Table B.9. Volatile Solids Removed Through Solids Separation	.71
Table B.10. Baseline Assumptions for Greenfield Projects	.71
Table C.1. Dairy and Swine Operations in the U.S. by Manure Management System (2006)	.73

Table C.2. Dairy and Swine Operations in the U.S. by Manure Management System (2012))73
Table C.3. Dairy and Swine Operations by Size and Manure Management System (2006) .	74
Table C.4. Dairy and Swine Operations by Size and Manure Management System (2012) .	74
Table C.5. Dairy and Swine Operations by Size and Manure Management System (2012) .	75
Table C.6. Dairy and Swine Operations by Size and Manure Management System (2012) .	76
Table C.7. Dairy and Swine Operations Utilizing Liquid Manure Management, by Size and	
Manure Management System (2012)	77
Table E.1. Effects of Relative Population Size on Composite B ₀ Value	83

Abbreviations and Acronyms

BCS	Biogas control system
CARB	California Air Resources Board
CH ₄	Methane
CNG	Condensed natural gas
CO ₂	Carbon dioxide
CRT	Climate Reserve Tonne
EPA	U.S. Environmental Protection Agency
GHG	Greenhouse gas
GWP	Global warming potential
IPCC	Intergovernmental Panel on Climate Change
lb	Pound
LNG	Liquefied natural gas
MCF	Methane conversion factor
MT	Metric ton or tonne
N ₂ O	Nitrous oxide
NG	Natural gas
QA/QC	Quality Assurance/Quality Control
Reserve	Climate Action Reserve
scf	Standard cubic foot at 1 atm pressure and 60°F temperature
SSR	Sources, sinks, and reservoirs
t	Metric ton or tonne
ТАМ	Typical animal mass
VS	Volatile solids

1 Introduction

The Climate Action Reserve's (Reserve) Livestock Project Protocol provides guidance to account for and report greenhouse gas (GHG) emission reductions associated with the installation of a biogas control system (BCS) for manure management on dairy cattle and swine farms. The protocol focuses on quantifying the change in methane emissions, but also accounts for potential increases in carbon dioxide emissions.

The Climate Action Reserve is the most experienced, trusted and efficient offset registry to serve the California cap-and-trade program and the voluntary carbon market. With deep roots in California and a reach across North America, the Reserve encourages actions to reduce greenhouse gas emissions and works to ensure environmental benefit, integrity and transparency in market-based solutions to address global climate change. It operates the largest accredited registry for the California compliance market and has played an integral role in the development and administration of the state's cap-and-trade program. For the voluntary market, the Reserve establishes high quality standards for carbon offset projects, oversees independent third-party verification bodies and issues and tracks the transparent, publicly-accessible system. The Reserve program promotes immediate environmental and health benefits to local communities and brings credibility and value to the carbon market. The Climate Action Reserve is a private 501(c)(3) nonprofit organization based in Los Angeles, California.

Project developers that install manure biogas capture and destruction technologies use this document to register GHG reductions with the Reserve. The protocol provides eligibility rules, methods to calculate reductions, performance-monitoring instructions, and procedures for reporting project information to the Reserve. Additionally, all project reports receive independent verification by Reserve-approved verification bodies. Guidance for verification bodies to verify reductions is provided in the Verification Program Manual and Section 8 of this protocol.

This project protocol facilitates the creation of GHG emission reductions determined in a complete, consistent, transparent, accurate, and conservative manner, while incorporating relevant sources.¹

¹ See the WRI/WBCSD GHG Protocol for Project Accounting (Part I, Chapter 4) for a description of GHG accounting principles.

2 The GHG Reduction Project

Manure treated and stored under anaerobic conditions decomposes to produce methane, which, if uncontrolled, is emitted to the atmosphere. This predominantly occurs when livestock operations manage waste with anaerobic, liquid-based systems (e.g. in lagoons, ponds, tanks, or pits). Within the livestock sector, the primary drivers of methane generation include the amount of manure produced and the fraction of volatile solids (VS) that decompose anaerobically. Temperature and the retention time of manure during treatment and storage also affect methane production.

2.1 Project Definition

For the purpose of this protocol, the GHG reduction project is defined as the installation and operation of a biogas control system² that captures and destroys methane gas from anaerobic manure treatment and/or storage facilities on livestock operations. The biogas control system must destroy methane gas that would otherwise have been emitted to the atmosphere in the absence of the project from uncontrolled anaerobic treatment and/or storage of manure.

Captured biogas can be destroyed on-site, or transported for off-site use (e.g. through gas distribution or transmission pipeline), or used to power vehicles. Regardless of how project developers take advantage of the captured biogas, the ultimate fate of the methane must be destruction.

"Centralized digesters" that integrate waste from more than one livestock operation also meet the definition of a GHG reduction project.

Note that the protocol does not preclude project developers from co-digesting organic matter in the biogas control system. However, the additional organics could impact the nutrient properties of digester effluent; project developers should consider this when assessing the project's associated water quality impacts. The Reserve has also developed the Organic Waste Digestion Project Protocol that provides a quantification methodology for crediting the co-digestion of eligible waste streams with livestock manure. The protocol is available at http://www.climateactionreserve.org/how/protocols/adopted/organic-waste-digestion/current/.

2.2 The Project Developer

The "project developer" is an entity that has an active account on the Reserve, submits a project for listing and registration with the Reserve, and is ultimately responsible for all project reporting and verification. Project developers could be livestock facility owners and operators, GHG project financiers, or other entities. The project developer must have clear ownership of the project's GHG reductions. Ownership of the GHG reductions must be established by clear and explicit title, and the project developer must attest to such ownership each time the project is verified by signing the Reserve's Attestation of Title form.³

Under this protocol, the project developer is the only party required to be involved with project implementation.

² Biogas control systems encompass anaerobic digester systems – which may be designed and operated in a variety of ways, from ambient temperature covered lagoons to heated lagoons to mesophilic plug flow or complete mix concrete tank digesters—as well as methane destruction systems, such as flares or engines.

³ Attestation of Title form available at <u>http://www.climateactionreserve.org/how/projects/register/project-submittal-forms/</u>.

3 Eligibility Rules

Project developers using this protocol must satisfy the following eligibility rules to register reductions with the Reserve. The criteria only apply to projects that meet the definition of a GHG reduction project.

Eligibility Rule I:	Location	\rightarrow	U.S., its territories, and tribal lands
Eligibility Rule II:	Project Start Date	\rightarrow	No more than 6 months prior to project submission
Eligibility Rule III:	Anaerobic Baseline	\rightarrow	Demonstrate anaerobic baseline conditions
Eligibility Rule IV:	Additionality	\rightarrow	Meet performance standard
		\rightarrow	Exceed regulatory requirements
Eligibility Rule V:	Regulatory Compliance	\rightarrow	Compliance with all applicable laws

3.1 Location

Only projects located in the United States and its territories, or on U.S. tribal lands, are eligible to register reductions with the Reserve under this protocol. Livestock projects located in Mexico must use the Mexico Livestock Project Protocol if seeking to register GHG reductions with the Reserve.

3.2 Project Start Date

The start date for a livestock project is defined as the date on which the project's biogas control system becomes operational. For the purposes of this protocol, a BCS is considered *operational* on the date that the system begins producing and destroying methane gas following an initial start-up period. This date can be selected by the project developer within the 6 month period following the date on which manure is first loaded into the digester or on the date that the cover installation was completed (for a covered lagoon digester where the lagoon already contained manure).

Projects must be submitted to the Reserve no more than six months after the project start date.

3.3 Project Crediting Period

Project developers are eligible to register GHG reductions with the Reserve according to this protocol for a period of ten years following the project's start date. All projects that initially pass the eligibility requirements set forth in this protocol are eligible to register GHG reductions with the Reserve for the duration of the project's first crediting period (ten years), even if a regulatory agency with authority over a livestock operation passes a rule obligating the installation of a BCS during this initial crediting period.

If a project developer wishes to apply for eligibility under a second crediting period, they must do so within the final six months of the initial crediting period. Thus, the Reserve may issue CRTs for GHG reductions quantified and verified according to the U.S. Livestock Project Protocol for a maximum of two ten year crediting periods after the project start date. Section 3.5.1 and 3.5.2 describe the requirements to qualify for a second crediting period. Deadlines and requirements

for reporting and verification, as laid out in this protocol, the Program Manual, and the Verification Program Manual, will continue to apply without interruption.

3.4 Uncontrolled Anaerobic Baseline

The installation of a BCS at a livestock operation where the primary manure management system is aerobic (produces little to no methane) may result in an increase of the amount of methane emitted to the atmosphere. Thus, the BCS must digest manure that would primarily be treated in an anaerobic system in the absence of the project in order for the project to meet the definition of a GHG reduction project. Sections 3.4.1, 3.4.2, and 3.4.3 explain the specific baseline scenario options. Under any one of these scenarios, the uncontrolled anaerobic baseline requirement may be temporarily disrupted for the purposes of construction of the project digester. In these cases, the verifier may use professional judgment to confirm that the requirements of this section have been met.

3.4.1 Existing Livestock Facilities

For livestock facilities that have been in operation for more than five years, developers of livestock projects must demonstrate that an uncontrolled anaerobic manure management system was in place for the five years immediately prior to the date that manure was first loaded into the project digester. That anaerobic system may include a lagoon or a pond as long as the depth of the system was sufficient to prevent algal oxygen production and create an oxygen-free bottom layer (i.e. greater than 1 meter in liquid depth).⁴

For livestock facilities that have been in operation for more than two years, but less than five years, developers of livestock projects must demonstrate that an uncontrolled anaerobic manure management system was in place at all times up until the project's start date.

3.4.2 New Livestock Facilities (Greenfields)

Greenfield livestock projects (i.e. projects that are implemented at livestock facilities that have been in operation for less than two years at a site that had no prior manure management infrastructure) are eligible only if the project developer can demonstrate that there are no restrictions to the construction and operation of an open, uncontrolled, anaerobic manure storage system. Since a greenfield project will not have an existing manure management system that can be used to model the baseline methane emissions, all greenfield projects shall utilize a set of standardized baseline management assumptions (see Table B.10).

3.4.3 Centralized Digesters

For projects that employ a centralized digester that will be accepting manure from more than one livestock operation, each individual source of manure (identified by livestock facility) must meet the anaerobic baseline requirements above as of the project start date. In other words, if a new facility begins sending manure to the project digester after the project start date, the anaerobic baseline of that manure must still be assessed as of the project start date.

⁴ This is consistent with the United Nations Framework Convention on Climate Change (UNFCCC) Clean Development Mechanism (CDM) methodology ACM00010 (available at:

http://cdm.unfccc.int/methodologies/PAmethodologies/approved.html). For additional information on the design and maintenance of anaerobic wastewater treatment systems, see U.S. Department of Agriculture Natural Resources Conservation Service, Conservation Practice Standard, Waste Storage Facility, No. 313; and U.S. Department of Agriculture Natural Resources Conservation Service, Conservation Service, Conservation Service, Conservation Practice, Conservation, No. 313; and U.S. Department of Agriculture Natural Resources, No. 359.

3.5 Additionality

The Reserve will only accept projects that yield surplus GHG reductions that are additional to what would have otherwise occurred. That is, the reductions are above and beyond business-as-usual operation.

Project developers satisfy the "additionality" eligibility rule by passing two tests:

- 1. The Performance Standard Test
- 2. The Legal Requirement Test

3.5.1 The Performance Standard Test

Projects pass the Performance Standard Test by meeting a program-wide performance threshold – i.e. a standard of performance applicable to all manure management projects, established on an *ex-ante* basis. The performance threshold represents "better than business-as-usual" manure management. If the project meets the threshold, then it exceeds what would happen under the business-as-usual scenario and generates surplus/additional GHG reductions.

For this protocol, the Reserve uses a technology-specific threshold; sometimes also referred to as a practice-based threshold, where it serves as "best-practice standard" for managing livestock manure. By installing a BCS, a project developer passes the Performance Standard Test.

The Reserve defined this performance standard by evaluating manure management practices in California and the United States. A summary of the study to establish the threshold is provided in Appendix C.

The Performance Standard Test is applied at the time of the project's start date. All projects that pass this test at the project's start date are eligible to register reductions with the Reserve for the duration of the first project crediting period, even if the Reserve revises the Performance Standard Test in subsequent versions of this protocol during that period. As stated in Section 3.3, the project crediting period is ten years.

If a project developer wishes to apply for a second crediting period, the project must meet the eligibility requirements of the most current version of this protocol at the time of the submittal for the second crediting period, including any updates to the Performance Standard Test.

3.5.2 The Legal Requirement Test

All projects are subject to a Legal Requirement Test to ensure that the GHG reductions achieved by a project would not otherwise have occurred due to federal, state, or local regulations, or other legally binding mandates. A project passes the Legal Requirement Test when there are no laws, statutes, regulations, court orders, environmental mitigation agreements, permitting conditions, or other legally binding mandates requiring the installation of a BCS at the livestock operation.

The Legal Requirement Test is applied at the time of a project's start date. To satisfy the Legal Requirement Test, project developers must submit a signed Attestation of Voluntary Implementation form⁵ prior to the commencement of verification activities for the first verification

⁵ Attestation forms are available at <u>http://www.climateactionreserve.org/how/projects/register/project-submittal-forms/</u>.

period. All projects that pass this test at the project's start date are eligible to register reductions with the Reserve for the duration of their first crediting period, even if legal requirements change or new legal requirements are enacted during that period.

If a project developer wishes to apply for a second crediting period, the project must meet the eligibility requirements of the most current version of this protocol, including any updates to the Legal Requirement Test. Furthermore, during a project's second crediting period, it must demonstrate that it passes the Legal Requirement Test during each reporting period. To satisfy the Legal Requirement Test, project developers must submit a signed Attestation of Voluntary Implementation form prior to the commencement of verification activities for each verification period. If project activities become legally required during a project's second crediting period, the project will only be eligible to receive CRTs up to the date that the system is required to be operational.

The Reserve's analysis of manure management practices in the U.S. identified no regulations that obligate livestock owners to invest in a manure BCS. The analysis looked most closely at recent, stringent California air quality regulations (e.g. SJVAPCD Rule 4570 and Sacramento AQMD Rule 496), and found that installing an anaerobic digester is one of several compliance options, although high capital costs appear to prohibit the use of anaerobic digesters as a practical compliance mechanism for these air quality regulations.

3.6 Regulatory Compliance

As a final eligibility requirement, project developers must attest that project activities do not cause material violations of applicable laws (e.g. air, water quality, safety, etc.). To satisfy this requirement, project developers must submit a signed Attestation of Regulatory Compliance form⁶ prior to the commencement of verification activities each time the project is verified. Project developers are also required to disclose in writing to the verifier any and all instances of legal violations – material or otherwise – caused by the project or project activities.

A violation should be considered to be "caused" by project activities if it can be reasonably argued that the violation would not have occurred in the absence of the project activities. If there is any question of causality, the project developer shall disclose the violation to the verifier.

If a verifier finds that project activities have caused a material violation, then CRTs will not be issued for GHG reductions that occurred during the period(s) when the violation occurred. Individual violations due to administrative or reporting issues, or due to "acts of nature," are not considered material and will not affect CRT crediting. However, recurrent administrative violations directly related to project activities may affect crediting. Verifiers must determine if recurrent violations rise to the level of materiality. If the verifier is unable to assess the materiality of the violation, then the verifier shall consult with the Reserve.

⁶ Attestation forms are available at <u>http://www.climateactionreserve.org/how/projects/register/project-submittal-forms/</u>.

4 The GHG Assessment Boundary

The GHG Assessment Boundary delineates the GHG sources, sinks, and reservoirs (SSRs) that shall be assessed by project developers to determine the net change in emissions associated with installing a BCS. This protocol's assessment boundary captures sources from waste production to disposal, including off-site manure disposal.

CH₄ emissions from the land application of manure and digester effluent are excluded from the GHG Assessment Boundary. As these emission sources will either remain the same or decrease from the baseline to the project scenario, this exclusion is considered to be conservative.

 N_2O emissions associated with manure management and disposal are also excluded from the GHG Assessment Boundary. Again, as these emission sources will either remain the same or decrease from the baseline to the project scenario, this exclusion is also considered to be conservative. Significant uncertainty remains regarding the quantification of potential N_2O changes. While some projects may result in a significant decrease in N_2O emissions, at this time there is no project-level methodology available to appropriately account for this uncertainty.

CO₂ emissions associated with the capture and destruction of biogas are considered biogenic emissions⁷ (as opposed to anthropogenic) and are not included in the GHG Assessment Boundary.

This protocol does not account for CO_2 emission reductions associated with displacing griddelivered electricity or fossil fuel use. However, project developers may reduce the project emissions associated with increased use of grid-connected electricity by utilizing projectgenerated electricity for project equipment.

Figure 4.1 provides a general illustration of the GHG Assessment Boundary, indicating which SSRs are included or excluded from the boundary. All SSRs within the dashed line are accounted for under this protocol.

Table 4.1 provides greater detail on each SSR and provides justification for the inclusion or exclusion of SSRs and gases from the GHG Assessment Boundary.

⁷ The rationale is that carbon dioxide emitted during combustion represents the carbon dioxide that would have been emitted during natural decomposition of the manure. Emissions from the biogas control system do not yield a net increase in atmospheric carbon dioxide because they are theoretically equivalent to the carbon dioxide absorbed during plant/feed growth.



Figure 4.1. General Illustration of the GHG Assessment Boundary

Table 4.1 relates GHG source categories to sources and gases, and indicates inclusion in the calculation methodology. It is intended to be illustrative – GHG sources are indicative for the source category, GHGs in addition to the main GHG are also mentioned, where appropriate.

SSR	GHG Source	Gas	Relevant to Baseline (B) or Project (P)	Included/ Excluded	Justification/Explanation
1	Emissions from enteric fermentation	CH₄	B, P	Excluded	It is very unlikely that a livestock operation would change its feeding strategy to maximize biogas production from a digester; thus impacting enteric fermentation emissions from ruminant animals.
2	Emissions from waste deposits in barn, milking parlor or pasture/corral	N ₂ O	B, P	Excluded	This exclusion is conservative as emissions will either remain the same or decrease from the baseline to the project scenario, see page 8 for further explanation.
	Emissions from mobile and stationary support equipment	CO ₂	B, P	Included	If any additional vehicles or equipment are required by the project beyond what is required in the baseline, emissions from such sources shall be accounted for.
		CH_4		Excluded	Emission source is assumed to be very small.
		N ₂ O		Excluded	Emission source is assumed to be very small.
	Emissions from mechanical systems used to collect and transport waste (e.g. engines and pumps for flush systems; vacuums and tractors for scrape systems)	CO ₂		Included	If any additional vehicle or equipment use is required by the project beyond what is required in the baseline, emissions from such sources shall be accounted for.
		CH_4		Excluded	Emission source is assumed to be very small.
		N ₂ O		Excluded	Emission source is assumed to be very small.
3	Vehicle emissions (e.g. for centralized digesters)	CO ₂	B, P	Included	If any additional vehicles or fuel use is required by the project beyond what is required in the baseline, emissions from such equipment shall be accounted for.
		CH ₄		Excluded	Emission source is assumed to be very small.
			N ₂ O		Excluded

Table 4.1. Description of all Sources, Sinks, and Reservoirs

SSR	GHG Source	Gas	Relevant to Baseline (B) or Project (P)	Included/ Excluded	Justification/Explanation
	Emissions from waste treatment and storage including: anaerobic lagoons, dry lot deposits, compost piles, solid storage piles, manure settling basins, aerobic treatment, storage ponds, etc.	CO ₂	B, P	Excluded	Biogenic emissions are excluded.
		CH_4		Included	Primary source of emissions in the baseline.
4		N ₂ O		Excluded	This exclusion is conservative as emissions will either remain the same or decrease from the baseline to the project scenario, see page 8 for further explanation.
	Emissions from support equipment	CO ₂		Included	If any additional equipment is required by the project beyond what is required in the baseline, emissions from such equipment shall be accounted for.
		CH_4		Excluded	Emission source is assumed to be very small.
		N_2O		Excluded	Emission source is assumed to be very small.
5	Emissions from the anaerobic digester due to biogas collection inefficiencies and venting events	CH₄	Ρ	Included	Project may result in leaked emissions from anaerobic digester.
6	Emissions from effluent treatment	CH_4	Р	Included	Primary source of emissions from project activities.
	system	N ₂ O		Excluded	See page 8.
7	Vehicle emissions for land application and/or off-site transport	CO ₂	B, P	Included	If any additional vehicle use is required by the project beyond what is required in the baseline, associated additional emissions shall be accounted for.
		CH_4		Excluded	Emission source is assumed to be very small.
		N ₂ O		Excluded	Emission source is assumed to be very small.
		CH4	B, P	Excluded	Project activity is unlikely to increase emissions relative to baseline activity.
8	Emissions from land application	N ₂ O	B, P	Excluded	This exclusion is conservative as emissions will either remain the same or decrease from the baseline to the project scenario, see page 8 for further explanation

SSR	GHG Source	Gas	Relevant to Baseline (B) or Project (P)	Included/ Excluded	Justification/Explanation	
	Emissions from	CO ₂		Excluded	Biogenic emissions are excluded.	
9	combustion during flaring, including emissions from	CH_4	Р	Included	Primary source of emissions from project activities.	
	incomplete combustion of biogas	N ₂ O		Excluded	Emission source is assumed to be very small.	
	Emissions from	CO ₂		Excluded	Biogenic emissions are excluded.	
10	electric generation,	CH ₄	Р	Included	Primary source of emissions from project activities.	
	combustion of biogas	N ₂ O		Excluded	Emission source is assumed to be very small.	
	Emissions from	CO ₂		Included	Emissions resulting from on- site fossil fuel use and/or grid electricity may be significant.	
11	upgrading biogas for pipeline injection or	CH₄	Р	Excluded	Emission source is assumed to be very small.	
	use as cind/Lind fuel	N ₂ O		Excluded	Emission source is assumed to be very small.	
	Emissions from	CO ₂	Р	Excluded	Biogenic emissions are excluded.	
12	including emissions	CH_4		Included	Primary source of emissions from project activities.	
	combustion of biogas	N ₂ O		Excluded	Emission source is assumed to be very small.	
	Emissions from combustion of biogas	CO ₂	P	Excluded	Biogenic emissions are excluded.	
13	by end user of pipeline or CNG/LNG, including incomplete combustion	CH_4		Included	Primary source of emissions from project activities.	
		N_2O		Excluded	Emission source is assumed to be very small.	
14	Use of project-	CO ₂ CH ₄	Р	Excluded	This protocol does not cover displacement of GHG emissions from the use of	
	generated electricity	N ₂ O			biogas-generated electricity.	
	Off-site use of project-	CO ₂ CH ₄		Excluded	This protocol does not cover displacement of GHG	
15	generated thermal energy or power	N ₂ O	Р		emissions from the use of biogas delivered through pipeline or other end uses.	
	Use of project-				This protocol does not cover displacement of GHG	
16	generated thermal		Р	Excluded	emissions from the use of	
	energy	N ₂ O			biogas-generated thermal energy.	
	Project construction		Р	Excluded	Emission source is assumed	
	emissions	N ₂ O			to be very small.	

5 Quantifying GHG Emission Reductions

GHG emission reductions from a livestock project are quantified by comparing actual project emissions to baseline emissions at the project site. Baseline emissions are an estimate of the GHG emissions from sources within the GHG Assessment Boundary (see Section 4) that would have occurred in the absence of the livestock project. Project emissions are actual GHG emissions that occur at sources within the GHG Assessment Boundary during the reporting period. Project emissions must be subtracted from the baseline emissions to quantify the project's total net GHG emission reductions (Equation 5.1).

GHG emission reductions are generally quantified and verified on an annual basis. Project developers may choose to verify GHG emission reductions on a more frequent or less frequent basis if they desire (see Section 7.3). The length of time over which GHG emission reductions are quantified and reported to the Reserve is called the "reporting period." The length of time over which GHG reductions are verified is called a "verification period." Under this protocol, a verification period may cover multiple reporting periods (see Section 7.3.4). Project developers should take note that some equations to calculate baseline and project emissions are run on a month-by-month basis and activity data monitoring takes place at varying levels of frequency. As applicable, monthly emissions data (for baseline and project) are summed together to calculate emission reductions over a given reporting period. Projects whose reporting periods begin or end with incomplete calendar months shall only quantify the baseline and project emissions for the portion of the month that is included within the reporting period. The calculations provided in this protocol are derived from internationally accepted methodologies.⁸ Project developers shall use the calculation methods provided in this protocol to determine baseline and project GHG emissions in order to quantify GHG emission reductions.

To support project developers and facilitate consistent and complete emissions reporting, the Reserve has developed an Excel-based calculation tool. This tool is available to all Reserve account holders and their designated representatives. Instructions for obtaining the most recent version of this tool are available on the <u>U.S. Livestock Project Protocol webpage</u>. The Reserve *recommends* the use of the Livestock Calculation Tool for all project calculations and emission reduction reports. Only the most recent version of this tool should be used, unless otherwise recommended by Reserve staff. In any case where there is potential disagreement between guidance provided in the protocol and guidance provided in the calculation tool, the protocol shall take precedence.

The current methodology for quantifying the GHG impact associated with installing a BCS requires the use of both modeled reductions (following Equation 5.2 to Equation 5.4 and Equation 5.6 to Equation 5.9) as well as the utilization of *ex-post* metered data from the BCS to be used as a check on the modeled reductions.

The Reserve recognizes that there can be material differences between modeled methane emission reductions and the actual metered quantity of methane that is captured and destroyed by the BCS due to digester start-up periods, venting events, and other BCS operational issues.

⁸ The Reserve's GHG reduction calculation method is derived from the Kyoto Protocol's Clean Development Mechanism (ACM0010 V.5), the EPA's Climate Leaders Program (Manure Offset Protocol, August 2008), and the RGGI Model Rule (January 5, 2007).

These operational issues have the potential to result in substantially less methane destruction than is modeled, leading to an overestimation of GHG reductions in the modeled case.

To address this issue and maintain consistency with international best practice, the Reserve requires the modeled methane emission reduction results to be compared to the *ex-post* metered quantity of methane that is captured and destroyed by the BCS. The lesser of the two values will represent the total methane emission reductions for the reporting period. Equation 5.1 below outlines the quantification approach for calculating the emission reductions from the installation of a BCS.

5.1 Required Parameters for Modeling Baseline and Project Emissions

The following parameters must be determined for the modeling of baseline and project emissions:

Population – P_L

The procedure requires project developers to differentiate between livestock categories (L) (e.g. lactating dairy cows, non-milking dairy cows, heifers, etc.). This accounts for differences in methane generation across livestock categories. See Appendix B, Table B.2 for methane generation values. The population of each livestock category shall be monitored on a monthly basis, and for Equation 5.4 is averaged for an annual total population.

Volatile solids – VS_L

This value represents the daily organic material in the manure for each livestock category and consists of both biodegradable and non-biodegradable fractions. The VS content of manure is a combination of excreted fecal material (the fraction of a livestock category's diet consumed and not digested) and urinary excretions, expressed in a dry matter weight basis (kg/animal).⁹ This protocol requires that the VS value for all livestock categories be determined as outlined in Box 5.1.

Mass_∟

This value is the annual average live weight of the animals, per livestock category. These data are necessary because default VS values are supplied in units of kg/day/1000kg mass, therefore the average mass of the corresponding livestock category is required in order to convert the units of VS into kg/day/animal. Site specific livestock mass is preferred for all livestock categories. If site-specific data are unavailable, Typical Animal Mass (TAM) values may be used (see Appendix B, Table B.2).

Maximum methane production – B_{0,L}

This value represents the maximum methane-producing capacity of the manure, differentiated by livestock category (*L*) and diet. Project developers shall use the default B_0 factors from Appendix B, Table B.3. Alternatively, project developers may follow the sampling and testing procedure contained in Section 6.1 in order to determine a site-specific B_0 value for a particular animal category.

⁹ IPCC 2006 Guidelines volume 4, chapter 10, p. 10.42.

MS_{s}

The MS value apportions manure from each livestock category to appropriate manure management system component (*S*), and is a critical factor in determining a project baseline, as well as project emissions from effluent treatment. It reflects the reality that waste from the operation's livestock categories are not managed uniformly. The MS value accounts for the operation's multiple types of manure management systems. It is expressed as a percent (%), relative to the total amount of VS produced by the livestock category. As waste production is normalized for each livestock category, the percentage shall be calculated as percent of population for each livestock category. For example, a dairy operation might send 85% of its milking cows' waste to an anaerobic lagoon and 15% could be deposited in a corral. In this situation, an MS value of 85% would be assigned to Equation 5.3 and 15% to Equation 5.4.

Importantly, the MS value indicates where the waste would have been managed in the baseline scenario. If a portion of the VS was removed from the waste stream through some sort of separation procedure, the MS value shall be adjusted to accurately reflect the baseline treatment of the VS. To account for VS removal from solids separation equipment, project developers may use a default value for the particular type of separation mechanisms employed (Table B.9), or a site-specific value based on the removal efficiency of the baseline system.

 MS_{BCS} , which represents the fraction of manure that is sent to the BCS in the project scenario, follows the same logic as above, but is used to accurately quantify the project methane emissions from effluent treatment (see Equation 5.8).

MGS_{BCS}

The MGS_{BCS} value represents the maximum biogas storage capacity of the BCS system. This value is needed only in the case of a venting event during the reporting period, which is quantified using Equation 5.7. If the BCS consists of multiple digester tanks or covered lagoons, the project only need quantify the maximum storage (MGS_{BCS}) and biogas flow (F_{pw}) of the component(s) of the BCS that experienced the venting event.

Methane conversion factor – MCF

This method to calculate methane emissions reflects the site-specific monthly biological performance of the operation's baseline anaerobic manure management systems, as predicted using the van't Hoff-Arrhenius equation and farm-level data on temperature, as well as VS loading and system VS retention time.¹⁰

Each manure management system component has a volatile solids-to-methane conversion efficiency that represents the degree to which maximum methane production (B_0) is achieved. Methane production is a function of the extent of anaerobic conditions present in the system, the temperature of the system, and the retention time of organic material in the system.¹¹

Default MCF values for non-anaerobic baseline manure management system components (as well as certain project BCS effluent treatment and Non-BCS sources) are available in Appendix B. These are used in Equation 5.4 and Equation 5.9.

Contrastingly, site-specific calculations of volatile solids-to-methane conversion efficiency are required for anaerobic baseline manure management system components and for the anaerobic

¹⁰ The method is derived from Mangino et al., "Development of a Methane Conversion Factor to Estimate Emissions from Animal Waste Lagoons" (2001).

¹¹ IPCC 2006 Guidelines volume 4, chapter 10, p. 10.43.

treatment of project BCS effluent. For anaerobic lagoons, storage ponds, liquid slurry tanks etc., project developers perform a site-specific calculation of the mass of volatile solids degraded by the anaerobic storage/treatment system. This is expressed as "degraded volatile solids" or VS_{deg} in Equation 5.3, which equals the system's monthly available volatile solids multiplied by '*f*, the van't Hoff-Arrhenius factor. The '*f* factor effectively converts total available volatile solids, based on the monthly temperature of the system. The multiplication of VS_{deg} by B₀ quantifies the maximum potential methane emissions that would have been produced for each livestock category's contribution of manure to that system.



Figure 5.1. Organization of Equations in Section 5

Equation 5.1.	GHG	Reductions	from	Installing a	Biogas	Control Syste	m

$ER = \min\{ER_{modeled}, ER_{metered}\}$						
$ER_{modeled} = BE_{modeled} - PE_{CH_4} - CO_{2,net}$						
Where,			<u>Units</u>			
ER _{modeled}	=	Avoided methane emissions associated with the project during the reporting period, quantified using a modeled baseline scenario	tCO ₂ e			
BE _{modeled}	=	Modeled baseline emissions from the baseline scenario (Equation 5.2)	tCO ₂ e			
PE _{CH4}	=	Total project methane emissions during the reporting period (Equation 5.5)	tCO ₂ e			
CO _{2,net}	=	Net increase in anthropogenic CO_2 emissions from electricity consumption and mobile and stationary combustion sources resulting from project activity (Equation 5.12)	tCO ₂ e			
$ER_{metered} = BE_{metered} - CO_{2,net}$						
Where,			<u>Units</u>			
ER _{metered}	=	Avoided methane emissions associated with the project during the reporting period, quantified using metered methane destruction data	tCO ₂ e			
BE _{metered}	=	Aggregated quantity of methane collected and destroyed during the reporting period (Equation 5.11)	tCO ₂ e			
CO _{2,net}	=	Net increase in anthropogenic CO_2 emissions from electricity consumption and mobile and stationary combustion sources resulting from project activity (Equation 5.12)	tCO ₂ e			

5.2 Modeling Baseline Methane Emissions

Baseline emissions represent the GHG emissions within the GHG Assessment Boundary that would have occurred if not for the installation of the BCS. For the purposes of this protocol, project developers calculate their baseline emissions according to the manure management system in place prior to installing the BCS. Baseline emissions are then recalculated for each reporting period to reflect what the emissions would have been had the previous management system continued to function under current conditions. For Greenfield projects, as defined in Section 3.4.2, the baseline manure management practices shall be modeled according to the default values provided in Table B.10.

The procedure to determine the modeled baseline methane emissions follows Equation 5.2, which combines Equation 5.3 and Equation 5.4. The calculation procedures use a combination of site-specific values and default factors.

Box 5.1. Daily Volatile Solids for All Livestock Categories

Consistent with international best-practice, it is recommended that appropriate VS_L values for dairy livestock categories be obtained from the state-specific lookup tables (Tables B.5.a – B.5.f) provided in Appendix B. When possible, use the year corresponding to the appropriate emission year. If the current year's table is not included in the protocol, use the most current year that is available from the Reserve. Updated tables will be provided in the Livestock Calculation Tool, as well as the Reserve website.¹²

VS_L values for all other livestock can be found in Appendix B, Table B.3.

Important – Units provided for all VS values in Appendix B are in (kg/day/1000kg), In order to get VS_L in the appropriate units (kg/animal/day), the following equation must be used:

$$VS_L = VS_{Table} \times \frac{Mass_L}{1000}$$

Where,		<u>Units</u>
VS _L VS _{Table}	 Volatile solid excretion on a dry matter weight basis Volatile solid excretion from lookup table (Table B.3 and Table B.5a - B.5d) 	kg/animal/day kg/day/1000kg
Mass _L	 Average live weight for livestock category <i>L</i>. If site specific data are unavailable, use values from Appendix B, Table B.2 corresponding to the appropriate emission year (or the most current year that is available from the Reserve) 	kg

Fa	ustion	52	Modeled	Rasolino	Methane	Emissions
Ξų	uation	J.Z .	woueled	Daseiine	weinane	ETHISSIONS

$BE_{modeled} = \sum_{S,L} (BE_{CH_4,AS,L} + BE_{CH_4,nAS,L})$					
Where,			<u>Units</u>		
BE _{modeled}	=	Total baseline methane emissions during the reporting period, summed for each baseline treatment system S and livestock category L	tCO ₂ e		
BE _{CH4,AS,L}	=	Total monthly baseline methane emissions from anaerobic storage/treatment system AS by livestock category L , aggregated for the reporting period. See Equation 5.3	tCO ₂ e		
BE _{CH4,nAS,L}	=	Total baseline methane emissions for the reporting period from non- anaerobic storage/treatment systems by livestock category <i>L</i> . See Equation 5.4	tCO ₂ e		

¹² http://www.climateactionreserve.org/how/protocols/us-livestock/

$BE_{CH_{4},AS,L} = \left(VS_{deg,AS,L} \times B_{0,L} \times days_{mo} \times 0.68 \times 0.001 \times 21\right) \times \left(\frac{rd_{mo}}{days_{mo}}\right)$						
Where,			<u>Units</u>			
$BE_{CH4,AS,L}$	=	Total monthly baseline methane emissions from anaerobic manure storage/treatment system AS from livestock category L	tCO ₂ e/yr			
$VS_{deg,AS,L}$	=	Monthly volatile solids degraded in anaerobic manure storage/treatment system AS from livestock category L	kg dry matter			
B _{0,L}	=	Maximum methane producing capacity of manure for livestock category L – see Appendix B, Table B.3 for default values or Section 6.1 for guidance on determining a site-specific value	m ^³ CH₄/kg of VS			
0.68	=	Density of methane (1 atm, 60°F)	kg/m ³			
0.001	=	Conversion factor from kg to metric tons				
21	=	Global Warming Potential of methane as carbon dioxide equivalent	tCO ₂ e/tCH ₄			
days _{mo}	=	Calendar days per month	days			
rd _{mo}	=	Reporting days during the current month (see Box 5.2)	days			
$VS_{deg,AS,L} =$	$\sum_{AS,L}$	$(VS_{avail,AS,L} \times f)$				
Where,			<u>Units</u>			
$VS_{deg,AS,L}$	=	Monthly volatile solids degraded by anaerobic manure storage/ treatment system AS by livestock category L	kg dry matter			
$VS_{avail,AS,L}$	=	Monthly volatile solids available for degradation from anaerobic manure storage/treatment system AS by livestock category L	kg dry matter			
f	=	The van't Hoff-Arrhenius factor = "the proportion of volatile solids that are biologically available for conversion to methane based on the monthly temperature of the system" ¹³				
Equation 5.3	con	tinued on next page.				

Equation 5.3. Modeled Baseline Methane Emissions from Anaerobic Storage/Treatment Systems

¹³ Mangino, et al.

Equation 5.3. Continued

$VS_{avail,AS,L} = (VS_L \times P_L \times MS_{AS,L} \times days_{mo} \times 0.8) + (VS_{avail-1,AS} - VS_{deg-1,AS})$					
Where,			<u>Units</u>		
$VS_{avail,AS,L}$	=	Monthly volatile solids available for degradation in anaerobic storage/treatment system AS by livestock category L	kg dry matter		
VSL	=	Volatile solids produced by livestock category L on a dry matter basis. Refer to Box 5.1 for guidance on using appropriate units for VS _L values from Appendix B	kg/animal/day		
PL	=	Average population of livestock category L (based on population data for the current month)			
$MS_{AS,L}$	=	Percent of manure sent to (managed in) anaerobic manure storage/treatment system AS from livestock category L ¹⁴	%		
days _{mo}	=	Calendar days per month	days		
0.8	=	Management and design practices factor ¹⁵			
VS _{avail-1,AS}	=	Previous month's volatile solids available for degradation in anaerobic system <i>AS</i> ¹⁶	kg		
$VS_{deg-1,AS}$	=	Previous month's volatile solids degraded by anaerobic system AS	kg		
$f = exp\left[\frac{E(n)}{(R)}\right]$	$(T_{mo})(T_{re})$	$\frac{-T_{ref}}{2f}(T_{mo})$			
Where,			<u>Units</u>		
f	=	The van't Hoff-Arrhenius factor			
E	=	Activation energy constant (15,175)	cal/mol		
T _{mo}	=	Monthly average ambient temperature (K = °C + 273). If $T_{mo} < 5^{\circ}C$ then $f = 0.104$. If $T_{mo} > 29.5^{\circ}C$ then $f = 0.95$	Kelvin		
T _{ref}	=	303.16; Reference temperature for calculation	Kelvin		
R	=	Ideal gas constant (1.987)	cal/Kmol		

¹⁴ The MS value represents the percent of manure that would be sent to (managed by) the anaerobic manure

storage/treatment systems in the baseline case – as if the biogas control system was never installed. ¹⁵ Mangino, et al. This factor was derived to "account for management and design practices that result in the loss of volatile solids from the management system." This reflects the difference between the theoretical modeled biological activity and empirical measurement of biological activity due to removal of liquid or other management practices that result in loss of VS from the treatment system. This does not account for removal of solids prior to the treatment

system. ¹⁶ IPCC 2006 Guidelines (Volume 4, Chapter 10, p. 42); ACM0010 (V2, p.8); and EPA Climate Leaders Manure Offset Protocol (August 2008).
Box 5.2. Calculating the Number of Reporting Days for a Reporting Period

For some projects, it may be necessary to exclude a number of days from the calculation of emission reductions. If the reporting period begins or ends mid-way through a month, the calculation shall be prorated to only include the number of days for each month that fall within the reporting period by setting *nrd* equal to the number of days that fall outside the reporting period. If the project is not eligible to report emission reductions for a certain period of time for other reasons (e.g. regulatory compliance issues, missing data), those days may also be included in the determination of *nrd*.

For example, if a reporting period begins on March 10, then $nrd_{March} = 9$. If the same reporting period ends on December 31st of the same year, then $nrd_{rp} = 9$, and rd = (306 - 9) = 297.

The following equation is used to determine the number of reporting days for the current period. This is to be applied for individual months for those equations that are run monthly, and for the entire reporting period for those equations that are run once per reporting period.

rd = days - nrd

Where,

rd	=	Number of reporting days in the current period (month, reporting period, etc.)
days	=	Number of calendar days in the current period (e.g. equal to 30 for June)

nrd = Non-reporting days in the current period

Retention of Volatile Solids

Equation 5.3 calculates methane emissions from anaerobic manure storage/treatment systems based on site-specific information on the mass of volatile solids degraded by the anaerobic storage/treatment system and available for methane conversion.¹⁷ It incorporates the effects of temperature through the van't Hoff-Arrhenius (*f*) factor and accounts for the retention of volatile solids through the use of monthly assumptions of baseline conditions. Each month, a certain quantity of VS is converted into methane (VS_{deg}). The VS that is available for conversion each month (VS_{avail}) is the sum of VS that enters the manure management system, as well as VS that remains in the system from the previous month (VS_{avail-1} – VS_{deg-1}).

Project developers shall not carry over volatile solids from one month to the next when modeling baseline anaerobic treatment systems where the retention time was 30 days or less. For these systems ($VS_{avail-1} - VS_{deg-1}$) = 0 in Equation 5.3 for every month.

Depending on the accumulation of sludge in the baseline manure storage system, it may have been necessary to drain and clean the system on a periodic basis. This cleaning removes the non-degraded VS that has accumulated in the system. For anaerobic lagoons with a retention time greater than 30 days, project developers shall zero out the VS retained in the system following the month when the system would have been completely drained and sludge removed under baseline operating conditions. For the month following the sludge removal, (VS_{avail-1} – VS_{deg-1}) = 0 in Equation 5.3. For projects where a BCS is being retrofit into existing operations, baseline anaerobic system management practices should reflect actual pre-project manure management practices on that farm.

¹⁷ These system components must meet the Anaerobic Baseline requirement in Section 3.4.

If the farm utilized solids separation in the baseline (thus preventing or delaying sludge accumulation), this removal and alternative treatment of VS should be reflected in the MS values, as explained earlier in this section.

The removal of supernatant liquids for spraying on fields at agronomic rates does not affect the monthly carryover of VS, as long as the system maintains at least one meter of liquid depth. Projects therefore do not need to account for regular field spraying activities that meet this description.

Equation 5.4 applies to non-anaerobic storage/treatment systems. Both Equation 5.3 and Equation 5.4 reflect basic biological principles of methane production from available volatile solids, determine methane generation for each livestock category, and account for the extent to which the waste management system handles each category's manure.

Equation 5.4. Modeled Baseline Methane for Non-Anaerobic Storage/Treatment Systems

$BE_{CH_4,nAS,L} = \left(P_L \times MS_{L,nAS} \times VS_L \times days_{rp} \times MCF_{nAS} \times B_{0,L}\right) \times 0.68 \times 0.001 \times 21 \times \left(\frac{rd_{rp}}{days_{rp}}\right)$					
Where,			<u>Units</u>		
$BE_{CH4,nAS,L}$	=	Total baseline methane emissions during the reporting period from non- anaerobic storage/treatment systems	tCO ₂ e		
PL	=	Average population of livestock category <i>L</i> during the reporting period (based on monthly population data)			
$\text{MS}_{\text{L},\text{nAS}}$	=	Percent of manure from livestock category <i>L</i> managed in non-anaerobic storage/treatment systems	%		
VSL	=	Volatile solids produced by livestock category L on a dry matter basis. Refer to Box 5.1 for guidance on using appropriate units for VS _L values from Appendix B	kg/animal/day		
days _{rp}	=	Number of days in the reporting period	days		
MCF _{nAS}	=	Methane conversion factor for non-anaerobic storage/treatment system. See Appendix B	%		
B _{0,L}	=	Maximum methane producing capacity for manure for livestock category <i>L</i> . See Appendix B, Table B.3 for default values, or Section 6.1 for determining a site-specific value	m ³ CH₄/kg of VS dry matter		
0.68	=	Density of methane (1 atm, 60°F)	kg/m ³		
0.001	=	Conversion factor from kg to metric tons	-		
21	=	Global Warming Potential of methane as carbon dioxide equivalent	tCO ₂ e/tCH ₄		
rd _{rp}	=	Reporting days during the reporting period	days		

5.3 Calculating Project Methane Emissions

Project emissions are actual GHG emissions that occur within the GHG Assessment Boundary after the installation of the BCS. Project emissions are calculated on an annual, *ex-post* basis. Like baseline emissions, some parameters are monitored on a monthly basis. Unlike baseline emission calculations, methane emissions from the BCS are calculated from metered data, rather than modeled projections. Methane emissions from manure storage and/or treatment systems other than the BCS are modeled much the same as in the baseline scenario.

As shown in Equation 5.5, project methane emissions equal:

- The amount of methane created by the BCS that is not captured and destroyed by the control system, plus
- Methane from the digester effluent treatment systems (where applicable), plus
- Methane from sources in the waste treatment and storage category other than the BCS and associated effluent treatment systems. This includes all other manure treatment systems such as compost piles, solids storage etc.

Consistent with this protocol's baseline methane calculation approach, the formula to account for project methane emissions incorporates all potential sources within the waste treatment and storage category. Non-BCS-related sources follow the same calculation approach as provided in the baseline methane equations. Several activity data for the variables in Equation 5.9 will be the same as those in Equation 5.2 to Equation 5.4.

If the project elects to install an impermeable cover on an effluent pond (potentially creating an additional anaerobic digester) and the biogas generated in this covered pond is collected and destroyed by the project BCS, then this covered pond shall be considered part of the project digester system. If the biogas generated by this covered pond is not destroyed, it must be quantified as project methane emissions using Equation 5.8.

Although not common under normal digester operation, it is possible that a venting event may occur due to catastrophic failure of digester cover materials, the digester vessel, or the gas collection system. In the event that a catastrophic system failure results in the venting of biogas, the quantity of methane released to the atmosphere shall be estimated according to Equation 5.7 below.

$PE_{CH_4} = \left(PE_{CH_4,BCS} + PE_{CH_4,ET,AS} + PE_{CH_4,ET,nAS} + PE_{CH_4,other}\right) \times 21$					
Where,			<u>Units</u>		
PE _{CH4}	=	Total project methane emissions for the reporting period,	tCO ₂ e		
PE _{CH4,BCS}	=	Methane emissions from the BCS during the reporting period (Equation 5.6)	tCH ₄		
PE _{CH4,ET,AS}	=	Monthly methane emissions from the BCS effluent anaerobic treatment systems, aggregated for the reporting period (Equation 5.8)	tCH ₄		
$PE_{CH4,ET,nAS}$	=	Methane emissions from the BCS effluent non-anaerobic treatment systems during the reporting period (Equation 5.9)	tCH ₄		
PE _{CH4,other}	=	Methane emissions from sources in the waste treatment and storage category other than the BCS and associated effluent treatment systems, during the reporting period (Equation 5.10)	tCH₄		
21	=	Global warming potential of methane as carbon dioxide equivalent	tCO ₂ e/tCH ₄		

Equation 5.5. Project Methane Emissions

Εα	uation 5.6	S. Pro	iect	Methane	Emissions	from	the	Biogas	Control	Syste	-m
∟ч	uation 5.0		jeu	methane	LIII3310113	nom	uie	Diogas	Control	Oysie	2111

$PE_{CH_4,BCS} =$	\sum_{i}	$\int_{i} \left[CH_{4,metered,i} \times \left(\left(\frac{1}{BCE} \right) - BDE_{i,weighted} \right) \right] + CH_{4,vent,i} \right]$			
Where,			<u>Units</u>		
PE _{CH4,BCS}	=	Methane emissions from the BCS, to be summed for each reporting	tCH ₄		
CH _{4,metered,i} BCE	= =	Quantity of methane collected and metered in month <i>i</i> Methane collection efficiency of the BCS. Project developers shall use the appropriate default value provided in Table B 4	tCH₄ fraction		
$\begin{array}{l} BDE_{i,weighted} \\ CH_{4,vent,i} \end{array}$	=	Weighted average of all destruction devices used in month i Quantity of methane that is vented to the atmosphere due to BCS venting events in month <i>i</i> , as quantified in Equation 5.7 below	fraction tCH ₄		
CH _{4,metered,i}	= F	$T \times \frac{520}{T_b} \times \frac{P}{1} \times CH_{4,conc} \times 0.0423 \times 0.000454$			
Where,		2	<u>Units</u>		
$CH_{4,metered,i}$ F T _b P CH _{4,conc} 0.0423 0.000454	= = = = =	Wuantity of methane collected and metered in month i^{18} Measured volumetric flow of biogas in month i Temperature of the biogas flow (°R = °F + 459.67) Pressure of the biogas flow Measured methane concentration of biogas for month i Density of methane gas (1 atm, 60°F) Conversion factor from lb to metric ton	tCH₄ scf °R atm fraction Ib CH₄/scf		
* The terms (520/T _b) and (P/1) should be omitted if the continuous flow meter internally corrects for temperature and pressure to 60°F and 1 atm.					
BDE _{i,weighte}	d =	$\frac{\sum_{DD} (BDE_{DD} \times F_{i,DD})}{F_i}$			
Where,			<u>Units</u>		
BDE _{i,weighted} BDE _{DD}	= =	Monthly weighted average of all destruction devices used in month <i>i</i> Default methane destruction efficiency of a particular destruction device 'DD' See Appendix B for default destruction efficiencies ¹⁹	fraction fraction		
F _{i,DD} Fi	=	Monthly flow of biogas to a particular destruction device 'DD' Total monthly measured volumetric flow of biogas to all destruction devices	scf/month scf/month		

¹⁸ This value reflects directly measured biogas mass flow and methane concentration in the biogas to the combustion device.
¹⁹ Project developers have the option to use either the default methane destruction efficiencies provided, or site

¹⁹ Project developers have the option to use either the default methane destruction efficiencies provided, or site specific methane destruction efficiencies, for each of the combustion devices used in the project. Site-specific values must be provided by an independent air emissions testing body that is accredited by a state or local agency, or the Stack Testing Accreditation Council (STAC). See Appendix B for more information. Where a state/region does not have an appropriate accreditation system or accredited service providers, the project developer may look to another state/region to find suitably qualified service providers.

_				<u> </u>			
Eq	uation	5.7.	Methane	Emissions	from	Venting	Events

$CH_{4,vent,i} = \left(MGS_{BCS} + (F_{pw} \times t)\right) \times CH_{4,conc} \times 0.0423 \times 0.000454$					
Where,			<u>Units</u>		
$CH_{4,vent,i}$	=	Quantity of methane that is vented to the atmosphere due to BCS venting events in month <i>i</i>	tCH ₄		
MGS _{BCS}	=	Maximum biogas storage of the BCS system ²⁰	scf		
F _{pw}	=	Average total daily flow of biogas from the digester for the entire week prior to the venting event ²⁰	scf/day		
t	=	Number of days of the month that biogas is venting uncontrolled from the BCS system (can be a fraction)	days		
$CH_{4,conc}$	=	Measured methane concentration of biogas prior to the venting event	fraction		
0.0423	=	Density of methane gas (1 atm, 60°F)	lb CH₄/scf		
0.000454	=	Conversion factor from lb to metric ton			

Equation 5.8, along with Equation 5.9, shall be used to account for all treatment systems associated with the BCS effluent. The factor ETF_i shall be estimated by the project developer to determine what fraction of the VS in the effluent is sent to each treatment system, and is represented as a fraction (e.g. if 85% of the BCS effluent is sent to an effluent pond, then ETF_i for that system is equal to 0.85). Anaerobic effluent treatment systems are those which store liquid effluent in a lagoon, pond, or tank. This includes liquid storage systems that employ non-airtight covers (i.e. biogas is freely vented to the atmosphere) as long as the entire system is managed as a passive storage system, rather than an actively-managed treatment system (i.e. no heating, mixing, etc.).

Equation 5.8. Modeled Project Methane Emissions from Anaerobic Treatment of BCS Effluent

PE _{CH4} ,ET,AS	=	$\sum_{i} (VS_{ET,i} \times B_{0,ET} \times days_{mo} \times 0.8 \times f \times 0.68 \times 0.001) \times \frac{rd_{mo}}{days_{mo}}$	
Where,			<u>Units</u>
$\begin{array}{c} PE_{CH4,ET,AS}\\ VS_{ET,i}\\ B_{0,ET}\\ days_{mo}\\ 0.8\\ f\\ 0.68\\ 0.001\\ rd_{mo} \end{array}$		Monthly methane emissions from anaerobic effluent treatment systems Volatile solids to anaerobic effluent treatment system <i>i</i> (see below) Maximum methane producing capacity (of VS dry matter) ²¹ Calendar days in the current month Management and design practices factor ¹⁵ The van't Hoff-Arrhenius factor, as calculated in Equation 5.3 Density of methane (1 atm, 60° F) Conversion from kg to metric tons Reporting days in the current month	tCH₄ kg/day m ³ CH₄/kg VS days fraction kg/m ³ t/kg days
Equation 5.	8 c	ontinued on next page	

²⁰ If the BCS consists of multiple digester tanks or covered lagoons, the project only need quantify the maximum storage (MGS_{BCS}) and biogas flow (F_{pw}) of the component(s) of the BCS that experienced the venting event. ²¹ The B_0 value for the project effluent pond is not differentiated by livestock category. Project developers shall use the B_0 value that corresponds with a weighted average of the operation's livestock categories that contribute manure to the BCS (weighted by the kg of VS contributed by each livestock category). Supporting laboratory data and documentation per Section 6.1 needs to be supplied to the verifier to justify an alternative value.

Equation 5.8. Continued

$VS_{ET,i} =$		$\sum_{L} (VS_L \times P_L \times MS_{L,BCS})) \times 0.3] \times ETF_i$	
Where,			<u>Units</u>
VS _{ET,i} VS _L	= =	Volatile solids to anaerobic effluent treatment system <i>i</i> Volatile solids produced by livestock category 'L' on a dry matter basis. <i>Important</i> – refer to Box 5.1 for guidance on using appropriate units for VS ₁ values from Appendix B	kg/day kg/animal/ day
P_{L}	=	Average population of livestock category <i>L</i> during the reporting period (based on monthly population data)	
MS _{L.BCS}	=	Fraction of manure from livestock category <i>L</i> that is managed in the BCS	fraction
0.3	=	Default value representing the amount of VS that exits the digester as a fraction of the VS entering the digester ²²	fraction
ETFi	=	Fraction of the effluent that exits the digester and is sent to effluent treatment system <i>i</i>	fraction

If the effluent from the project digester is directed to a covered liquid effluent storage system, and the biogas from this storage system is not collected and destroyed, then the following scenarios apply:

 If the effluent from this system is applied directly to land and biogas flow and methane concentration are monitored in accordance with Section 6, then PE_{CH4,ET,AS} for this system shall be determined using Equation 5.6, assuming a BCE value of 0.95 and a BDE value of 0.

For any periods where biogas flow and/or methane concentration data from this system are missing (and not replaceable through data substitution) or not in conformance with Section 6, Equation 5.8 shall be used to determine the quantity of project methane emissions from this system component.

2. If the effluent from the covered liquid effluent storage system is directed to another treatment system (i.e. not land-applied), then an additional calculation is required. The methane released from the covered liquid effluent system shall be quantified using the guidance in Scenario 1 above, but the additional methane released by the further treatment system must also be quantified. Equation 5.9 shall be used to calculate the methane released from the additional treatment system using the default assumptions that 30% of the VS_{ET,i} from the effluent storage system enters the additional treatment system.

²² Per ACM0010 (V2 Annex I).

Equation 5.9. N	/lodeled Project N	lethane Emissions from	n Non-Anaerobic	Treatment of BCS Effluent ²³
-----------------	--------------------	------------------------	-----------------	---

$PE_{CH_4,ET,nAS} = \sum_{i} (VS_{ET,i} \times B_{0,ET} \times rd_{rp} \times 0.68 \times MCF_{ET,i} \times 0.001)$					
Where,		1	<u>Units</u>		
$PE_{CH4,ET,nAS}$	=	Project methane emissions from non-anaerobic effluent treatment systems during the reporting period	tCH ₄		
$VS_{ET,i}$	=	Volatile solids to non-anaerobic effluent treatment system <i>i</i> (see Equation 5.8)	kg/day		
$B_{0,ET}$	=	Maximum methane producing capacity (of VS dry matter) ²⁴	m³CH₄/kg		
rd _{rp}	=	Number of reporting days in the current reporting period	days		
0.68	=	Density of methane (1 atm, 60°F)	kg/m ³		
MCF _{ET,i}	=	Methane conversion factor for effluent treatment system <i>i</i> (Table B.6)	fraction		
0.001	=	Conversion factor from kg to metric tons			

Equation 5.10. Project Methane Emissions from Non-BCS Related Sources²⁵

PE _{CH4,other}	= 2	$\sum_{L} (P_L \times VS_L \times B_{0,L} \times MCF_{non-BCS} \times rd_{rp} \times 0.68 \times 0.001)$	
Where,		L	<u>Units</u>
PE _{CH4,other}	=	Methane from sources in the waste treatment and storage category other than the BCS and associated effluent treatment systems during the reporting period	tCH ₄
P∟ VS∟	=	Average population of livestock category <i>L</i> during the reporting period Volatile solids produced by livestock category 'L' on a dry matter basis. Refer to Box 5.1 for guidance on using appropriate units for VS _L values from Appendix B	kg/ animal/ day
B _{0,L}	=	Maximum methane producing capacity of VS dry matter for manure for livestock category / (Appendix B, Table B, 3)	m³ CH₄/kg
MCF _{non-BCS}	=	Management-weighted methane conversion factor for waste treatment and storage systems other than the BCS and associated effluent treatment systems	fraction
rd _{rp}	=	Number of reporting days in the current reporting period	days
0.68	=	Density of methane (1 atm, 60°F)	kg/m³
0.001	=		
MCF _{non-BC}	s =	$\sum_{S} (MCF_{S} \times MS_{L,S})$	
Where,			<u>Units</u>
MCF _{non-BCS}	=	Management-weighted methane conversion factor for waste treatment and storage systems other than the BCS and associated effluent treatment systems	fraction
MCFs	=	Methane conversion factor for system component S (Table B.9)	fraction
MS _{L,S}	=	Fraction of manure from livestock category <i>L</i> that is managed in non- BCS system component <i>S</i>	fraction

²³ Non-anaerobic effluent treatment systems are those which manage effluent in solid form, or those which manage liquid effluent in a way that would be considered aerobic (e.g. a pond with effective aeration equipment). ²⁴ The B_o value for the project effluent pond is not differentiated by livestock category. Project developers shall use

²⁴ The B_o value for the project effluent pond is not differentiated by livestock category. Project developers shall use the B_o value that corresponds with a weighted average of the operation's livestock categories that contribute manure to the BCS (weighted by the kg of VS contributed by each livestock category). Supporting laboratory data and documentation per Section 6.1, need to be supplied to the verifier to justify an alternative value. ²⁵ According to this protocol, non-BCS-related sources means manure management system components (system

⁵ According to this protocol, non-BCS-related sources means manure management system components (system component 'S') other than the biogas control system and the BCS effluent treatment systems (if used).

5.4 Metered Methane Destruction Comparison

As described above, the Reserve requires all projects to compare the modeled methane emission reductions for the reporting period, as calculated in Equation 5.2 to Equation 5.4 and Equation 5.6 to Equation 5.9, with the actual metered amount of methane that is destroyed in the BCS over the same period. The lesser of the two values is to be used as the total methane emission reductions for the reporting period in question.

In order to calculate the metered methane reductions, the monthly quantity of biogas that is metered and destroyed by the BCS must be aggregated over the reporting period. In the event that a project developer is reporting reductions for a period of time that is less than a full year, the total modeled methane emission reductions would be aggregated over this time period and compared with the metered methane that is destroyed in the BCS over the same period of time. Similarly, projects whose reporting periods begin or end with incomplete calendar months shall only quantify the baseline and project emissions for the portion of the month that is included within the reporting period. For example, if a project is reporting and verifying only 6 months of data (e.g. July to December), then the modeled emission reductions over the same six month period, and the lesser of the two values would be used as the total methane emission reduction quantity for this six month period. See Equation 5.1 for calculation guidance.

Equation 5.11 below details the metered methane destruction calculation.

$BE_{metered} =$	\sum_{i}	$(CH_{4,metered,i} \times BDE_{i,weighted}) \times 21$	
Where,	-		<u>Units</u>
BE _{metered}	=	Aggregated quantity of methane collected and destroyed during the reporting period	tCO ₂ e
$CH_{4,metered,i}$	=	Quantity of methane collected and metered in month i. See Equation 5.6 for calculation guidance	tCH₄/month
BDE _{i,weighted}	=	Weighted average of all destruction devices used in month <i>i</i> . ²⁶ See Equation 5.6 for calculation guidance	fraction
21	=	Global warming potential of methane as carbon dioxide equivalent	tCO ₂ e/tCH ₄

Equation 5.11.	Metered Methane	Destruction
----------------	-----------------	-------------

5.5 Calculating Baseline and Project Carbon Dioxide Emissions

Sources of carbon dioxide emissions associated with a project may include electricity use by pumps and equipment, fossil fuel generators used to power pumping systems or milking parlor equipment, tractors that operate in barns or free-stalls, on-site manure hauling trucks, or vehicles that transport manure off-site. Per Table 4.1, the carbon dioxide emissions from any additional equipment, vehicles, or fuel use that is required by the project beyond what is required in the baseline shall be accounted for. In practice, project developers shall account for the emissions from any new electric- or fuel-powered equipment or vehicles purchased and

²⁶ Project developers have the option to use either the default methane destruction efficiencies provided, or site specific methane destruction efficiencies, for each of the combustion devices used in the project. Site-specific values must be provided by an independent air emissions testing body that is accredited by a state or local agency, or the Stack Testing Accreditation Council (STAC). See Appendix B for more information.

installed/operated specifically for the purpose of implementing the project, as well as any additional fuel used by old or new vehicles to collect or transport waste.

Project developers may either use Equation 5.12 below to calculate the net increase in carbon dioxide emissions, or, if they can demonstrate during verification that project carbon dioxide emissions are estimated to be equal to or less than 5% of the total baseline emissions, then the project developer may estimate baseline and project carbon dioxide emissions. If an estimation method is used, verifiers shall confirm based on professional judgment that project carbon dioxide emissions are equal to or less than 5% of the total baseline emissions based on documentation and the estimation methodology provided by the project developer. If emissions cannot be confirmed to be below 5%, then Equation 5.12 shall be used. Regardless of the method used, all estimates or calculations of anthropogenic carbon dioxide emissions within the GHG Assessment Boundary must be verified and included in emission reduction calculations.²⁷

If calculations or estimates indicate that the project results in a net decrease in carbon dioxide emissions from grid-delivered electricity, mobile and stationary sources, then for quantification purposes the net increase in these emissions must be specified as zero (i.e. $CO_{2,net} = 0$ in Equation 5.12).

Carbon dioxide emissions from the combustion of biogas are considered biogenic emissions and are excluded from the GHG Assessment Boundary.

Equation 5.12 below calculates the net increase in anthropogenic carbon dioxide emissions resulting from the project activity.

²⁷ This is consistent with guidance in WRI's GHG Project Protocol regarding the treatment of significant secondary effects.

Equation 5.12. Increased Carbon Dioxide Emissions

CO _{2,net} =	$BE_{CO_2,MSC} - PE_{CO_2,MSC}$	
Where,		<u>Units</u>
CO _{2,net}	Net increase in anthropogenic CO ₂ emissions from electricity consumption and mobile and stationary combustion sources resulting from project activity during the reporting period. If result is <0, use a value of 0.	tCO ₂
BE _{CO2,MSC}	 Total baseline CO₂ emissions from electricity consumption and mobile and stationary combustion sources during the reporting period (see equation below) 	tCO ₂
PE _{CO2,MSC}	 Total project CO₂ emissions from electricity consumption and mobile and stationary combustion sources during the reporting period (see equation below) 	tCO ₂
All CO ₂ em calculated	issions associated with electricity consumption and stationary and mobile combustion using the equation:	are
$CO_{2,MSC} =$	$= \left(\sum_{c} QE_{c} \times EF_{CO_{2},e}\right) + \left[\left(\sum_{c} QF_{c} \times EF_{CO_{2},f}\right) \times 0.001\right]$	
Where,	<u>U</u>	nits
$\rm CO_{2,MSC}$	= Anthropogenic CO ₂ emissions from electricity consumption and mobile to	CO ₂
QE_{c}	= Quantity of grid-connected electricity consumed for each emissions N source 'c' ²⁸ during the reporting period	lWh
EF _{CO2}	= CO_2 emission factor for electricity used ²⁹ tCO	₂ /MWh
QF _c	= Quantity of fuel consumed for each mobile and stationary emission MM	Btu or
	source 'c' during the reporting period ga	llons
EF _{CO2,f}	= Fuel-specific emission factor <i>f</i> from Appendix B kg CO	₂ /MMBtu
0.001	er Kg C = Conversion factor from kg to metric tons	O ₂ /gallon

²⁸ Emissions from electricity generated by the BCS and consumed onsite, do not need to be reported, as the resulting CO_2 emissions are considered biogenic, CH_4 is captured by the BDE calculation and N_2O emissions are excluded as negligible. ²⁹ Refer to the version of the U.S. EPA eGRID most closely corresponding to the time period during which the

²⁹ Refer to the version of the U.S. EPA eGRID most closely corresponding to the time period during which the electricity was used. Projects shall use the annual total output emission rates for the subregion where the project is located, not the annual non-baseload output emission rates. The eGRID tables are available from the U.S. EPA website: http://www.epa.gov/cleanenergy/energy-resources/egrid/index.html

6 Project Monitoring

The Reserve requires a Monitoring Plan to be established for all monitoring and reporting activities associated with the project. The Monitoring Plan will serve as the basis for verification bodies to confirm that the monitoring and reporting requirements in this section and Section 7 have been and will continue to be met, and that consistent, rigorous monitoring and record-keeping is ongoing at the project site. The Monitoring Plan must cover all aspects of monitoring and reporting contained in this protocol and must specify how data for all relevant parameters in Table 6.1 (below) will be collected and recorded.

At a minimum the Monitoring Plan shall stipulate the frequency of data acquisition; a record keeping plan (see Section 7.2 for minimum record keeping requirements); the frequency of instrument field check and calibration activities; and the role of individuals performing each specific monitoring activity, as well as QA/QC provisions to ensure that data acquisition and meter calibration are carried out consistently and with precision. The Monitoring Plan shall also contain a detailed diagram of the BCS, including the placement of all meters and equipment that affect SSRs within the GHG Assessment Boundary (see Figure 4.1 and Appendix F).

For a project's second crediting period, the Monitoring Plan must also include procedures that the project developer will follow to ascertain and demonstrate that the project at all times passes the Legal Requirement Test (Section 3.5.2).

Project developers are responsible for monitoring the performance of the project and operating each component of the biogas collection and destruction system in a manner consistent with the manufacturer's recommendations.

6.1 Site-Specific Determination of Maximum Methane Potential (B₀)³⁰

The determination of a site-specific value for maximum methane potential (B_0) is optional for manure from dairy facilities. Swine facilities must use the default values. For projects that choose this option for the quantification of emission reductions related to one or more manure streams being digested in the project's BCS, or the BCS effluent, the following criteria must be met in order to ensure accuracy and consistency of the site-specific B_0 values:

- 1. Manure samples for each eligible livestock category must be sampled prior to mixing with manure from other animal categories or any other waste streams. These samples shall be taken from the manure collection system, rather than from an individual animal.
 - a. Scrape systems: Samples shall be collected from the freshly scraped manure.
 - b. Flush systems: Samples shall be collected at the point that the flushed manure leaves the barn. Additional samples must be collected of the flush water prior to mixing with manure.
 - c. BCS effluent: Samples shall be collected after the effluent has exited the digester and prior to any further treatment.
- 2. Sampling events shall occur during the time period between August and October, inclusive.
 - a. Manure samples: For each eligible animal category, there shall be one single-day sampling event. A total of at least six samples of at least one half liter each must

³⁰ Background information on the development of this section can be found in Appendix E.

be taken during the event. Samples shall be taken one to three hours apart, and all samples of the same type shall be combined (i.e. dairy cow manure samples in one container). The composite sample shall be delivered to the testing laboratory as soon as possible following the collection of the final sample.³¹

- b. Flush water samples: If the farm utilizes a flush system for manure collection, the flush water must be sampled prior to mixing with manure. Two samples of at least one liter shall be collected, one to three hours apart, during the manure sampling event. These samples shall be combined into one container and delivered to the testing laboratory as soon as possible.
- c. Effluent samples: Two samples of at least one liter shall be collected, one to three hours apart, during the manure sampling event. These samples shall be combined into one container and delivered to the testing laboratory as soon as possible.³²
- 3. All samples must be analyzed using a Biochemical Methane Potential (BMP) Assay procedure at an independent, third-party laboratory that is familiar and experienced with this test and ISO 11734.³³ The laboratory must be able to document at least three years of experience with the BMP assay, and must have procedures in place to maintain a consistent inoculum. The laboratory must maintain and follow a standard operating procedure that outlines the process used in undertaking BMP analysis at that laboratory, and which can be made available to the verifier upon request.
- 4. At least six test runs shall be conducted using material from the mixed manure sample (i.e. split the sample into two and test each in triplicate). Tests shall report the weight of VS for the sample (as kg of dry matter) as well as the volume of methane produced, in order to determine the maximum methane potential as m³ CH₄/kg VS. If applicable, the flush water sample and effluent sample shall each be used for one test run in triplicate. The laboratory shall conduct an assay on the seed inoculum itself in order to control for its contribution to the methane potential of the manure samples. The laboratory shall also conduct a control assay with a substrate of known methane potential (such as glucose or cellulose) to verify correct procedures were followed and that the inoculum was viable. If the control assay differs from its established expected value by greater than 15%, all results from that batch of assays shall be discarded. Measurement of gas flow shall be corrected to standard temperature and pressure (60°F and 1 atm). Devices used to measure gas flow and methane content shall be properly installed and calibrated, such that they can provide results within +/- 5% accuracy.
- 5. After the manure sample has been analyzed, there should be at least six estimates for the methane potential. The site specific value for B₀ shall equal the 90% lower confidence limit of all assay results. For flush systems, the mean methane potential of the flush water results must be subtracted from the calculated methane potential of the flushed manure sample. For BCS effluent, the mean methane potential of the test results

³¹ Note, while there is no prescribed timeline regarding how quickly samples must be delivered to a laboratory, the longer a sample is retained before testing, the lower the methane generating potential will be. This loss can be mitigated by storing and transporting samples at temperatures below 5°C.

³² Ibid.

³³ For more information on BMP Assay analysis and procedures, see: Moody et al. "Use of Biochemical Methane Potential (BMP) Assays for Predicting and Enhancing Anaerobic Digester Performance." (2009) <u>http://sa.pfos.hr/sa2009/radovi/pdf/Radovi/r10-009.pdf</u>

shall be used for the quantification. Additional sampling and assays may be carried out, and will reduce uncertainty and result in a final value that is closer to the mean.

Site-specific B_0 values determined using this procedure shall be valid for the reporting period during which the sampling occurred. Projects may elect to determine a site-specific B_0 value for only a subset of the eligible manure streams and utilize default values for the remainder. The verifier must confirm that sampling procedures conform to this section and that the personnel responsible for the sampling are trained and competent.

6.2 Biogas Control System Monitoring Requirements

The methane capture and control system must be monitored with measurement equipment that directly meters:

- The total flow of biogas, measured continuously and recorded every 15 minutes or totalized and recorded at least daily, adjusted for temperature and pressure, prior to delivery to the destruction device(s).
- The flow of biogas delivered to each destruction device (except as described below), measured continuously and recorded at least every 15 minutes or totalized and recorded at least daily, adjusted for temperature and pressure.
- The fraction of methane in the biogas, measured with a continuous analyzer or, alternatively, with at least quarterly measurements.
- The operational status of each destruction device (except as described below), measured and recorded at least hourly.

Flow data must be corrected for temperature and pressure at 60°F and 1 atm, either internally or by following the guidance in Equation 5.6.

A single flow meter may be used to monitor the flow of gas to multiple destruction devices under certain conditions. If all destruction devices are of identical methane destruction efficiency (as described in Table B.7) and verified to be operational (i.e. there is recorded evidence of destruction), no additional steps are necessary for project registration. One example of this scenario would be a single meter used for a bank of multiple, identical engines that are in constant operation. If the destruction devices are not of identical efficiency, then the destruction efficiency of the least efficient device shall be applied to the flow data for this meter. If there are any periods where the operational data show that one or more devices were not destroying methane, these periods are eligible for crediting, provided that the verifier can confirm all of the following conditions are met:

- The destruction efficiency of the least efficient destruction device in operation shall be used as the destruction efficiency for all destruction devices monitored by this meter; and
- b. All devices are either equipped with valves on the input gas line that close automatically if the device becomes non-operational (requiring no manual intervention), or designed in such a manner that it is physically impossible for gas to pass through while the device is non-operational; and
- c. For any period where one or more destruction device(s) within this arrangement is not operational, it must be documented that the remaining operational devices have the capacity to destroy the maximum gas flow recorded during the period. For devices other than flares, it must be shown that the output corresponds to the flow of gas.

Figure 6.1 represents the suggested arrangement of the biogas flow meters and methane concentration metering equipment.



Note: The number of flow meters must be sufficient to track the total flow as well as the flow to each combustion device. The above example includes one more flow meter than would be necessary to achieve this objective. **Figure 6.1.** Suggested Arrangement of Biogas Metering Equipment

Operational activity of the destruction devices shall be monitored and documented at least hourly to ensure actual methane destruction.

If for any reason the destruction device or the operational monitoring equipment (for example, the thermocouple on the flare) is inoperable, then all metered biogas going to the particular device shall be assumed to be released to atmosphere during the period of inoperability. In other words, during the period of inoperability, the destruction efficiency of the device must be assumed to be zero. In Equation 5.10, the monthly destruction efficiency (BDE) value shall be adjusted accordingly. See Box 6.1 below for an example BDE adjustment.

Box 6.1. Example BDE Adjustment

As an example, consider a situation where the primary destruction device is an open flare with a BDE of 96%, and it is found to be inoperable for a period of 5 days of a 30 day month. Assume that the total flow of biogas to the flare for the month is 3,000,000 scf, and that the total flow recorded for the 5 day period of inoperability is 500,000 scf. In this case the monthly BDE would be adjusted as follows:

 $BDE = \frac{\left[(0.96 \times 2,500,000) + (0.0 \times 500,000)\right]}{3,000,000} = 80\%$

6.3 Biogas Measurement Instrument QA/QC

All gas flow meters³⁴ and continuous methane analyzers must be:

- In calibration (accurate to +/- 5% of the true value being measured) at time of installation. Calibration accuracy can be demonstrated through either a recent field check (as installed) or calibration by the manufacturer or a certified calibration service.
- Maintained per manufacturer's guidance, as well as cleaned and inspected on a quarterly basis, with the activities performed and as found/as left condition of the equipment documented.
- Field checked for calibration accuracy by an appropriately trained individual or a thirdparty technician with the percent drift documented, using either a portable instrument (such as a pitot tube)³⁵ or manufacturer specified guidance, at the end of but no more than 60 days prior to or after the end date of the reporting period.³⁶
- Calibrated by the manufacturer or a certified calibration service per manufacturer's guidance or every 5 years, whichever is more frequent. Meters shall be calibrated to the range of conditions expected on site (e.g. pipe diameter, flow rate, temperature, pressure, gas composition) and as found/as left condition of the equipment documented.

If a stationary meter that was in use for 60 days or more is removed and not reinstalled during a reporting period, that meter shall either be field-checked for calibration accuracy prior to removal or calibrated (with percent drift documented) by the manufacturer or a certified calibration service prior to quantification of emission reductions for that reporting period.

If the field check on a piece of equipment reveals accuracy outside of a +/-5% threshold, calibration by the manufacturer or a certified service provider is required for that piece of equipment, with as found/as left condition of the equipment documented.

For the interval between the last successful field check and any calibration event confirming accuracy below the +/- 5% threshold, all data from that meter or analyzer must be scaled according to the following procedure. These adjustments must be made for the entire period from the last successful field check until such time as the meter is properly calibrated and reinstalled.

 For calibrations that indicate the flow meter was outside the +/- 5% accuracy threshold, the project developer shall estimate total emission reductions using i) the metered values without correction, and ii) the metered values adjusted based on the greatest calibration drift recorded at the time of calibration. The lower of the two emission reduction estimates shall be reported as the scaled emission reduction estimate.

³⁴ Field checks and calibrations of flow meters shall assess the volumetric output of the flow meter in SCF at 1 atm pressure and 60°F temperature.

³⁵ It is recommended that a professional third party calibration service be hired to perform flow meter field checks if using pitot tubes or other portable instruments, as these types of devices require professional training in order to achieve accurate readings.

achieve accurate readings. ³⁶ Instead of performing field checks, the project developer may instead have equipment calibrated by the manufacturer or a certified calibration service per manufacturer's guidance, at the end of but no more than 60 days prior to or after the end date of the reporting period to meet this requirement.

For example, if a project conducts field checks quarterly during a year-long verification period, then only three months of data will be subject at any one time to the penalties above. However, if the project developer feels confident that the meter does not require field checks or calibration on a greater than annual basis, then failed events will accordingly require the penalty to be applied to the entire year's data. Further, frequent calibration may minimize the total accrued drift (by zeroing out any error identified), and result in smaller overall deductions.

If a portable instrument is used (such as a handheld methane analyzer), the portable instrument shall be calibrated at least annually – or per the manufacturer's guidance, whichever is more frequent – by the manufacturer or at an ISO 17025 accredited laboratory. Portable methane analyzers shall be calibrated to a known reference gas prior to each use.

6.3.1 Missing Data

In situations where the flow rate or methane concentration monitoring equipment is missing data, the project developer shall apply the data substitution methodology provided in Appendix D. This methodology may also be used for periods where the project developer can show that the data are available but known to be corrupted (and where this corruption can be verified with reasonable assurance). If for any reason the monitoring equipment on any given destruction device is inoperable (for example, the thermocouple on the flare), then the destruction efficiency of that device must be assumed to be zero. For periods when it is not possible to use data substitution to fill data gaps, no emission reductions may be claimed. The methane flow volume for these days shall be zero, and the number of reporting days for that month shall be reduced to exclude the days of missing data (see Box 5.2).

During any period where the project is not claiming emission reduction credits and is not classifying the period as a venting event, the project developer must be able to demonstrate that project emissions were not greater than baseline emissions.

6.4 Monitoring Parameters

Provisions for monitoring other variables to calculate baseline and project emissions are provided in Table 6.1. The parameters are organized by general project factors then by the calculation methods.

Equation Reference	Parameter	Description	Data Unit	Calculated (c) Measured (m) Reference (r) Operating Records (o)	Measurement Frequency	Comment
	Regulations	Project developer attestation to compliance with regulatory requirements relating to the manure digester project	All applicable regulations	n/a	Every verification period	Information used to demonstrate compliance with associated regulations and rules, e.g. criteria pollutant and effluent discharge limits.
	L	Type of livestock categories on the farm	Livestock categories	o	Monthly	See Appendix B, Table B.2.
Equation 5.1	ER _{modeled}	Avoided methane emissions associated with the project during the reporting period	tCO ₂ e	с	Every reporting period	Quantified using a modeled baseline scenario.
Equation 5.1	BE _{modeled}	Modeled baseline emissions during the reporting period	tCO ₂ e	с	Every reporting period	Quantified using a modeled baseline scenario.
Equation 5.1 Equation 5.5	PE _{CH4}	Total project methane emissions during the reporting period	tCO ₂ e	с	Every reporting period	Quantified using a modeled project scenario and metered methane destruction data.
Equation 5.1 Equation 5.12	CO _{2,net}	Net increase in anthropogenic CO ₂ emissions from electricity and mobile/stationary combustion	tCO ₂ e	с	Every reporting period	
Equation 5.1	ER _{metered}	Avoided methane emissions associated with the project during the reporting period	tCO ₂ e	с	Every reporting period	Quantified using metered methane destruction data.
Equation 5.1 Equation 5.11	BE _{metered}	Aggregated quantity of methane collected and destroyed during the reporting period	tCO ₂ e	с	Every reporting period	Quantified using metered methane destruction data.

 Table 6.1. Project Monitoring Parameters

Equation Reference	Parameter	Description	Data Unit	Calculated (c) Measured (m) Reference (r) Operating Records (o)	Measurement Frequency	Comment
Equation 5.2	BE _{CH4,AS,L}	Total baseline methane emissions from anaerobic storage/treatment systems by livestock category, aggregated for reporting period	tCO ₂ e	с	Monthly	
Equation 5.2 Equation 5.4	BE _{CH4,nAS,L}	Total baseline methane emissions for the reporting period from non-anaerobic storage/treatment systems by livestock category	tCO ₂ e	с	Every reporting period	
Equation 5.3	VS _{deg,AS,L}	Monthly volatile solids degraded in each anaerobic storage system <i>AS</i> , for each livestock category <i>L</i>	kg	C, O	Monthly	Calculated value from operating records. Recommend Reserve Livestock Calculation Tool for all calculations.
Equation 5.3 Equation 5.4 Equation 5.10	B _{0,L}	Maximum methane producing capacity for manure by livestock category	(m ³ CH₄/ kg VS)	r	Every reporting period	See Appendix B, Table B.3.
Equation 5.3 Equation 5.8	days _{mo}	Calendar days per month	days	r	Monthly	See Box 5.2.
Equation 5.3 Equation 5.8	rd _{mo}	Reporting days during the current month	days	0	Monthly	See Box 5.2.
Equation 5.3	VS _{avail,AS,L}	Monthly volatile solids available for degradation in each anaerobic storage system, for each livestock category	kg	C, O	Monthly	Calculated value from operating records. Recommend Reserve Livestock Calculation Tool for all calculations.
Equation 5.3 Equation 5.8	f	van't Hoff-Arrhenius factor	n/a	с	Monthly	The proportion of volatile solids that are biologically available for conversion to methane based on the monthly temperature of the system. Recommend Reserve Livestock Calculation Tool for all calculations.
Equation 5.3 Equation 5.4 Equation 5.8 Equation 5.10	VSL	Daily volatile solid production for each livestock category	(kg/animal/ day)	r, c	Every reporting period	Appendix B, Table B.3 and Table B.5a- d; see Box 5.1 for guidance on converting units from (kg/day/1000kg) to (kg/animal/day).

Equation Reference	Parameter	Description	Data Unit	Calculated (c) Measured (m) Reference (r) Operating Records (o)	Measurement Frequency	Comment
Equation 5.3 Equation 5.4 Equation 5.8 Equation 5.10	PL	Average number of animals for each livestock category	population (# head)	0	Monthly	
Equation 5.3	MS _{AS,L}	Fraction of manure from each livestock category managed in the anaerobic waste handling system	%	0	Every reporting period	Reflects the percent of waste handled by the system components S pre- project. Each system component must have an MS value per livestock category. Within each livestock category, the sum of MS values (for all treatment/storage systems) equals 100%. See Appendix B, Table B.1.
Equation 5.3	VS _{avail-1,AS}	Previous month's volatile solids available for degradation in anaerobic system	kg	с	Monthly	
Equation 5.3	VS _{deg-1,AS}	Previous month's volatile solids degraded by anaerobic system	kg	с	Monthly	
Equation 5.3	E	Activation energy constant	cal/mol	r		15,175 cal/mol
Equation 5.3	T _{mo}	Average monthly temperature at location of the operation	°C	m/o	Monthly	Used for van't Hoff calculation and for choosing appropriate MCF value.
Equation 5.3	T _{ref}	Reference temperature	K	r		303.16 Kelvins
Equation 5.3	R	Ideal gas constant	cal/Kmol	r		1.987 cal/Kmol
Equation 5.4	MS _{L,nAS}	Fraction of manure from each livestock category <i>L</i> managed in the non-anaerobic waste handling system	%	0	Every reporting period	Reflects the percent of waste handled by the system components <i>S</i> pre- project. Each system component must have an MS value per livestock category. Within each livestock category, the sum of MS values (for all treatment/storage systems) equals 100%. See Appendix B, Table B.1.
Equation 5.4	days _{rp}	Number of days in the reporting period	days	0	Every reporting period	See Box 5.2.
Equation 5.4	MCF _{nAS}	Methane conversion factor for non-anaerobic storage/treatment system	%	r	Every reporting period	From Appendix B. Differentiate by livestock category.

Equation Reference	Parameter	Description	Data Unit	Calculated (c) Measured (m) Reference (r) Operating Records (o)	Measurement Frequency	Comment
Equation 5.4 Equation 5.9 Equation 5.10	rd _{rp}	Reporting days during the reporting period	days		Every reporting period	See Box 5.2.
Equation 5.5 Equation 5.6	PE _{CH4,BCS}	Methane emissions from the BCS	tCH ₄	m, c	Every reporting period	Calculated for each month and summed for the reporting period.
Equation 5.5 Equation 5.8	PE _{CH4,ET,AS}	Methane emissions from the BCS effluent anaerobic treatment systems	tCH₄	m, c	Every reporting period	Calculated for each month and summed for the reporting period.
Equation 5.5 Equation 5.9	PE _{CH4,ET,nAS}	Methane emissions from the BCS effluent non-anaerobic treatment systems	tCH₄	m, c	Every reporting period	Calculated for the reporting period.
Equation 5.5 Equation 5.10	PE _{CH4,other}	Methane emissions from sources in the waste treatment and storage category other than the BCS and associated effluent treatment systems	tCH ₄	m, c	Every reporting period	Calculated for the reporting period.
Equation 5.6 Equation 5.11	CH _{4,metered,i}	Metered amount of methane collected and destroyed by the BCS in month <i>i</i>	tCH₄	m, c	Monthly calculation from continuous data	Calculated from biogas flow and methane fraction meter readings (See <i>F</i> and <i>CH</i> _{4,conc} parameters below).
Equation 5.6	BCE	Biogas capture efficiency of the anaerobic digester, accounts for fugitive emissions	fraction	r	Every reporting period	Use default value from Table B.4.
Equation 5.6 Equation 5.11	BDE _{i,weighted}	Methane destruction efficiency of destruction device(s)	fraction	r, c	Monthly	Actual efficiency of the system to destroy captured methane gas – accounts for different destruction devices.
Equation 5.6 Equation 5.7	CH _{4,vent,i}	Quantity of methane that is vented to the atmosphere due to BCS venting events	scf	с	Monthly	Calculated from average total flow of biogas from the digester and the number of days biogas is venting.
Equation 5.6	F	Volume of biogas from digester to destruction devices	scf	m	Continuously, aggregated monthly	Measured continuously from flow meter and recorded every 15 minutes or totalized and recorded at least once daily. Data to be aggregated monthly.

Equation Reference	Parameter	Description	Data Unit	Calculated (c) Measured (m) Reference (r) Operating Records (o)	Measurement Frequency	Comment
Equation 5.6	T _b	Temperature of the biogas	°R (Rankine)	m	Continuously, averaged monthly	Measured to normalize volume flow of biogas to STP. No separate monitoring of temperature is necessary when using flow meters that automatically measure temperature and pressure, expressing biogas volumes in normalized cubic feet.
Equation 5.6	Ρ	Pressure of the biogas	atm	m	Continuously, averaged monthly	Measured to normalize volume flow of biogas to STP. No separate monitoring of pressure is necessary when using flow meters that automatically measure temperature and pressure, expressing biogas volumes in normalized cubic feet.
Equation 5.6 Equation 5.7	CH _{4,conc}	Methane concentration of biogas	fraction	m	At least quarterly	Samples to be taken at least quarterly. See Section 6.2 for metering guidance.
Equation 5.6	BDE _{DD}	Default methane destruction efficiency of a particular destruction device	%	r	Monthly	See Appendix B for default destruction efficiencies by device.
Equation 5.6	F _{i,DD}	Flow of biogas to a particular destruction device	scf	m	Monthly	See Section 6.2 for metering guidance.
Equation 5.6	Fi	Total volumetric flow of biogas to all destruction devices	scf	m	Monthly	See Section 6.2 for metering guidance.
Equation 5.7	MGS _{BCS}	Maximum biogas storage of the BCS system	scf	r	Every reporting period	Obtained from digester system design plans. Necessary to quantify the release of methane to the atmosphere due to an uncontrolled venting event.
Equation 5.7	F _{pw}	Average total daily flow of biogas from the digester for the entire week prior to the uncontrolled venting event	scf/day	m	Weekly	Average flow of biogas can be determined from the daily records from the previous week.
Equation 5.7	t	Number of days of the month that biogas is venting uncontrolled from the BCS system	days	m, o	Monthly	

Equation Reference	Parameter	Description	Data Unit	Calculated (c) Measured (m) Reference (r) Operating Records (o)	Measurement Frequency	Comment
Equation 5.8 Equation 5.9	VS _{ET,i}	Volatile solids to effluent treatment system <i>i</i>	kg/day	r, c	Every reporting period	If project uses effluent pond, equals 30% of the average daily VS entering the digester.
Equation 5.8 Equation 5.9	B _{0,ET}	Maximum methane producing capacity of VS dry matter	(m ³ CH₄/ kg VS)	с	Every reporting period	An average of the $B_{0,EF}$ value of the operation's livestock categories that contributes manure to the BCS.
Equation 5.8	MS _{L,BCS}	Fraction of manure from each livestock category managed in the BCS	fraction	ο	Every reporting period	Used to determine the total VS entering the digester. The fraction should be tracked in operational records.
Equation 5.8	ETFi	Fraction of the effluent that exits the digester that is sent to effluent treatment system		o, r	Every reporting period	Used to determine the amount of VS for each effluent treatment system. The percentage should be tracked in operational records, or the project developer may provide a technical reference to support this fraction.
Equation 5.9	$MCF_{ET,i}$	Methane conversion factor for effluent treatment system	%	r	Every reporting period	See Appendix B. Project developers should use the <i>liquid slurry</i> MCF value.
Equation 5.10	MCFnon-BCS	Management-weighted methane conversion factor for waste treatment and storage systems other than the BCS and associated effluent treatment systems	%	r	Every reporting period	Referenced from Appendix B.
Equation 5.10	MCFs	Methane conversion factor for system component		r		See Table B.9.
Equation 5.10	MS _{L,S}	Manure from each livestock category managed in the baseline waste handling system	fraction	0	Every reporting period	Fraction of waste handled by the system component S pre-project. Each system component must have an MS value per livestock category. Within each livestock category, the sum of MS values (for all treatment/storage systems) equals 1. See Appendix B, Table B.1.
Equation 5.12	BE _{CO2,MSC}	Total baseline CO ₂ emissions from electricity and mobile/stationary combustion during reporting period	tCO ₂	с	Every reporting period	

Equation Reference	Parameter	Description	Data Unit	Calculated (c) Measured (m) Reference (r) Operating Records (o)	Measurement Frequency	Comment
Equation 5.12	PE _{CO2,MSC}	Total project CO ₂ emissions from electricity and mobile/stationary combustion during reporting period	tCO ₂	с	Every reporting period	
Equation 5.12	CO _{2,MSC}	Anthropogenic CO ₂ emissions from electricity and mobile/stationary combustion	tCO ₂	с	Every reporting period	
Equation 5.12	QEc	Quantity of electricity consumed	MWh	0, C	Every reporting period	Electricity used by project for manure collection, transport, treatment/storage, and disposal.
Equation 5.12	EF _{CO2,e}	Emission factor for electricity used by project	tCO ₂ /MWh	r	Every reporting period	See Appendix B. If biogas produced from digester is used to generate electricity consumed, the EF is zero.
Equation 5.12	QFc	Quantity of fuel used for mobile/stationary combustion sources	MMBtu or gallons	o, c	Every reporting period	Fuel used by project for manure collection, transport, treatment/storage, and disposal, and stationary combustion sources including supplemental fossil fuels used in combustion device.
Equation 5.12	EF _{CO2,f}	Fuel-specific emission factor for mobile/stationary combustion sources	kg CO ₂ / MMBtu or kg CO ₂ / gallon	r	Every reporting period	Refer to EPA eGRID for emission factors. If biogas produced from digester is used as an energy source, the EF is zero.

7 Reporting Parameters

This section provides requirements and guidance on reporting rules and procedures. A priority of the Reserve is to facilitate consistent and transparent information disclosure among project developers. Project developers must submit either a project monitoring report or a verified emission reduction report to the Reserve annually at minimum, depending on the verification option selected by the project developer.

7.1 Project Documentation

Project developers must provide the following documentation to the Reserve in order to register a livestock project:

- Project Submittal form
- Project diagram from Monitoring Plan see Appendix F (not public)
- Completed Reserve Livestock Calculation Tool, if used (not public)
- Signed Attestation of Title form
- Signed Attestation of Voluntary Implementation form³⁷
- Signed Attestation of Regulatory Compliance form
- Verification Report
- Verification Statement

Project developers must provide the following documentation each verification period in order for the Reserve to issue CRTs for quantified GHG reductions:

- Verification Report
- Verification Statement
- Project diagram from Monitoring Plan see Appendix F (not public)
- Completed Reserve Livestock Calculation Tool, if used (not public)
- Signed Attestation of Title form
- Signed Attestation of Regulatory Compliance form
- Signed Attestation of Voluntary Implementation form (second crediting period only)

Unless otherwise specified, the above project documentation will be available to the public via the Reserve's online registry. Further disclosure and other documentation may be made available on a voluntary basis through the Reserve. Project forms can be found athttp://www.climateactionreserve.org/how/program/documents/. .

7.2 Record Keeping

For purposes of independent verification and historical documentation, project developers are required to keep all information outlined in this protocol for a period of 10 years after the information is generated or 7 years after the last verification. This information will not be publicly available, but may be requested by the verifier or the Reserve.

³⁷ A project developer only needs to attest that the project passes the Legal Requirement Test during its first verification period of a crediting period. Meeting the Legal Requirement Test is not required for the remainder of the first crediting period after initial verification.

System Information:

- All data inputs for the calculation of the baseline emissions and project emission reductions
- CO₂e annual tonnage calculations (including copies of the Reserve Livestock Calculation Tool, if used)
- Relevant sections of the BCS operating permits
- Executed Attestation of Title forms, Attestation of Regulatory Compliance forms, and Attestation of Voluntary Implementation form
- BCS information (installation dates, equipment list, etc.)
- Biogas flow meter information (model number, serial number, manufacturer's calibration procedures)
- Cleaning and inspection records for all biogas meters
- Field check results for all biogas meters
- Calibration results for all biogas meters
- Methane monitor information (model number, serial number, calibration procedures)
- Biogas flow data (for each flow meter)
- Biogas temperature and pressure readings (only if flow meter does not correct for temperature and pressure automatically)
- Methane concentration monitoring data
- Destruction device monitoring data (for each destruction device)
- Destruction device, methane monitor and biogas flow monitor information (model numbers, serial numbers, calibration procedures)
- Initial and annual verification records and results
- All maintenance records relevant to the BCS, monitoring equipment, and destruction devices

If using a calibrated portable gas analyzer for CH_4 content measurement:

- Date, time, and location of methane measurement
- Methane content of biogas (% by volume) for each measurement
- Methane measurement instrument type and serial number
- Date, time, and results of instrument calibration
- Corrective measures taken if instrument does not meet performance specifications

7.3 Reporting and Verification Cycle

To provide flexibility and help manage verification costs associated with livestock projects, there are three verification options to choose from after a project's initial verification and registration. Regardless of the option selected, project developers must report GHG reductions resulting from project activities during each reporting period. A "reporting period" is a period of time over which a project developer quantifies and reports GHG reductions to the Reserve. Under this protocol, the reporting period cannot exceed 12 months. A "verification period" is the period of time over which GHG reductions are verified. Under this protocol, a verification period may cover multiple reporting periods (see Section 7.3.4). The end date of any verification period must correspond to the end date of a reporting period.

A project developer may choose to utilize one option for the duration of a project's crediting period, or may choose different options at different points during a single crediting period. Regardless of the option selected, reporting periods must be contiguous; there may be no time gaps in reporting during the crediting period of a project once the initial reporting period has commenced.

7.3.1 Initial Reporting and Verification Period

While a reporting period cannot exceed 12 months, a project developer may register multiple reporting periods (i.e. more than 12 months of data) during a project's initial verification period. A project developer may also register a project's initial verification period as a zero-credit reporting period (see the Reserve Program Manual for more information on zero-credit reporting periods).

Once a project is registered and has had at least 3 months of emission reductions verified, the project developer may choose one of the verification options below.

7.3.2 Option 1: Twelve-Month Maximum Verification Period

Under this option, the verification period may not exceed 12 months. Verification with a site visit is required for CRT issuance. The project developer may choose to have a sub-annual verification period (e.g. quarterly or semi-annually).

7.3.3 Option 2: Twelve-Month Verification Period with Desktop Verification

Under this option, the verification period cannot exceed 12 months. However, CRTs may be issued upon successful completion of a desktop verification as long as: (1) site-visit verifications occur at two-year intervals; and (2) the verifier has confirmed that there have been no significant changes in data management systems, equipment, or personnel since the previous site visit. Desktop verifications must cover all other required verification activities.

In order to utilize this option, there are two additional requirements that must be satisfied:

- Prior to a desktop verification commencing, the project developer must attest to the verifier that there have been no significant changes to the project's data management systems, project set up/equipment, or site personnel involved with the project since the last site-visit verification. For each verification period, the project developer must provide the following documentation for review by the verifier prior to the desktop verification commencing:
 - a. A schematic of system equipment and configuration, detailing any changes since the previous site visit, and any other supporting documentation for system or operation changes
 - b. A list of personnel performing key functions related to project activities (personnel who manage and perform monitoring, measurement, and instrument QA/QC activities for the project), and documentation of any personnel or roles or changes since the pervious site visit; this shall include documented handover of personnel changes, including personnel change dates
 - c. The sections from the Monitoring Plan that summarize the data management systems and processes in place and a summary of any changes to the systems or processes since the previous site visit
- 2. Desktop verifications must be conducted by the same verification body that conducted the most recent site-visit verification.

For projects using this option, the initial verification in this cycle shall be a full verification, including a site visit, and shall cover a minimum of 3 months and maximum 12 months of project data. All subsequent verification periods under this option shall be 12-month verification periods. Projects that wish to upgrade to the latest protocol version from a previous version whilst simultaneously taking advantage of the desktop verification option shall be allowed to do so, provided:

- i. The verification of the previous verification period (e.g. under Version 2.1, 2.2 or 3.0) was a full verification, including site visit, and covered a minimum of 3 months of project data, and
- ii. The two additional requirements specified in Section 7.3.3 are satisfied.

Taking into consideration the Reserve's policy that a verification body may provide verification services to a project for a maximum of six consecutive years (see the Verification Program Manual, Section 2.6 for more information), Table 7.1 below details what the verification cycle might look under Option 2.

Reporting Period	Verification Activity	Verification Body (VB)
Year 1 (initial verification)	Site-visit verification	VB A
Year 2	Desktop verification	VB A
Year 3	Site-visit verification	VB A
Year 4	Desktop verification	VB A
Year 5	Site-visit verification	VB A
Year 6	Desktop verification	VB A
Year 7	Site-visit verification	VB B (new verification body)
Year 8	Desktop verification	VB B

Table 7.1. Sample Verification Cycle under Option 2

7.3.4 Option 3: Twenty-Four Month Maximum Verification Period

Under this option, the verification period cannot exceed 24 months and the project's monitoring report must be submitted to the Reserve for the interim 12 month reporting period. The project monitoring report must be submitted for projects that choose Option 3 to meet the annual documentation requirement of the Reserve program. It is meant to provide the Reserve with information and documentation on a project's operations and performance, and adherence to the project's monitoring plan. It is submitted via the Reserve's online registry, but is not a publicly available document. A monitoring report template for livestock projects is available at http://www.climateactionreserve.org/how/program/documents/. The monitoring report shall be submitted within 30 days of the end of the interim reporting period. The only exception to this requirement is for projects that verify under Option 3 as part of a protocol upgrade, and fall within the specific timeline outlined below.

Project developers that wish to upgrade to Version 4.0 of this protocol and immediately utilize the 24-month verification period shall be allowed to do so, provided that the verification of the previous verification period (e.g. under Version 2.0, 2.1, 2.2, or 3.0) was a full verification, including a site visit, and covered a minimum of 3 months of project data.

All project developers utilizing the 24-month verification period must submit the monitoring report within 30 days of the end of the interim reporting period.

Under this option, CRTs may be issued upon successful completion of a site-visit verification for GHG reductions achieved over a maximum of 24 months. CRTs will not be issued based on the Reserve's review of project monitoring plans/reports. Project developers may choose to have a verification period shorter than 24 months.

Taking into consideration the Reserve's policy that a verification body may provide verification services to a project for a maximum of six consecutive years (see the Verification Program Manual, Section 2.6 for more information), Table 7.2 below details what the verification cycle might look under Option 3.

Reporting Period	Verification Activity	Verification Body (VB)
Year 1 (initial verification)	Site-visit verification	VB A
Year 2	Project monitoring plan and report submitted to Reserve	n/a
Year 3	Site-visit verification for years 2 & 3	VB A
Year 4	Project monitoring plan and report submitted to Reserve	n/a
Year 5	Site-visit verification for years 4 & 5	VB A
Year 6	Project monitoring plan and report submitted to Reserve	n/a
Year 7	Site-visit verification for years 6 & 7	VB B (new verification body)
Year 8	Project monitoring plan and report submitted to Reserve	n/a

Table 7.2. Sample Verification Cycle under Option 3

8 Verification Guidance

This section provides verification bodies with guidance on verifying GHG emission reductions associated with installing a biogas control system for manure management on dairy cattle and swine farms. This verification guidance supplements the Reserve's Verification Program Manual and describes verification activities specifically related to livestock manure management projects.

Verification bodies trained to verify livestock projects must be familiar with the following documents:

- Climate Action Reserve Program Manual
- Climate Action Reserve Verification Program Manual
- Climate Action Reserve U.S. Livestock Project Protocol

The Reserve's Program Manual, Verification Program Manual, and project protocols are designed to be compatible with each other and are available on the Reserve's website at <u>http://www.climateactionreserve.org</u>.

In cases where the Program Manual and/or Verification Program Manual differ from the guidance in this protocol, this protocol takes precedent.

Only Reserve-approved verification bodies are eligible to verify livestock project reports. Verification bodies approved under other project protocol types are not permitted to verify livestock projects. Information about verification body accreditation and Reserve project verification training can be found on the Reserve website at http://www.climateactionreserve.org.

8.1 Standard of Verification

The Reserve's standard of verification for livestock projects is the U.S. Livestock Project Protocol (this document), the Reserve Program Manual, and the Verification Program Manual. To verify a livestock project report, verification bodies apply the guidance in the Verification Program Manual and this section of the protocol to the standards described in Sections 2 through 7 of this protocol. Sections 2 through 7 provide eligibility rules, methods to calculate emission reductions, performance monitoring instructions and requirements, and procedures for reporting project information to the Reserve.

8.2 Monitoring Plan

The Monitoring Plan serves as the basis for verification bodies to confirm that the monitoring and reporting requirements in Section 6 and Section 7 have been met, and that consistent, rigorous monitoring and record-keeping is ongoing at the project site. Verification bodies shall confirm that the Monitoring Plan covers all aspects of monitoring and reporting contained in this protocol and specifies how data for all relevant parameters in Section 6 are collected and recorded.

8.3 Verifying Project Eligibility

Verification bodies must affirm a livestock project's eligibility according to the rules described in this protocol. The table below outlines the eligibility criteria for livestock projects. This table does

not present all criteria for determining eligibility comprehensively; verification bodies must also look to Section 3 and the verification items list in Table 8.2.

Eligibility Rule	Eligibility Criteria	Frequency of Rule Application
Start Date	Projects must be submitted for listing within 6 months of the project start date	Once during first verification
Location	United States, its territories, and U.S. tribal areas	Once during first verification
Performance Standard Test	Installation of a biogas control system that captures and destroys methane gas from anaerobic manure treatment and/or storage facilities on livestock operations	Once during first verification
Anaerobic Baseline	Projects must demonstrate that the depth of the anaerobic lagoons or ponds prior to the project's implementation were sufficient to prevent algal oxygen production and create an oxygen-free bottom layer; which means at least 1 meter in liquid depth	Once during first verification
Legal Requirement Test	Signed Attestation of Voluntary Implementation form and additional documentation demonstrating that the project passes the Legal Requirement Test	Once during first verification for first crediting period; every verification for second crediting period
Regulatory Compliance	Signed Attestation of Regulatory Compliance form and disclosure of all non-compliance events to verifier, and monitoring; project must be in material compliance with all applicable laws	Every verification

Table 8.1. Summary of Eligibility Criteria for a Livestock Project

8.4 Core Verification Activities

The U.S. Livestock Project Protocol provides explicit requirements and guidance for quantifying the GHG reductions associated with installing a BCS to capture and destroy methane gas from livestock operations. The Verification Program Manual describes the core verification activities that shall be performed by verification bodies for all project verifications. They are summarized below in the context of a livestock project, but verification bodies must also follow the general guidance in the Verification Program Manual.

Verification is a risk assessment and data sampling effort designed to ensure that the risk of reporting error is assessed and addressed through appropriate sampling, testing, and review. The three core verification activities are:

- 1. Identifying emission sources, sinks, and reservoirs
- 2. Reviewing GHG management systems and estimation methodologies
- 3. Verifying emission reduction estimates

Identifying emission sources, sinks, and reservoirs

The verification body reviews for completeness the SSRs identified for a project, such as energy use waste collection and transport, treatment and storage, and uncombusted methane from the biogas control system.

Reviewing GHG management systems and estimation methodologies

The verification body reviews and assesses the appropriateness of the methodologies and management systems that the livestock project operator uses to gather data and calculate baseline and project emissions. This includes the examination of assertions or assumptions regarding MS, the percentage of manure going to anaerobic treatment systems in the baseline, and the baseline lagoon cleaning frequency.

Verifying emission reduction estimates

The verification body further investigates areas that have the greatest potential for material misstatements and then confirms whether or not material misstatements have occurred. This involves site visits to the project to ensure the systems on the ground correspond to and are consistent with data provided to the verification body. In addition, the verification body recalculates a representative sample of the performance or emissions data for comparison with data reported by the project developer in order to double-check the calculations of GHG emission reductions.

8.5 Verification Period

Per Section 7.3, this protocol provides project developers three verification options for a project after its initial verification and registration in order to provide flexibility and help manage verification costs associated with livestock projects. The different options require verification bodies to confirm additional requirements specific to this protocol, and in some instances, to utilize professional judgment on the appropriateness of the option selected.

8.5.1 Option 1: Twelve-Month Maximum Verification Period

Option 1 does not require verification bodies to confirm any additional requirements beyond what is specified in the protocol.

8.5.2 Option 2: Twelve-Month Verification Period with Desktop Verification

Option 2 requires verification bodies to review the documentation specified in Section 7.3.3 in order to determine if a desktop verification is appropriate. The verifier shall use his/her professional judgment to assess any changes that have occurred related to a project's data management systems, equipment, or personnel and determine whether a site visit should be required as part of verification activities in order to provide a reasonable level of assurance on the project's verification. The documentation shall be reviewed prior to the COI/NOVA renewal being submitted to the Reserve, and the verification body shall provide a summary of its assessment and decision on the appropriateness of a desktop verification when submitting the COI/NOVA renewal. The Reserve reserves the right to review the documentation provided by the project developer and the decision made by the verification body on whether a desktop verification is appropriate.

8.5.3 Option 3: Twenty-Four Month Maximum Verification Period

Under Option 3 (see Section 7.3.4), verification bodies shall look to the project monitoring report submitted by the project developer to the Reserve for the interim 12 month reporting period as a resource to inform its planned verification activities. While verification bodies are not expected to provide a reasonable level of assurance on the accuracy of the monitoring report as part of verification, the verification body shall list a summary of discrepancies between the monitoring report and what was ultimately verified in the List of Findings.

8.6 Livestock Verification Items

The following tables provide lists of items that a verification body needs to address while verifying a livestock project. The tables include references to the section in the protocol where requirements are further specified. The table also identifies items for which a verification body is expected to apply professional judgment during the verification process. Verification bodies are expected to use their professional judgment to confirm that protocol requirements have been met in instances where the protocol does not provide (sufficiently) prescriptive guidance. For more information on the Reserve's verification process and professional judgment, please see the Verification Program Manual.

Note: These tables shall not be viewed as a comprehensive list or plan for verification activities, but rather guidance on areas specific to livestock projects that must be addressed during verification.

8.6.1 Project Eligibility and CRT Issuance

Table 8.2 lists the criteria for reasonable assurance with respect to eligibility and CRT issuance for livestock projects. These requirements determine if a project is eligible to register with the Reserve and/or have CRTs issued for the reporting period. If any requirement is not met, either the project may be determined ineligible or the GHG reductions from the reporting period (or sub-set of the reporting period) may be ineligible for issuance of CRTs, as specified in Sections 2, 3, and 6.

Protocol Section	Eligibility Qualification Item	Apply Professional Judgment?
2.1	Verify that the project meets the definition of a livestock project	No
2.2	Verify ownership of the reductions by reviewing Attestation of Title and other relevant contracts, documentation	No
3.2	Verify eligibility of project start date	No
3.2	Verify accuracy of project start date based on operational records	Yes
3.3	Verify that project is within its 10-year crediting period	No
3.4	Verify that all pre-project manure treatment lagoons/ponds/tanks were of sufficient depth to ensure an oxygen free bottom layer (> 1m)	Yes
3.4	Verify that the pre-project manure management system met the requirements of this section for the relevant period of time	Yes
3.4	If the project is a greenfield project, verify that the project site meets the definition of a greenfield	Yes
3.5.1	Verify that the project meets the Performance Standard Test	No
3.5.2	Confirm execution of the Attestation of Voluntary Implementation form to demonstrate eligibility under the Legal Requirement Test (initial verification only)	No
3.6	Verify that the project activities comply with applicable laws by reviewing instances of non-compliance provided by the project developer and performing a risk-based assessment to confirm the statements made by the project developer in the Attestation of Regulatory Compliance form	Yes
6	Verify that monitoring meets the requirements of the protocol. If it does not, verify that variance has been approved for monitoring variations	No
6	Verify that all gas flow meters and continuous methane analyzers adhered to the inspection, cleaning, and calibration schedule specified in the protocol. If they do not, verify that a variance has been approved for	No

Table 8.2. Eligibility Verification Items

Protocol Section	Eligibility Qualification Item	Apply Professional Judgment?
	monitoring variations or that adjustments have been made to data per the protocol requirements	
6	Verify that adjustments for failed calibrations were properly applied	No
6, Appendix D	If used, verify that data substitution methodology was properly applied	No

8.6.2 Quantification

Table 8.3 lists the items that verification bodies shall include in their risk assessment and recalculation of the project's GHG emission reductions. These quantification items inform any determination as to whether there are material and/or immaterial misstatements in the project's GHG emission reduction calculations. If there are material misstatements, the calculations must be revised before CRTs are issued.

Table 8.3. Quantification Verification Items

Protocol Section	Quantification Item	Apply Professional Judgment?
4	Verify that all SSRs in the GHG Assessment Boundary are accounted for	No
5	Verify that the modeled baseline is compared with the total amount of methane metered and destroyed by the project, and the lesser of the two values is used as the baseline for the GHG reduction calculation	No
5.1	Verify that the livestock categories (L) are correctly differentiated	Yes
5.1	Verify that the project developer applied the correct VS and B ₀ values for each livestock category	No
5.1, 6.1	If site-specific B ₀ values were developed, verify that the sampling and analysis procedures were correctly followed	Yes
5.1	Verify that the fraction of manure (MS) handled by the different manure management system components (i.e. GHG source) is satisfactorily represented	Yes
5.1	Verify that the baseline lagoon cleaning frequency is satisfactorily represented	Yes
5.1	Verify that the project developer used methane conversion factors (MCF) differentiated by temperature	No
5.1	Verify that the methane baseline emissions calculations for each livestock category were calculated according to the protocol with the appropriate data	No
5.1	Verify that the project developer correctly aggregated methane emissions from sources within each livestock category	Yes
5.4	Verify that the project developer correctly monitored, quantified and aggregated electricity use	Yes
5.2, 5.4	Verify that the project developer correctly monitored, quantified and aggregated fossil fuel use	Yes
5.2, 5.4	Verify that the project developer applied the correct emission factors for fossil fuel combustion and grid-delivered electricity	No
5.2	Verify that the project developer applied the correct methane destruction efficiencies	No
5.2	Verify that the project developer applied the correct B ₀ value for Modeled Project Methane Emissions from Anaerobic Treatment of BCS Effluent	No
5.2	Verify that the project developer correctly quantified the amount of uncombusted methane	No

Protocol Section	Quantification Item	Apply Professional Judgment?
5.2	Verify that methane emissions resulting from any venting event are estimated correctly	Yes
5.2, 5.4	Verify that the project emissions calculations were calculated according to the protocol with the appropriate data	No
5.2, 5.1	Verify that the project developer assessed baseline and project emissions on a month-to-month basis	No
5.2	Verify that the project developer correctly monitored and quantified the amount of methane destroyed by the project	No
5.3	Verify that the modeled methane emission reductions are compared with the <i>ex-post</i> methane metered and destroyed by the project, and the lesser of the two values is used to quantify project emission reductions	No

8.6.3 Risk Assessment

Verification bodies will review the following items in Table 8.4 to guide and prioritize their assessment of data used in determining eligibility and quantifying GHG emission reductions.

Protocol Section	Item that Informs Risk Assessment	Apply Professional Judgment?
6	Verify that the project Monitoring Plan is sufficiently rigorous to support the requirements of the protocol and proper operation of the project	Yes
6	Verify that the BCS was operated and maintained according to manufacturer specifications	No
6	Verify that appropriate monitoring equipment is in place to meet the requirements of the protocol	No
6	Verify that the individual or team responsible for managing and reporting project activities are qualified to perform this function	Yes
6	Verify that appropriate training was provided to personnel assigned to greenhouse gas reporting duties	Yes
6	Verify that all contractors are qualified for managing and reporting greenhouse gas emissions if relied upon by the project developer. Verify that there is internal oversight to assure the quality of the contractor's work	Yes
7.2	Verify that all required records have been retained by the project developer	No

Table 8.4.	Risk Assessment	Verification	Items

8.7 Completing Verification

The Verification Program Manual provides detailed information and instructions for verification bodies to finalize the verification process. It describes completing a Verification Report, preparing a Verification Statement, submitting the necessary documents to the Reserve, and notifying the Reserve of the project's verified status.

9 Glossary of Terms

Accredited verifier	A verification firm approved by the Reserve to provide verification services for project developers.
Additionality	Manure management practices that are above and beyond business-as-usual operation, exceed the baseline characterization, and are not mandated by regulation.
Anaerobic	Pertaining to or caused by the absence of oxygen.
Anthropogenic emissions	GHG emissions resultant from human activity that are considered to be an unnatural component of the Carbon Cycle (i.e. fossil fuel combustion, deforestation etc.).
Biogas	The mixture of gas (largely methane) produced as a result of the anaerobic decomposition of livestock manure.
Biogas control system (BCS)	A system designed to capture and destroy the biogas that is produced by the anaerobic treatment and/or storage of livestock manure and/or other organic material. Commonly referred to as a "digester."
Biogenic CO ₂ emissions	CO_2 emissions resulting from the combustion and/or aerobic decomposition of organic matter. Biogenic emissions are considered to be a natural part of the carbon cycle, as opposed to anthropogenic emissions.
Carbon dioxide (CO ₂)	The most common of the six primary greenhouse gases, consisting of a single carbon atom and two oxygen atoms.
CO_2 equivalent (CO_2 e)	The quantity of a given GHG multiplied by its total global warming potential. This is the standard unit for comparing the degree of warming which can be caused by different GHGs.
Direct emissions	Greenhouse gas emissions from sources that are owned or controlled by the reporting entity.
Emission factor	A unique value for determining an amount of a greenhouse gas emitted for a given quantity of activity data (e.g. metric tons of carbon dioxide emitted per barrel of fossil fuel burned).
Flare	A destruction device that uses an open flame to burn combustible gases with combustion air provided by uncontrolled ambient air around the flame.
Fossil fuel	A fuel, such as coal, oil, and natural gas, produced by the decomposition of ancient (fossilized) plants and animals.
Greenfield	For the purposes of this protocol, a livestock facility that has been in operation for less than two years at a site that had no prior manure management infrastructure.
Greenhouse gas	Carbon dioxide (CO ₂), methane (CH ₄), nitrous oxide (N ₂ O),

(GHG)	sulfur hexafluoride (SF ₆), hydrofluorocarbons (HFCs) or perfluorocarbons (PFCs).
Global warming potential (GWP)	The ratio of radiative forcing (degree of warming to the atmosphere) that would result from the emission of one unit of a given GHG compared to one unit of CO_2 .
Indirect emissions	Emissions that are a consequence of the actions of a reporting entity, but are produced by sources owned or controlled by another entity.
Livestock project	Installation of a biogas control system that, in operation, causes a decrease in GHG emissions from the baseline scenario through destruction of the methane component of biogas.
Metric ton (tonne, MT, t)	A common international measurement for the quantity of GHG emissions, equivalent to about 2204.6 pounds or 1.1 short tons.
Methane (CH ₄)	A potent GHG with a GWP of 21, consisting of a single carbon atom and four hydrogen atoms.
MMBtu	One million British thermal units.
Mobile combustion	Emissions from the transportation of materials, products, waste, and employees resulting from the combustion of fuels in company owned or controlled mobile combustion sources (e.g. cars, trucks, tractors, dozers, etc.).
Nitrous oxide (N ₂ O)	A GHG consisting of two nitrogen atoms and a single oxygen atom.
Project baseline	A business-as-usual GHG emission assessment against which GHG emission reductions from a specific GHG reduction activity are measured.
Project developer	An entity that undertakes a project activity, as identified in the Livestock Project Protocol. A project developer may be an independent third party or the dairy/swine operating entity.
Reporting period	The period of time over which a project developer quantifies and reports GHG reductions to the Reserve. Under this protocol, the reporting period cannot exceed 12 months.
Stationary combustion source	A stationary source of emissions from the production of electricity, heat, or steam, resulting from combustion of fuels in boilers, furnaces, turbines, kilns, and other facility equipment.
van't Hoff-Arrhenius factor (<i>f</i>)	The proportion of volatile solids that are biologically available for conversion to methane based on the monthly temperature of the system. ³⁸

³⁸ Mangino, et al.
Verification	The process used to ensure that a given participant's greenhouse gas emissions or emission reductions have met the minimum quality standard and complied with the Reserve's procedures and protocols for calculating and reporting GHG emissions and emission reductions.					
Verification body	An accredited firm that is able to render a verification opinion and provide verification services for operators subject to reporting under this protocol.					
Verification period	The period of time over which GHG reductions are verified. Under this protocol, a verification period may cover multiple reporting periods (see Section 7.3.4). The end date of any verification period must correspond to the end date of a reporting period.					

10 References

American Society of Agricultural Engineers, Standard: ASAE D384.2 (2005).

Intergovernmental Panel on Climate Change, Good Practice Guidance and Uncertainty Management in National Greenhouse Gas Inventories (2001).

Intergovernmental Panel on Climate Change, IPCC Guidelines for National Greenhouse Gas Inventories, Chapter 10: Emissions from Livestock and Manure Management (2006).

Intergovernmental Panel on Climate Change, IPCC Guidelines for National Greenhouse Gas Inventories, Chapter 11: N20 Emissions from Managed Soils, and CO2 Emissions from Lime and Urea Application (2006).

Regional Greenhouse Gas Initiative, Draft Model Rule (January 2007).

Mangino, J., Bartram, D. and Brazy, A. Development of a methane conversion factor to estimate emissions from animal waste lagoons. Presented at U.S. EPA's 17th Annual Emission Inventory Conference, Atlanta GA, April 16-18, 2001.

Moser, M., Dr. J. Martin, A. Martin, R.P. Mattocks. Pig Manure Solids Separation. Unpublished report prepared by ICF Inc. for the Engineering Analysis Division, United States Environmental Protection Agency, Washington, DC. (1999).

Solid Waste Association of North America, Landfill gas operation and maintenance, manual of practice (1997).

Seebold, J.G., et al., Reaction Efficiency of Industrial Flares: The Perspective of the Past (2003).

United Nations Framework Convention on Climate Change (UNFCCC), Revisions to the Approved Consolidated Baseline Methodology ACM0010, "Consolidated baseline methodology for greenhouse gas emission reductions from manure management systems," Clean Development Mechanism, Version 02, Sectoral Scopes 13 and 15 (2006).

U.S. Department, of Agriculture Natural Resources Conservation Service, Conservation Practice Standard, Anaerobic Digester—Ambient Temperature, No. 365.

U.S. Department of Agriculture Natural Resources Conservation Service, Conservation Practice Standard, Anaerobic Digester—Controlled Temperature, No. 366.

U.S. Department of Agriculture Natural Resources Conservation Service, Conservation Practice Standard, Waste Storage Facility, No. 313.

U.S. Department of Agriculture Natural Resources Conservation Service, Conservation Practice Standard, Waste Treatment Lagoon, No. 359.

U.S. Department of Energy 1605(b) Technical Guidelines for Voluntary Reporting of Greenhouse Gas Program.

U.S. Environmental Protection Agency, Inventory of U.S. Greenhouse Gas Emissions and Sinks: 1990-2002, 1990-2003, 1990-2004, 1990-2005, 1990-2006, and 1990-2007.

U.S. Environmental Protection Agency – Climate Leaders Draft Manure Offset Protocol (Managing Manure with Biogas Recovery Systems) (October 2006).

U.S. Environmental Protection Agency – Climate Leaders Offset Methodology for Managing Manure with Biogas Recovery Systems V.1.3 (2008).

Association of State Energy Research and Technology Transfer Institutions (ASERTTI), U.S. Environmental Protection Agency AgStar Program, and U.S. Department of Agriculture Rural Development, Protocol for Quantifying and Reporting the Performance of Anaerobic Digestion Systems for Livestock Manures (January 2007).

World Resource Institute and World Business Counsel for Sustainable Development, Greenhouse Gas Protocol for Project Accounting (November 2005).

Appendix A Associated Environmental Impacts

Manure management projects have many documented environmental benefits, including air emission reductions, water quality protection, and electricity generation. These benefits are the result of practices and technologies that are well managed, well implemented, and well designed. However, in cases where practices or technologies are poorly or improperly designed, implemented, and/or managed, local air and water quality could be compromised.

With regard to air quality, there are a number of factors that must be considered and addressed to realize the environmental benefits of a biogas project and reduce or avoid potential negative impacts. Uncontrolled emissions from combustion of biogas may contain between 200 to 300 ppm NOx. The anaerobic treatment process creates intermediates such as ammonia, hydrogen sulfide, orthophosphates, and various salts, all of which must be properly controlled or captured. In addition, atmospheric releases at locations off-site where bio-gas is shipped may negate or decrease the benefit of emissions controls on-site. Thus, while devices such as Selective Catalyst Reduction (SCR) units can reduce NOx emissions and proper treatment system operation can control intermediates, improper design or operation may lead to violations of federal, state, and local air quality regulations as well as release of toxic air contaminants.

With regard to water quality, it is critical that project developers and managers ensure digester integrity and fully consider and address post-digestion management of the effluent in order to avoid contamination of local waterways and groundwater resources. Catastrophic digester failures; leakage from pipework and tanks; and lack of containment in waste storage areas are all examples of potential problems. Further, application of improperly treated digestate and/or improper application timing or rates of digestate to agricultural land may lead to increased nitrogen oxide emissions, soil contamination, and/or nutrient leaching, thus negating or reducing benefits of the project overall.

Project developers must not only follow the protocol to register GHG reductions with the Reserve, they must also comply with all local, state, and national air and water quality regulations. Projects must be designed and implemented to mitigate potential releases of pollutants such as those described, and project managers must acquire the appropriate local permits prior to installation to prevent violation of the law.

The Reserve agrees that GHG emission reduction projects should not undermine air and water quality efforts and will work with stakeholders to establish initiatives to meet both climate-related and localized environmental objectives.

Appendix B Emission Factor Tables

Table B.1. Manure Management System Components

System	Definition
Pasture/Range/ Paddock	The manure from pasture and range grazing animals is allowed to lie as deposited, and is not managed.
Daily spread	Manure is routinely removed from a confinement facility and is applied to cropland or pasture within 24 hours of excretion.
Solid storage	The storage of manure, typically for a period of several months, in unconfined piles or stacks. Manure is able to be stacked due to the
	presence of a sufficient amount of bedding material or loss of moisture by evaporation.
Dry lot	A paved or unpaved open confinement area without any significant vegetative cover where accumulating manure may be removed periodically.
Liquid/Slurry	Manure is stored as excreted or with some minimal addition of water in either tanks or earthen ponds outside the animal housing,
	usually for periods less than one year. Per IPCC Guidelines, if manure contains less than 20% dry matter it can be considered liquid.
Uncovered anaerobic	A type of liquid storage system designed and operated to combine waste stabilization and storage. Lagoon supernatant is usually used
lagoon	to remove manure from the associated confinement facilities to the lagoon. Anaerobic lagoons are designed with varying lengths of
	storage (up to a year or greater), depending on the climate region, the volatile solids loading rate, and other operational factors. The
	water from the lagoon may be recycled as flush water or used to irrigate and fertilize fields.
Pit storage below animal	Collection and storage of manure usually with little or no added water typically below a slatted floor in an enclosed animal confinement
confinements	facility, usually for periods less than one year.
Anaerobic digester	Animal excreta with or without straw are collected and anaerobically digested in a large containment vessel or covered lagoon.
	Digesters are designed and operated for waste stabilization by the microbial reduction of complex organic compounds to CO2 and CH4,
	which is captured and flared or used as a fuel.
Burned for fuel	The dung and urine are excreted on fields. The sun dried dung cakes are burned for fuel.
Cattle and Swine deep	As manure accumulates, bedding is continually added to absorb moisture over a production cycle and possibly for as long as 6 to 12
bedding	months. This manure management system also is known as a bedded pack manure management system and may be combined with a
	dry lot or pasture.
Composting – In-vessel	Composting, typically in an enclosed channel, with forced aeration and continuous mixing.
Composting – Static pile*	Composting in piles with forced aeration but no mixing.
Composting – Intensive	Composting in windrows with regular (at least daily) turning for mixing and aeration.
windrow [*]	
Composting – Passive	Composting in windrows with infrequent turning for mixing and aeration.
windrow^	
Aeropic treatment	I ne biological oxidation of manure collected as a liquid with either forced or natural aeration. Natural aeration is limited to aerobic and
	acuitative ponds and wettand systems and is due primarily to photosynthesis. Hence, these systems typically become anoxic during periods without suplicit
*Composing is the histogical	penede without summynt.

*Composting is the biological oxidation of a solid waste including manure usually with bedding or another organic carbon source typically at thermophilic temperatures produced by microbial heat production.

Source: 2006 IPCC Guidelines for National Greenhouse Gas Inventories, Chapter 10: Emissions from Livestock and Manure Management, Table 10.18: Definitions of Manure Management Systems, p. 10.49.

Table B.2. Livestock Categories and Typical Animal Mass

Livestock Category (L)	Livestock Typical Animal Mass (TAM) in kg									
	2006 - 2008	2009 - 2010								
Dairy cows (on feed)	604 ^b	680 ^c								
Non-milking dairy cows (on feed)	684 ^a	684 ^a								
Heifers (on feed)	476 ^b	407 [°]								
Bulls (grazing)	750 ^b	750 [°]								
Calves (grazing)	118 ^b	118 [°]								
Heifers (grazing)	420 ^b	351 [°]								
Cows (grazing)	533 ^b	582.5 [°]								
Nursery swine	12.5 ^ª	12.5 ^ª								
Grow/finish swine	70 ^a	70 ^a								
Breeding swine	198 ^⁵	198 [°]								

Sources for TAM: ^a American Society of Agricultural Engineers (ASAE) Standards 2005, ASAE D384.2.

^{b.} Environmental Protection Agency (EPA), Inventory of US GHG Emissions and Sinks 1990-2006 (2007), Annex 3, Table A-161, pg. A-195.

^{c.} Environmental Protection Agency (EPA), Inventory of US GHG Emissions and Sinks 1990-2010 (2012), Annex 3, Table A-191, pg. A-246.

Table B.3. Volatile Solids and Maximum Methane Potential by Livestock Category

Livestock category (L)	VS _L (kg/day/1000 kg mass)	B _{o,∟} ^b (m³ CH₄/kg VS added)
Dairy cows	See Appendix B, Tables 5a-e	0.24
Non-milking dairy cows	5.56	0.24
Heifers	See Appendix B, Tables 5a-e	0.17
Bulls (grazing)	6.04 ^b	0.17
Calves (grazing)	6.41 ^b	0.17
Heifers (grazing)	See Appendix B, Tables 5a-e	0.17
Cows (grazing)	See Appendix B, Tables 5a-e	0.17
Nursery swine	8.89 ^b	0.48
Grow/finish swine	5.36 ^b	0.48
Breeding swine	2.71 ^b	0.35

^{a.} American Society of Agricultural Engineers (ASAE) Standards 2005, ASAE D384.2, VS_L(kg/day per animal) from table 1.b (p.2) converted to (kg/day/1000 kg mass) using average Live Weight (kg)values from table 5c (p.7). ^{b.} Environmental Protection Agency (EPA) – Climate Leaders Draft Manure Offset Protocol, October 2006, Table IIa: Animal Waste Characteristics (VS, B₀, and N_{ex} rates), p. 18.

Table B.4. Biogas Collection Efficiency by Digester Type

Digester Type	Cover Type	Biogas Collection Efficiency (BCE) as a Decimal					
Covered Apparabia	Bank-to-Bank, impermeable	0.95					
Lagoon	Partial area (modular), impermeable	(0.95) x (% area covered)					
Complete mix, plug flow, or fixed film digester	Enclosed vessel	0.98					
	With flow motored for each stage	$(BCE1) \times (Gasflow1) + (BCE2) \times (Gasflow2)$					
I wo stages of differing types	with now metered for each stage	Total biogas flow					
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	No separate flow metering	$(BCE1) \times 0.7 + (BCE2) \times 0.3$					

Adapted from: U.S. EPA Climate Leaders, Offset Project Methodology for Managing Manure and Biogas Recovery Systems, 2008. Table IIf (original table has been expanded upon).

Table B.5a. 2010 Volatile Solid Default Values for Dairy Cows, Heifers, Heifers-Grazing and Cows-Grazing by State (kg/day/1000 kg mass)

State	VS Dairy Cow	VS Heifer	VS Heifer-Grazing	VS Cows- Grazing
Alabama	8.99	8.43	8.53	7.82
Alaska	7.98	8.43	9.98	8.89
Arizona	11.47	8.43	9.77	8.89
Arkansas	8.30	8.43	8.48	7.82
California	11.27	8.43	9.48	8.89
Colorado	11.54	8.43	9.27	8.89
Connecticut	10.22	8.43	8.62	7.87
Delaware	9.53	8.43	8.53	7.87
Florida	10.26	8.43	8.63	7.82
Georgia	10.03	8.43	8.49	7.82
Hawaii	8.43	8.43	9.77	8.89
Idaho	11.24	8.43	9.41	8.89
Illinois	10.19	8.43	7.78	7.47
Indiana	10.54	8.43	7.91	7.47
Iowa	10.67	8.43	7.64	7.47
Kansas	10.74	8.43	7.61	7.47
Kentucky	9.11	8.43	8.40	7.82
Louisiana	7.98	8.43	8.63	7.82
Maine	9.94	8.43	8.51	7.87
Maryland	10.00	8.43	8.51	7.87
Massachusetts	9.67	8.43	8.53	7.87
Michigan	11.42	8.43	7.83	7.47
Minnesota	10.25	8.43	7.83	7.47
Mississippi	8.59	8.43	8.53	7.82
Missouri	8.81	8.43	7.97	7.47
Montana	10.63	8.43	8.42	7.82
Nebraska	10.38	8.43	9.25	8.89
Nevada	11.08	8.43	8.01	7.47
New Hampshire	10.40	8.43	9.62	8.89
New Jersey	9.69	8.43	8.45	7.87
New Mexico	11.81	8.43	8.43	7.87
New York	10.69	8.43	9.50	8.89
North Carolina	10.54	8.43	8.61	7.87
North Dakota	9.92	8.43	8.31	7.82
Ohio	10.27	8.43	7.95	7.47
Oklahoma	9.59	8.43	7.90	7.47
Oregon	10.54	8.43	8.33	7.82
Pennsylvania	10.39	8.43	9.56	8.89
Rhode Island	9.76	8.43	8.66	7.87
South Carolina	10.02	8.43	8.61	7.87
South Dakota	10.59	8.43	8.19	7.82
Tennessee	9.56	8.43	8.12	7.47
Texas	10.87	8.43	8.21	7.82
Utah	10.86	8.43	8.42	7.82
Vermont	10.00	8.43	9.56	8.89
Virginia	10.09	8.43	8.52	7.87
Washington	11.50	8.43	8.25	7.82
West Virginia	9.15	8.43	9.73	8.89
Wisconsin	10.63	8.43	7.96	7.47
Wyoming	10.46	8.43	9.62	8.89

Source: Environmental Protection Agency (EPA). U.S. Inventory of GHG Sources and Sinks 1990-2010 (2012), Annex 3, Table A-192, page A-237.

Table B.5b. 2009 Volatile Solid Default Values for Dairy Cows, Heifers, Heifers-Grazing and Cows-Grazing by State (kg/day/1000 kg mass)

State	VS Dairy Cow	VS Heifer	VS Heifer-Grazing	VS Cows- Grazing
Alabama	9.13	8.42	8.61	7.90
Alaska	7.43	8.42	11.51	10.15
Arizona	11.35	8.42	11.23	10.15
Arkansas	8.24	8.42	8.53	7.87
California	10.97	8.42	8.13	7.70
Colorado	11.37	8.42	7.42	7.27
Connecticut	10.05	8.42	8.53	7.77
Delaware	9.54	8.42	8.29	7.77
Florida	10.08	8.42	8.71	7.90
Georgia	10.24	8.42	8.61	7.90
Hawaii	8.70	8.42	11.32	10.15
Idaho	11.07	8.42	10.86	10.15
Illinois	10.10	8.42	8.10	7.77
Indiana	10.48	8.42	8.20	7.77
Iowa	10.55	8.42	7.98	7.77
Kansas	10.77	8.42	7.38	7.27
Kentucky	8.91	8.42	8.52	7.90
Louisiana	8.01	8.42	8.68	7.87
Maine	9.86	8.42	8.43	7.77
Maryland	9.92	8.42	8.32	7.77
Massachusetts	9.71	8.42	8.43	7.77
Michigan	11.18	8.42	8.15	7.77
Minnesota	10.21	8.42	8.17	7.77
Mississippi	8.82	8.42	8.60	7.90
Missouri	8.83	8.42	8.33	7.77
Montana	10.42	8.42	7.83	7.27
Nebraska	10.36	8.42	7.42	7.27
Nevada	10.99	8.42	11.14	10.15
New Hampshire	10.30	8.42	8.37	7.77
New Jersey	9.81	8.42	8.34	7.77
New Mexico	11.74	8.42	11.06	10.15
New York	10.46	8.42	8.20	7.77
North Carolina	10.55	8.42	8.60	7.90
North Dakota	9.46	8.42	7.68	7.27
Ohio	10.06	8.42	8.28	7.77
Oklahoma	9.55	8.42	8.32	7.87
Oregon	10.36	8.42	11.03	10.15
Pennsylvania	10.25	8.42	8.20	7.77
Rhode Island	9.78	8.42	8.55	7.77
South Carolina	10.29	8.42	8.64	7.90
South Dakota	10.48	8.42	7.57	7.27
Tennessee	9.53	8.42	8.58	7.90
Texas	10.73	8.42	8.26	7.87
Utah	10.74	8.42	11.11	10.15
Vermont	9.93	8.42	8.23	7.77
Virginia	10.08	8.42	8.56	7.90
Washington	11.39	8.42	10.93	10.15
West Virginia	8.85	8.42	8.35	7.77
Wisconsin	10.46	8.42	8.33	7.77
Wyoming	10.08	8.42	7.72	7.27

Source: Environmental Protection Agency (EPA). U.S. Inventory of GHG Sources and Sinks 1990-2009 (2011), Annex 3, Table A-186, page A-225.

Table B.5c. 2008 Volatile Solid Default Values for Dairy Cows, Heifers, Heifers-Grazing and Cows-Grazing by State (kg/day/1000 kg mass)

State	VS Dairy Cow	VS Heifer	VS Heifer-Grazing	VS Cows- Grazing
Alabama	8.40	8.35	7.81	7.02
Alaska	7.30	8.35	10.05	9.02
Arizona	10.37	8.35	10.34	9.02
Arkansas	7.59	8.35	7.86	7.00
California	10.02	8.35	7.95	6.85
Colorado	10.25	8.35	7.69	6.46
Connecticut	9.22	8.35	7.67	6.90
Delaware	8.63	8.35	7.72	6.90
Florida	8.90	8.35	7.75	7.02
Georgia	9.07	8.35	7.85	7.02
Hawaii	7.00	8.35	10.26	9.02
Idaho	10.11	8.35	10.82	9.02
Illinois	9.07	8.35	8.07	6.91
Indiana	9.38	8.35	7.98	6.91
Iowa	9.46	8.35	8.27	6.91
Kansas	9.63	8.35	7.75	6.46
Kentucky	7,89	8.35	7.91	7.02
Louisiana	7,39	8.35	7.73	7.00
Maine	8,99	8.35	7.76	6.90
Maryland	9.02	8.35	7.76	6.90
Massachusetts	8,63	8.35	7.74	6.90
Michigan	10.05	8.35	7 99	6.91
Minnesota	9 17	8.35	8.04	6.91
Mississippi	8,19	8.35	7.82	7.02
Missouri	8.02	8.35	7.85	6.91
Montana	9.03	8.35	7.17	6.46
Nebraska	9.09	8.35	7.71	6.46
Nevada	9.65	8.35	10.49	9.02
New Hampshire	9.44	8.35	7.74	6.90
New Jersey	8.51	8.35	7,89	6.90
New Mexico	10.34	8.35	10.56	9.02
New York	9.42	8.35	8.02	6.90
North Carolina	9.38	8.35	7.83	7.02
North Dakota	8.40	8.35	7.43	6.46
Ohio	9.01	8.35	7.93	6.91
Oklahoma	8.58	8.35	8.08	7.00
Oregon	9.40	8.35	10.54	9.02
Pennsylvania	9.26	8.35	8.00	6.90
Rhode Island	8.94	8.35	7.60	6.90
South Carolina	9.05	8.35	7.81	7.02
South Dakota	9.45	8.35	7.50	6.46
Tennessee	8,60	8.35	7.86	7.02
Texas	9.51	8.35	8.21	7 00
Utah	9 70	8.35	10.51	9.02
Vermont	9.03	8.35	7.89	6.90
Virginia	9,02	8.35	7,87	7.02
Washington	10.36	8.35	10.77	9.02
West Virginia	8,13	8.35	7,74	6.90
Wisconsin	9.34	8.35	7,87	6,91
Wyoming	9,29	8.35	7.30	6.46
	=-			-

Source: Environmental Protection Agency (EPA). U.S. Inventory of GHG Sources and Sinks 1990-2008 (2010), Annex 3, Table A-181, page A-213.

For VS values for reporting years prior to 2008, please refer to the Livestock Project Protocol V3.0, Appendix B.

MCF Values by Temperature for Manure Management Systems																				
								Averag	je anni	ual ten	nperat	ure (°C	;)							
			Cool				Temperate													
System ^a	<10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	>28	Source and comments
Pasture/Range/Paddock			0.010								0.015							0.020		Judgment of IPCC Expert Group in combination with Hashimoto and Steed (1994).
Daily spread			0.001								0.005							0.010		Hashimoto and Steed (1993).
Solid storage			0.02				0.04									0.05		Judgment of IPCC Expert Group in combination with Amon et al. (2001), which shows emissions of approximately 2% in winter and 4% in summer. Warm climate is based on judgment of IPCC Expert Group and Amon et al. (1998).		
Dry lot			0.010								0.015							0.020		Judgment of IPCC Expert Group in combination with Hashimoto and Steed (1994).
Liquid/slurry w/natural crust cover ⁴⁰	0.10	0.11	0.13	0.14	0.15	0.17	0.18	0.20	0.22	0.24	0.26	0.29	0.31	0.34	0.37	0.41	0.44	0.48	0.50	Judgment of IPCC Expert Group in combination with Mangino et al. (2001) and Sommer (2000). The estimated reduction due to the crust cover (40%) is an annual average value based on a limited data set and can be highly variable dependent on temperature, rainfall, and composition.
Liquid/slurry uncovered	0.17	0.19	0.20	0.22	0.25	0.27	0.29	0.32	0.35	0.39	0.42	0.46	0.50	0.55	0.60	0.65	0.71	0.78	0.80	Judgment of IPCC Expert Group in combination with Mangino et al. (2001).
Uncovered anaerobic lagoon	0.66	0.68	0.70	0.71	0.73	0.74	0.75	0.76	0.77	0.77	0.78	0.78	0.78	0.79	0.79	0.79	0.79	0.80	0.80	Judgment of IPCC Expert Group in combination with Mangino et al. (2001). Uncovered lagoon MCFs vary based on several factors, including temperature, retention time, and loss of volatile solids from the system (through removal of lagoon effluent and/or solids).
Pit storage below animal confinements (<1 month)			0.03				0.03										0.03		Judgment of IPCC Expert Group in combination with Moller et al. (2004) and Zeeman (1994). Note that the ambient temperature, not the stable temperature is to be used for determining the climatic conditions.	
Pit storage below animal confinements (>1 month)	0.17	0.19	0.20	0.22	0.25	0.27	0.29	0.32	0.35	0.39	0.42	0.46	0.50	0.55	0.60	0.65	0.71	0.78	0.80	Judgment of IPCC Expert Group in combination with Mangino et al. (2001). Note that the ambient temperature, not the stable temperature is to be used for determining the climatic conditions.

Table B.6. IPCC 2006 Methane Conversion Factors by Manure Management System Component/Methane Source 'S' ³⁹

³⁹ Adapted from 2006 IPCC Guidelines for National Greenhouse Gas Inventories, Chapter 10: Emissions from Livestock and Manure Management, Table 10.17. MCF values shall be chosen based on the average temperature at the site for an entire calendar year, even if the reporting period does not exactly cover a calendar year.
⁴⁰ A "natural crust cover" is a naturally-forming layer that covers the majority of the liquid surface at a thickness sufficient to support communities of oxidizing

⁴⁰ A "natural crust cover" is a naturally-forming layer that covers the majority of the liquid surface at a thickness sufficient to support communities of oxidizing bacteria, and which persists throughout the year. Evidence of such a cover (including the area covered, thickness, and persistence) must be provided by the project developer during verification in order to justify the use of this MCF value.

Anaerobic digester			0 - 1			0 - 1 0 - 1											Should be subdivided in different categories, considering amount of recovery of the biogas, flaring of the biogas and storage after digestion. Calculation with Formula 1.			
Burned for fuel			0.10								0.10							0.10		Judgment of IPCC Expert Group in combination with Safley et al. (1992).
Cattle and swine deep bedding (<1 month)			0.03								0.03							0.30		Judgment of IPCC Expert Group in combination with Moller et al. (2004). Expect emissions to be similar, and possibly greater, than pit storage, depending on organic content and moisture content.
Cattle and swine deep bedding (>1 month)	0.17	0.19	0.20	0.22	0.25	0.27	0.29	0.32	0.35	0.39	0.42	0.46	0.50	0.55	0.60	0.65	0.71	0.78	0.90	Judgment of IPCC Expert Group in combination with Mangino et al. (2001).
Composting - in-vessel or aerated static pile ^b			0.005								0.005							0.005		Judgment of IPCC Expert Group and Amon et al. (1998). MCFs are less than half of solid storage. Not temperature dependant.
Composting - passive or intensive windrow ^b			0.005			0.010											0.015		Judgment of IPCC Expert Group and Amon et al. (1998). MCFs are slightly less than solid storage. Less temperature dependant.	
Aerobic treatment	0.00 0.00											0.00		MCFs are near zero. Aerobic treatment can result in the accumulation of sludge which may be treated in other systems. Sludge requires removal and has large VS values. It is important to identify the next management process for the sludge and estimate the emissions from that management process if significant.						
^a Definitions for manure m ^b Composting is the biolog	ianage gical ox	ment s	ystems of a sc	are pro lid was	ovided ste, incl	in Tabl uding r	e B.1. nanure	, usual	ly with	bedding	g or ar	other c	organic	carbon	source	e, typic	ally at t	thermo	philic te	emperatures produced by microbial heat production.

Table B.7. Biogas Destruction Efficiency Default Values by Destruction Device

If available, the official source tested methane destruction efficiency shall be used in place of the default methane destruction efficiency. Otherwise, project developers have the option to use either the default methane destruction efficiencies provided, or the site specific methane destruction efficiencies, for each of the combustion devices used in the project case performed on an annual basis. Site-specific values must be provided by an independent air emissions testing body that is accredited by a state or local regulatory agency, or the Stack Testing Accreditation Council. Where a state/region does not have an appropriate accreditation system or accredited service providers, the project developer may look to another state/region to find suitably qualified service providers.

Biogas Destruction Device	Biogas Destruction Efficiency (BDE)*
Open Flare	0.96 ²
Enclosed Flare	0.995 ²
Lean-burn Internal Combustion Engine	0.936 ²
Rich-burn Internal Combustion Engine	0.995 ²
Boiler	0.98 ²
Microturbine or large gas turbine	0.995 ²
Upgrade and use of gas as CNG/LNG fuel	0.95 ²
Upgrade and injection into natural gas transmission and distribution pipeline	0.98 ³
Direct pipeline to an end-user	Per corresponding destruction device

Source:

¹ Seebold, J.G., et al., Reaction Efficiency of Industrial Flares, 2003

² The default destruction efficiencies for this source are based on a preliminary set of actual source test data provided by the Bay Area Air Quality Management District. The default destruction efficiency values are the lesser of the twenty fifth percentile of the data provided or 0.995. These default destruction efficiencies may be updated as more source test data are made available to the Reserve.

³ The Revised 1996 IPCC Guidelines for National Greenhouse Gas Inventories gives a standard value for the fraction of carbon oxidized for gas destroyed of 99.5% (Reference Manual, Table 1.6, page 1.29). It also gives a value for emissions from processing, transmission and distribution of gas which would be a very conservative estimate for losses in the pipeline and for leakage at the end user (Reference Manual, Table 1.58, page 1.121). These emissions are given as 118,000kgCH4/PJ on the basis of gas consumption, which is 0.6%. Leakage in the residential and commercial sectors is stated to be 0 to 87,000kgCH4/PJ, which equates to 0.4%, and in industrial plants and power station the losses are 0 to 175,000kg/CH4/PJ, which is 0.8%. These leakage estimates are compounded and multiplied. The methane destruction efficiency for landfill gas injected into the natural gas transmission and distribution system can now be calculated as the product of these three efficiency factors, giving a total efficiency of (99.5% * 99.4% * 99.6%) 98.5% for residential and commercial sector users, and (99.5% * 99.4% * 99.2%) 98.1% for industrial plants and power stations.⁴¹

⁴¹ GE AES Greenhouse Gas Services, Landfill Gas Methodology, Version 1.0 (July 2007).

Fuel Type	Heat Content	Carbon Content (Per Unit Energy)	Fraction Oxidized	CO₂ Emission Factor (Per Unit Energy)	CO₂ Emission Factor (Per Unit Mass or Volume)
Coal and Coke	MMBTU / Short ton	kg C / MMBTU		kg CO ₂ / MMBTU	kg CO ₂ / Short ton
Anthracite Coal	25.09	28.26	1.00	103.62	2,599.83
Bituminous Coal	24.93	25.49	1.00	93.46	2,330.04
Sub-bituminous Coal	17.25	26.48	1.00	97.09	1,674.86
Lignite	14.21	26.30	1.00	96.43	1,370.32
Unspecified (Residential/ Commercial)	22.05	26.00	1.00	95.33	2,102.29
Unspecified (Industrial Coking)	26.27	25.56	1.00	93.72	2,462.12
Unspecified (Other Industrial)	22.05	25.63	1.00	93.98	2,072.19
Unspecified (Electric Utility)	19.95	25.76	1.00	94.45	1,884.53
Coke	24.80	31.00	1.00	113.67	2,818.93
Natural Gas (By Heat Content)	BTU / Standard ft ³	kg C / MMBTU		kg CO ₂ / MMBTU	kg CO ₂ / Standard ft ³
975 to 1,000 Btu / Standard ft ³	975 – 1,000	14.73	1.00	54.01	Varies
1,000 to 1,025 Btu / Standard ft ³	1,000 – 1,025	14.43	1.00	52.91	Varies
1,025 to 1,050 Btu / Standard ft ³	1,025 – 1,050	14.47	1.00	53.06	Varies
1,050 to 1,075 Btu / Standard ft ³	1,050 – 1,075	14.58	1.00	53.46	Varies
1,075 to 1,100 Btu / Standard ft ³	1,075 – 1,100	14.65	1.00	53.72	Varies
Greater than 1,100 Btu / Standard ft ³	> 1,100	14.92	1.00	54.71	Varies
Weighted U.S. Average	1,029	14.47	1.00	53.06	0.0546
Petroleum Products	MMBTU / Barrel	kg C / MMBTU		kg CO ₂ / MMBTU	kg CO ₂ / gallon
Asphalt & Road Oil	6.636	20.62	1.00	75.61	11.95
Aviation Gasoline	5.048	18.87	1.00	69.19	8.32
Distillate Fuel Oil (#1, 2, and 4) (diesel)	5.825	19.95	1.00	73.15	10.15
Jet Fuel	5.670	19.33	1.00	70.88	9.57
Kerosene	5.670	19.72	1.00	72.31	9.76
LPG (average for fuel use)	3.849	17.23	1.00	63.16	5.79
Propane	3.824	17.20	1.00	63.07	5.74
Ethane	2.916	16.25	1.00	59.58	4.14
Isobutene	4.162	17.75	1.00	65.08	6.45
n-Butane	4.328	17.72	1.00	64.97	6.70
Lubricants	6.065	20.24	1.00	74.21	10.72
Motor Gasoline	5.218	19.33	1.00	70.88	8.81
Residual Fuel Oil (#5 and 6)	6.287	21.49	1.00	78.80	11.80
Crude Oil	5.800	20.33	1.00	74.54	10.29
Naphtha (<401°F)	5.248	18.14	1.00	66.51	8.31
Natural Gasoline	4.620	18.24	1.00	66.88	7.36
Other Oil (>401°F)	5.825	19.95	1.00	73.15	10.15
Pentanes Plus	4.620	18.24	1.00	66.88	7.36
Petrochemical Feedstocks	5.428	19.37	1.00	71.02	9.18
Petroleum Coke	6.024	27.85	1.00	102.12	14.65
Still Gas	6.000	17.51	1.00	64.20	9.17
Special Naphtha	5.248	19.86	1.00	72.82	9.10
Untinished Oils	5.825	20.33	1.00	74.54	10.34
Waxes	5.537	19.81	1.00	72.64	9.58

Source: EPA Climate Leaders, Stationary Combustion Guidance (2007), Table B-2 except:

Default CO_2 emission factors (per unit energy) are calculated as: Carbon Content × Fraction Oxidized × 44/12. Default CO_2 emission factors (per unit mass or volume) are calculated as: Heat Content x Carbon Content × Fraction Oxidized × 44/12× Conversion Factor (if applicable). Heat content factors are based on higher heating values (HHV).

Type of Solids Separation	Volatile Solids Removed (fraction)			
Gravity	0.45			
Mechanical:				
Stationary screen	0.17			
Vibrating screen	0.15			
Screw press	0.25			
Centrifuge	0.50			
Roller drum	0.25			
Belt press/screen	0.50			

Table B.9. Volatile Solids Removed Through Solids Separation⁴²

Table B.10. Baseline Assumptions for Greenfield Projects⁴³

	Dairy Cattle		
Baseline Assumption	>200 Mature Dairy Cows	<200 Mature Dairy Cows	Swine Operations
Anaerobic manure storage system	Flush system into an anaerobic lagoon with >30 day retention time	Flush system into an anaerobic lagoon with >30 day retention time	Flush system into an anaerobic lagoon with >30 day retention time
Non-anaerobic manure storage system(s)	Solids storage	Solids Storage	Solids Storage
MS∟	90% lagoon 10% solids storage	50% lagoon 50% solids storage	95% lagoon 5% solids storage
Lagoon cleaning schedule	Annually, in September	Annually, in September	Annually, in September

 ⁴² U.S.EPA National Pollutant Discharge Elimination System (NPDES) Development Document, Chapter 5, "Industry Subcategorization for Effluent Limitations Guidelines and Standards". Adapted from Moser et al. (1999).
 ⁴³ The simplified assumptions contained within this table are based on the waste management system data compiled

⁴³ The simplified assumptions contained within this table are based on the waste management system data compiled by the U.S. Environmental Protection Agency for the development of Table A-194 in Annex 3 of the U.S. Inventory of GHG Sources and Sinks 1990-2010 (2012).

Appendix C Summary of Performance Standard Development

The analysis to establish a performance standard for the U.S. Livestock Project Protocol was undertaken by Science Applications International Corporation (SAIC) and independent consultant Kathryn Bickel Goldman. It took place at the end of 2006. The analysis culminated in a paper that provided a performance standard recommendation to support the Reserve's protocol development process, which the Reserve has incorporated into the protocol's eligibility rules (see Section 33). This analysis was re-visited during the development of Version 4.0 of the protocol and, although there was no recommended change to the performance standard, this appendix has been updated to reflect more recent data and analysis.

The purpose of a performance standard is to establish a threshold that is significantly better than average GHG production for a specified service, which, if met or exceeded by a project developer, satisfies the criterion of "additionality." This protocol focuses on the following direct emission reduction activity: avoiding methane emissions from the anaerobic storage and treatment of livestock manure. Therefore, in this case the methane emissions correspond to GHG production, and manure treatment/storage correspond to the specified service.

The analysis to establish the performance standard evaluated U.S.- and California-specific data on dairy and swine manure management systems. Ultimately, it recommended a practice-based/technology-specific GHG emissions performance standard – i.e. the installation of a manure digester (or Biogas Control System (BCS), more generally). The paper was composed of the following sections:

- The livestock industry in the U.S. and California
- Livestock manure management practices
- GHG emissions from livestock manure management
- Data on livestock manure management practices in the U.S. and California
- Current and anticipated regulations in California impacting manure management practices
- Recommendation for a performance threshold for livestock operations
- Considerations for baseline determinations

The initial analysis from that paper can be found in earlier versions of the U.S. Livestock Project Protocol Performance Standard Appendix.⁴⁴ In this updated Performance Standard Appendix, The additional, California-specific analysis showed adoption rates similar to the rest of the country, and thus has been removed from this document to reflect the Reserve's decision to apply the same performance standard to all operations across the United States. Beef facility and animal information has also been removed as beef operations are not currently eligible under the Protocol.

⁴⁴ Climate Action Reserve U.S. Livestock Project Protocol V1.0-3.0, Appendix C, http://www.climateactionreserve.org/how/protocols/us-livestock/

C.1 Analysis of Common Practice

C.1.1 U.S. Data on Manure Management Practices

For the initial performance standard analysis, data from the Draft EPA Climate Leaders Offset Protocol for Managing Manure with Biogas Recovery Systems (2006) were used to assess national-level manure management practices. That protocol relied on data describing farm distribution and manure management systems from the Manure Management portion of the Inventory of U.S. Greenhouse Gas Emissions and Sinks: 1990 – 2004 and used data on the number of farms by farm size and geographic location from the 2002 Census of Agriculture.⁴⁵

Information compiled for the EPA's U.S. GHG Inventory also provided a breakdown of the assumed predominant manure management systems in use for dairy and swine operations. Table C.1 and Table C.3 show data compiled for the systems in place in 2006. Table C.2 and Table C.4 show the Reserve's approximate recreation of the same analysis using the most recently published numbers.⁴⁶

A ::::::::::::::::::::::::::::::::::::		Number of Operations by Manure Management System									
Animai	P/R/P	Anaerobic Digester	Lagoon	Liquid/ Slurry	Solid Storage	Deep Pit	Total				
Dairy	72,487	62	4,453	4,345	9,494	1,147	91,989				
Swine	53,230	18	6,571	6,303	1,129	11,643	78,894				

Table C.1. Dair	v and Swine O	perations in	the U.S. b	v Manure N	Management S	vstem (2006	5)
Tuble officeur		poradono m		y manaro r	nanagonioni o	yotonn (2000	')

Source: U.S. EPA Climate Leaders Offset Protocol for Managing Manure with Biogas Recovery Systems (2008), Table I.A.

Table C.2. Dair	v and Swine O	perations in	the U.S. by	v Manure Mana	gement System	(2012)
Tuble O.L. Dun	y and Ownie O	perations in	the 0.0. b	y manare mana	gernerit Oystern	(2012)

		Number of Operations by Manure Management System										
Animal	P/R/P	Anaerobic Digester	Lagoon	Liquid/ Slurry	Solid Storage	Deep Pit	Total					
Dairy	56,075	185*	3,332	3,261	6,263	775	69,890					
Swine	55,110	30	5,740	4,641	892	9,029	75,442					

Source: U.S. EPA GHG Inventory (2012), U.S. EPA AgSTAR Database (2012), U.S. Dept. of Agriculture, 2007 Census of Agriculture

* There are three systems in operation that digest both swine and dairy manure. For the purpose of this analysis they are considered as dairy.

⁴⁵ EPA GHG Inventory Reports in subsequent years (including 2010) still rely on the results of the 2002 Census for this data.

⁴⁶ The equivalent analysis based on the 2007 census is unavailable in the same format from the EPA Climate Leaders program. The Reserve performed a similar analysis using data for manure management from the Inventory of U.S. Greenhouse Gas Emissions and Sinks (2012), data on the prevalence of anaerobic digesters from the U.S. EPA's AgSTAR database (Sept. 2012), and data on the number of farms by farms size and geographic location from the 2007 Census of Agriculture, the results of which are Table C.2 and Table C.4. This analysis may not have been performed in precisely the same way as the EPA Climate Leaders Program analysis; however it serves the purpose of evaluating the current state of the dairy and swine manure management practices. The following classification assumptions were made: 1. digester projects associated with farms of size are classified by based on other information in the AgSTAR database, if available, or assumed to be in the medium size class; 2. farms employing anaerobic digesters are subtracted from the USDA counts based on "Baseline System" or other information in the AgSTAR database, if available. Where the "Baseline System" is categorized as "Storage Tank or Pond or Pit," the farm is assumed to belong in the "Liquid/Slurry" category for Dairy and the "Deep Pit" category for Swine.

The distribution of livestock across different sized operations can be an important criterion when developing a livestock manure management performance standard. There is a general relationship between manure management practices and operation size, where larger operations (in terms of livestock numbers) tend to use manure management systems that treat and store waste in liquid form (i.e. flush or scrape/slurry systems), particularly in dairy and swine operations.⁴⁷

Animal	Number of Operations by Farm Size and Manure Management System										
	Farm Size	P/R/P	Anaerobic Digester	Lagoon	Liquid/ Slurry	Solid Storage	Deep Pit	Total			
Dairy	≥500 head	320	48	1,614	675	245	-	2,902			
	200-499	3,213	9	617	652	54	-	4,546			
	1-199	6,8954	5	2,223	3,017	9,195	1,147	84,541			
Swine	≥2000 head	-	14	2,581	1,084	297	2,774	6,749			
	200-2000	-	3	3,990	5,219	832	8,869	18,913			
	1-199	53,230	1	-	-	-	-	53,231			

 Table C.3. Dairy and Swine Operations by Size and Manure Management System (2006)

Source: U.S. 2002 Census of Agriculture.

Table C.4. Dair	y and Swine O	perations by	Size and Manure	Management S	vstem (2012)
					J - · - V	- /

Animal	Number of Operations by Farm Size and Manure Management System										
	Farm Size	P/R/P	Anaerobic Digester	Lagoon	Liquid/ Slurry	Solid Storage	Deep Pit	Total			
Dairy	≥500 head	312	154	1,824	710	284	-	3,284			
	200-499	3205	25	502	531	44	-	4,307			
	1-199	52559	6	1,006	2,020	5,934	775	62,299			
Swine	≥2000 head	-	26	3,182	1,295	358	3,345	8,206			
	200-2000	-	3	2,557	3,347	534	5,685	12,125			
	1-199	55,110	1	-	-	-	-	55,111			

Source: U.S. EPA GHG Inventory (2012), U.S. EPA AgSTAR Database (2012), U.S. Dept. of Agriculture, 2007 Census of Agriculture.

According to the Interim Draft Winter 2006 AgSTAR Digest used for the initial analysis, of 91,988 dairy and 78,894 swine farm operations in the United States, a total of 80 anaerobic digesters were in operation: 62 (0.07%) for dairy manure and 18 (0.02%) for swine manure.

Data were also disaggregated in the Climate Leaders protocol to determine whether digester installation was a common practice in any animal production operation size range. As was shown in Table C.3, even at large animal production operations, very few digester systems were in place. At dairy farms with ≥500 head, only 1.7% of manure management systems included digesters, and of swine farms with >2000 head, only 0.2% had digesters.

⁴⁷ U.S. Inventory of Greenhouse Gas Emissions and Sinks: 1990-2004 (and earlier editions), US Environmental Protection Agency, Report # 430-R-06-002, April 2006.

The most current information from the AgSTAR database (September 2012) shows that the number of anaerobic digesters in operation or under construction has nearly tripled at dairy farms and increased by more than 50% at swine farms. In terms of prevalence as a manure management practice across farms however, the practice remains the exception, rather than the rule. Currently there are 185 digesters at dairy farms (0.14%), and 30 at swine farms (0.03%). The number of digesters at the largest farms increased the most significantly, with 154 digesters at dairy farms with \geq 500 head (4.69%), and 26 at swine operations with \geq 2000 head (0.32%). Of the 185 dairy farms with anaerobic digesters in operation, 84 have participated in GHG offset programs; eight of the 30 swine farms with anaerobic digester have participated in GHG offset programs. Table C.5 shows the distribution and percentages of digesters in operation or under construction by size farm, compared to farms with other manure management practices; Table C.6 shows the same distribution, but does not include the digesters at farms participating in GHG offset programs.

The "natural" market penetration of anaerobic digesters on livestock facilities can be considered as the percentage of farms that choose this management option without the incentive provided by GHG offset programs. Table C.6 shows that the natural market penetration of anaerobic digesters on dairy and swine facilities in the U.S. remains very low. The highest rate of adoption is among dairy farms with \geq 500 head, at 2.31%. However, this number conservatively includes anaerobic digestion facilities that are currently under construction. As many if not all of these facilities may actually be installed in response to GHG offset programs (which is often not known until they are operational and become publicly listed in one of these programs), even this small rate of adoption is likely to be overestimated by this analysis. If the anaerobic digesters that are under construction are all assumed to be GHG offset projects, then the natural market penetration of anaerobic digesters on dairy facilities of \geq 500 head drops to 1.71%.

Animal	Number of Operations by Farm Size and Manure Management System									
	Farm Size	P/R/P	Anaerobic Digester	Lagoon	Liquid/ Slurry	Solid Storage	Deep Pit	Total		
Dairy	≥500 head	312 9.49%	154 4.69%	1,824 55.53%	710 21.63%	284 8.66%	-	3,284		
	200-499	3,205 74.41%	25 0.58%	502 11.66%	531 12.32%	44 1.03%	-	4,307		
	1-199	52,559 84.37%	6 0.01%	1,006 1.61%	2,020 3.24%	5,934 9.52%	775 1.24%	62,299		
	Total	56,075 80.23%	185 0.26%	3,332 4.77%	3,261 4.67%	6,263 8.96%	775 1.11%	69,890		
Swine	≥2000 head	-	26 0.32%	3,182 38.78%	1,295 15.78%	358 4.37%	3,345 40.76%	8,206		
	200-1999	-	3 0.02%	2,557 21.09%	3,347 27.60%	534 4.40%	5,685 46.88%	12,125		
	1-199	55,110 99.998%	1 0.002%	-	-	-	-	55,111		
	Total	55,110 73.05%	30 0.04%	5,740 7.61%	4,641 6.15%	892 1.18%	9,029 11.97%	75,442		

Table C.5	Dairy and Swine (Operations h	v Size and Manure	Management Sy	vstem (2012)
	Jaily and Swine v	Jperations b	y Size and Manure	Manayement O	ysienn (2012)

Source: U.S. EPA GHG Inventory (2012), U.S. EPA AgSTAR Database (2012), U.S. Dept. of Agriculture, 2007 Census of Agriculture.

Animal	Number of Operations by Farm Size and Manure Management System							
	Farm Size	P/R/P	Anaerobic Digester	Lagoon	Liquid/ Slurry	Solid Storage	Deep Pit	Total
Dairy	≥500 head	312 9.73%	74 2.31%	1,824 56.91%	710 22.17%	284 8.88%	-	3,204
	200-499	3,205 74.47%	21 <i>0.4</i> 9%	502 11.67%	531 12.33%	44 1.03%	- -	4,303
	1-199	52,559 84.37%	6 0.01%	1,006 <i>1.61%</i>	2,020 3.24%	5,934 9.52 <i>%</i>	775 1.24%	62,299
	Total	56,075 80.33%	101 <i>0.14%</i>	3,332 4.77%	3,261 <i>4</i> .67%	6,263 8.97%	775 1.11%	69,806
Swine	≥2000 head	-	19 0.23%	3,182 38.81%	1,295 <i>15.79%</i>	358 <i>4</i> .37%	3,345 40.80%	8,199
	200-1999	-	2 0.02%	2,557 21.09%	3,347 27.60%	534 <i>4.40%</i>	5,685 46.89%	12,124
	1-199	55,110 99.998%	1 0.002%	-	-	-	- -	55,111
	Total	55,110 73. <i>0</i> 6%	22 0.03%	5,740 7.61%	4,641 6. <i>15%</i>	892 1.18%	9,029 11.97%	75,434

Table C.6. Dairy and Swine Operations by Size and Manure Management System (2012)Not including those participating in a GHG offset program.

Source: U.S. EPA GHG Inventory (2012), U.S. EPA AgSTAR Database (2012), U.S. Dept. of Agriculture, 2007 Census of Agriculture, open GHG offset program registries.

Finally, as anaerobic digesters are most likely to be installed on livestock facilities that already utilize liquid-based manure management systems, it is useful to examine the market penetration among only these facilities. Table C.7 shows that, among the total facilities utilizing liquid manure management systems, the natural market penetration of anaerobic digesters is 1.35% for dairy farms and 0.11% for swine farms.⁴⁸ The highest rate, seen among dairy farms of ≥500 head, is 2.84%. This continues to be an extremely low rate of adoption for anaerobic digestion technology.

⁴⁸ There is seemingly 100% market penetration on swine farms with <200 animals, due to the fact that there was only one farm in the dataset utilizing liquid manure management, and it also had an anaerobic digester. A greater trend of adoption of anaerobic digestion cannot be drawn from this single farm.

Table C.7. Dairy and Swine Operations Utilizing Liquid Manure Management, by Size and Manure Management System (2012)

Animal	Number of Operations by Farm Size Using Anaerobic Manure Management (Excluding GHG Offsets)					
	Farm Size	Anaerobic Digester	Liquid Manure Management	Total		
Dairy	≥500 head	74 2.84%	2,534 97.16%	2,608		
	200-499	21 1.99%	1,033 <i>98.01%</i>	1,054		
	1-199	6 0.16%	3,800 <i>99.84%</i>	3,806		
	Total	101 1.35%	7,367 98.65%	7,468		
	≥2000 head	19 <i>0.24%</i>	7,822 99.76%	7,841		
Swine	200-1999	2 0.02%	11,589 <i>99.98%</i>	11,591		
Swine	1-199	1 <i>100.00%</i>	-	1		
	Total	22 0.11%	19,410 <i>99.89%</i>	19,432		

Not including those participating in a GHG offset program.

C.1.2 U.S. and State Manure Management Regulations

As a part of the Reserve's protocol management, regulatory developments are tracked through, among other outreach and research activities, reporting on regulatory requirements by project developers and verification bodies in the verification process. Of the farms with an anaerobic digester that have participated in GHG offset projects documented in EPA's AgSTAR program, 65 have listed their projects under the Reserve's U.S. Livestock Project Protocol. Twenty-seven projects have been registered with the Reserve, i.e., successfully undergone the verification process. This includes projects in four of the five top dairy producing states, namely, California, Wisconsin, Texas and Idaho. In states where registered Reserve projects are located, no state or federal regulations have been found that would require the use of a BCS.

C.2 Performance Standard Recommendation

The original SAIC report recommended that a performance standard apply to the control of methane emissions from dairy and swine livestock operations in the U.S. and California. In particular, the performance standard should be a technology-specific threshold that dairy or swine operators would meet. The recommended threshold would be the installation of a BCS (e.g. an anaerobic digester).

The report found that even under favorable conditions digesters were found on less than 1% of the dairies in California, which was found to be representative of the U.S. market; and that if a dairy operator chose to install a digester then the farmer would be managing waste in the 99th percentile. This constitutes above and beyond common practice. The report also found that the main barrier inhibiting the installation and use of digesters was cost. Cost studies performed by EPA's AgSTAR program and the California Electricity Commission indicated that significant subsidies and/or incentives were needed to encourage additional digester installations.

The Reserve adopted this performance standard recommendation based on the data available at the time of the SAIC report. While the number of anaerobic digesters has increased significantly, the market penetration of BCS technology remains quite low, especially among those farms which are not receiving revenues from GHG offset markets. Today a dairy operator who chooses to install a digester would be managing waste in the 98th percentile—a modest increase since the original analysis, but hardly a significant shift in common practice. Furthermore, cost continues to inhibit wider adoption of BCS technologies according to a recent EPA report on the status of anaerobic digester adoption.⁴⁹ In light of these facts, the Reserve will not alter the current performance standard, but will continue to monitor market developments in the future.

C.3 Renewable Energy Credits and Other Revenue Opportunities for Biogas-to-Energy Projects

Along with carbon credits, there are opportunities for farms installing digesters to earn additional revenues from a variety of sources that support renewable energy generation. These include loans and grants for developing biogas-to-energy projects and the sale of Renewable Energy Certificates (RECs) for use in a renewable portfolio standard (RPS) or a renewable portfolio goal (RPG)⁵⁰.

When considering additionality and the ability to generate RECs and CRTs from a livestock project, it is important to remember that the REC and CRT are created by two different but related activities. The REC is awarded for generating renewable electricity from the biogas collected by the BCS, whereas the CRT is awarded for the climate benefit created by the conversion of CH_4 in the biogas into CO_2 through combustion of the biogas. Under this protocol, projects are not required to generate electricity with collected biogas or send it to a natural gas pipeline. Rather, they are only required to destroy the biogas. So while a project may generate renewable electricity with its biogas, renewable energy generation is not an activity required or credited under this protocol.

As there are a number of active RPS, RPG and voluntary REC programs nationwide, the availability of revenue from the sales of RECs is inherently represented in the data analyzed to set the performance standard. Since this analysis shows that the installation of a digester is not common practice at dairy and swine farms, the Reserve does not limit a project's ability to generate or sell RECs. Due to the numerous barriers to implementation of an anaerobic digester project, their success typically relies on a complex array of factors, including multiple incentive program. Renewable energy incentives alone have not significantly increased the natural market penetration of these projects.

When considering additionality and the availability of public dollars to support the development of biogas-to-energy projects, the Reserve has identified numerous state and local programs to support such projects through grants, loans and payments. Although the Reserve's performance standard tests do not require individual project assessments of financial viability or returns, they are designed to reflect these factors in determining which projects are additional. Even with the funds available, the installation of anaerobic digesters according to this protocol is still very rare. Thus, even if a project does receive a grant or loan to support the generation of renewable

http://www.epa.gov/agstar/documents/digester_status_report2010.pdf

⁴⁹ U.S. Anaerobic Digester Status Report, October 2010,

⁵⁰ Whereas compliance with an RPS is mandatory, RPGs set voluntary compliance targets.

energy from a biogas project, the performance standard and rules set forth in this protocol should ensure the additionality of the CRTs generated.

Beyond grants and loans for biogas-to-energy projects, there are two nationwide payment programs administered by USDA Natural Resource Conservation Service (NRCS) that support the installation of anaerobic digesters. Authorized by the 2008 Farm Bill, the Environmental Quality Incentives Program (EQIP), and the Chesapeake Bay Watershed Initiative (CBWI) are programs that provide payments to support the installation of a BCS and are implemented at the state- and county-level. NRCS expressly allows the sale of environmental credits from enrolled lands,⁵¹ but does not provide any additional guidance on ensuring the environmental benefit of any mitigation payment stacked with an NRCS payment.

All NRCS programs share a common set of conservation practice standards that contain information on why and where the practice is to be applied, and set forth the minimum quality criteria that must be met during the application of that practice in order for it to achieve its intended purpose(s).

NRCS Conservation Practice Standard 366 – *Anaerobic Digester* (CPS 366) provides assistance to farmers for the treatment of manure and other byproducts of animal agricultural operations for one or more of the following reasons: to capture biogas for energy production, to manage odors, to reduce the net effect of greenhouse gas emissions, or to reduce pathogens.⁵²

Data obtained from NRCS show that less than 0.3% of farms eligible for funding under CPS 366 (i.e., farms with anaerobic operations) have received NRCS funds to install a BCS.⁵³ In practice, only 9% of the farms that installed BCS since 2004 have received NRCS funds. Because the installation of anaerobic digesters is expensive, uncommon and generally not already funded by NRCS programs, the use of NRCS payments to help finance project activity is allowed under this protocol.

⁵¹ EQIP, 7 CFR §1466.36; CSP, 7 CFR §1470.37.

⁵² Natural Resources Conservation Service. (September 2009). Conservation Practice Standard, Anaerobic Digester, Code 366. State-specific conservation practice standards can be downloaded from http://efotg.sc.egov.usda.gov//efotg_locator.aspx.

http://efotg.sc.egov.usda.gov//efotg_locator.aspx. ⁵³ Based on 2004-2011 data obtained from NRCS Resource Economics, Analysis and Policy Division through personal communication.

Appendix D Data Substitution

This appendix provides guidance on calculating emission reductions when data integrity has been compromised either due to missing data points or a failed calibration. No data substitution is permissible for the operational status of destruction devices. Rather, the methodologies presented below are to be used only for the methane concentration and flow metering parameters. If operational data are missing for a destruction device, then the device shall be assumed to have been inoperable, and will be assigned a destruction efficiency of zero for that period.

D.1 Missing Data

The Reserve expects that projects will have continuous, uninterrupted data for the entire verification period. However, the Reserve recognizes that unexpected events or occurrences may result in brief data gaps.

The following data substitution methodology may be used only for flow and methane concentration data gaps that are discrete, limited, non-chronic, and due to unforeseen circumstances. Data substitution can only be applied to methane concentration *or* flow readings, but not both simultaneously. If data are missing for both parameters, no reductions can be credited.

Further, substitution may only occur when the following is true:

- 1. For methane concentration substitution, flow rates during the data gap must be consistent with normal operation.
- 2. For flow substitution, methane concentration rates during the data gap must be consistent with normal operations.

If corroborating parameters fail to demonstrate any of these requirements, no substitution may be employed. If the requirements above can be met, the following substitution methodology maybe applied:

Duration of Missing Data	Substitution Methodology
Less than six hours	Use the average of the four hours immediately before and following the outage
Six to 24 hours	Use the 90% lower or upper confidence limit of the 24 hours prior to and after the outage, whichever results in greater conservativeness
One to seven days	Use the 95% lower or upper confidence limit of the 72 hours prior to and after the outage, whichever results in greater conservativeness
Greater than one week	No data may be substituted and no credits may be generated

Note: It is conservative to use the upper confidence limit when calculating emissions from the BCS (Equation 5.6); however it is conservative to use the lower confidence limit when calculating the total amount of methane that is destroyed in the BCS Equation 5.10.

For periods when it is not possible to use data substitution to fill data gaps, no emission reductions may be claimed. The methane flow volume for these days shall be zero, and the number of reporting days for that month shall be reduced to exclude the days of missing data. This guidance is not to be used for venting events.

Appendix E Development of the B₀ Sampling and Analysis Methodology

With the release of Livestock Protocol Version 4.0, the Reserve has adopted a novel methodology for the sampling and analysis of livestock manure to determine maximum methane potential. In all previous versions of the protocol, the value of this term was defined by the default options provided in Table B.3, which were themselves sourced from the EPA Climate Leaders Draft Manure Offset Protocol. Other than a change in the value of the default for Dairy Cows with Version 2.1 from a "low roughage" value to a "high roughage" value, these default values have not changed since the first version of the protocol was adopted. Reserve staff have received feedback from stakeholders that in many cases, the default value for a particular animal category, especially Dairy Cows, is excessively conservative. Based on this feedback, the Reserve initiated a process to explore the options for updating the default values for maximum methane potential (B₀). After review of existing methodologies and literature related to manure methane potential, the Reserve determined that there is currently not a clear basis for establishing different default values. However, direct sampling and analysis were identified as an option that could be immediately provided as an alternative to the existing default values.

In 2009 the Reserve adopted the Organic Waste Digestion project protocol (updated to Version 2.0 in 2011). This protocol introduced a procedure for the determination of site-specific B_0 value for organic wastewater streams (OWD V2.0, Section 6.1.3.2). These requirements formed the basis for the development of a sampling and analysis procedure for livestock projects.

In early September, 2012, the Reserve solicited stakeholder interest for participation in the development process for this new methodology. A diverse group of 36 stakeholders representing carbon project developers, academia, government, livestock industry, GHG verification bodies, and others, responded to this request. These stakeholders then received a memorandum detailing the proposed methodology and were invited to a webinar on September 19, 2012 to provide feedback and engage in discussion. 22 individuals participated in the webinar discussion, providing a great deal of feedback and suggestions for improvement.

In addition to the public stakeholder consultation, Reserve staff worked directly with experts in industry and academia to further refine the methodology. The goal was to identify a sampling and testing regime that could consistently provide accurate estimates of the B_0 value of different manure streams, and that would be reasonably practical for implementation. The major considerations and decisions are addressed below.

Sampling Schedule

The sampling procedure requires that six samples be taken at regular intervals throughout the day. These individual samples are then combined into one composite sample to represent that event. The sampling procedure in the OWD protocol calls for 10 samples spaced out over at least one week. In consultation with expert stakeholders, it was determined that livestock manure will be less variable over such short timescales, and that the collection of multiple samples in a single day would be sufficient to control for sample variability and error. A more onerous sampling requirement would introduce additional resourcing requirements and costs disproportionate to any reduction in uncertainty/error.

The procedure also requires that the sampling event take place between the months of August through November (inclusive). The Reserve has limited the applicability of this procedure to dairy facilities, and expects that it will mainly be used for the determination of a site-specific B₀

for dairy cows. Thus, the timing of the sampling procedure is designed to avoid overestimating the B₀ value for this particular livestock category. Academic experts advised the Reserve that the methane generating potential of dairy cow manure tends to be positively correlated with milk production.⁵⁴ To ensure that the average B₀ value for the year is not overestimated, it is appropriate to avoid sampling the manure during periods of above-average milk production. Reserve staff used data from the National Agricultural Statistics Service⁵⁵ to examine monthly milk production trends. For the years 1998-2011, the milk production for each month (in lb/head) was compared to the average monthly milk production for that year. This process highlighted the months with above or below-average milk production, while controlling for the overall trend of increasing milk production year-over-year. Figure E.1 shows the results of this analysis and the consistent pattern of milk production during this 14 year period.



Figure E.1. Monthly Milk Production Trends as a Percent Change Over Annual Average Monthly Milk Production (1998-2011)

Based on this analysis the Reserve has limited the sampling period to August through November. These months consistently exhibit average- to below-average milk production, which should result in a conservative estimate of the annual average B_0 value.

Sample Source

The procedure instructs the user to obtain a manure sample that represents only a single animal category, prior to mixing with other residues (except for flush water in the case of flush systems). While certain stakeholders indicated through public comment that they would prefer to sample the entire waste stream as it enters the digester, there are two main reasons why this requirement was not amended:

⁵⁴ In the future, it may be possible to develop a default methane potential that is based directly on monthly milk production, though additional research is needed.

⁵⁵ Accessed from the USDA website at <u>http://quickstats.nass.usda.gov/</u>.

- 1. The waste stream entering the digester may contain ineligible materials which, while permitted to be processed by the project BCS, should not be represented in the quantification of baseline emissions.
- 2. The baseline quantification model is run on a monthly basis, using the actual animal population figures for that month. The relative populations of different animal categories may change during the year, resulting in an overall B₀ value for the manure from that facility that is variable through time. To use a composite B₀ value, representative of multiple animal categories, would create quantification inaccuracies if relative populations change from one month to the next (see Table E.1).

Animal Category	B₀ Value	Population in Month 1	Population in Month 2	Population in Month 3
Dairy Cows	0.24	2,000	800	3,000
Heifers	0.17	500	2,000	200
Calves	0.17	500	1,200	0
	Composite B ₀ Value	0.22	0.18	0.24

Table F 1 Effects	of Relative Po	nulation Size	on Composite	R _a Value
		pulation Size		

There is an additional step for dairies that utilize a flush system for manure management, as the flush water is typically composed of some type of wastewater, which could have a significant methane potential. For these systems it is necessary to also sample the flush water inlet point prior to mixing with the manure, so that the methane potential of the flush water can then be subtracted from the methane potential of the sample.

Laboratory Analysis

The Reserve undertook research to determine whether standard procedures/processes existed for the professional analysis of B_0 potential. This research revealed that while there is currently no standard laboratory certification scheme within the US pertaining to this type of analysis, there are commonly-accepted methods for undertaking the relevant biochemical methane potential (BMP) analysis itself. The requirements to document a laboratory's experience and standard operating procedures were introduced to ensure rigor and consistency among testing bodies.

The Reserve consulted with commercial and university testing laboratories regarding the requirements for the biochemical methane potential (BMP) assay. The resulting requirements closely resemble the standard procedures of existing laboratories. It is necessary for the protocol to prescribe at least basic parameters for the BMP assay in order to ensure consistency among projects that hire different laboratories. The inclusion of a control assay was suggested by multiple laboratories as an important quality check on the viability of the seed inoculum that is used for the BMP assay.

Stakeholder Participation

The Reserve would like to thank the following stakeholders, in addition to others not listed here, for their participation in the research and development of this methodology.

David Belcher	Camco
Michael Carim	First Environment, Inc.
Dr. Craig Frear	Washington State University
Noel Gurwick	Smithsonian Environmental Research Center
Karen Haugen-Kozyra	The Prasino Group
Cortney Itle	Eastern Research Group, Inc.
Dr. Xiaomei Li	XY Green Carbon
Dr. John H. Martin, Jr.	Hall Associates
Carl Morris	Joseph Gallo Farms
Dr. Scott Subler	Environmental Credit Corp.
Peter Weisberg	The Climate Trust

